



Florida Department of Transportation

RICK SCOTT
GOVERNOR

5007 Northeast 39th Avenue
Gainesville, Florida 32609

ANANTH PRASAD, P.E.
SECRETARY

June 4, 2012

This Memo Has Expired

MATERIALS BULLETIN NO. 08-12
DCE MEMORANDUM NO. 20-12
(FHWA Approved 6/04/12)

**TO: DISTRICT MATERIALS RESEARCH ENGINEERS
DISTRICT CONSTRUCTION ENGINEERS**

FROM: Timothy J. Ruelke, P.E., Director, Office of Materials
David A. Sadler, P.E., Director, Office of Construction

Handwritten signatures of Timothy J. Ruelke and David A. Sadler in black ink.

COPIES: Jim Musselman, Bob Burleson (FTBA), Jim Warren (ACAF),
Chris Richter (FHWA), Chad Thompson, Heather Dean, Rafiq Darji, Tom Byron

SUBJECT: MODIFICATIONS TO SECTION 334 SUPERPAVE ASPHALT CONCRETE

The Superpave mix design requirement related to the initial number of gyrations (N_{ini}) is eliminated from the mix design requirements provided in subarticle 334-3.2.5 of the Department's Specifications and referenced to AASHTO M 323.

This change will allow for additional sources of fine aggregate to be used without affecting performance.

This memorandum serves as a blanket approval to process this specification change for projects let on or after the date of this memorandum but prior to the official specification change, which will appear in the January 2013 workbook.

For any questions concerning this matter, please contact Greg Sholar, 352.955.2920, at the State Materials Office.

TR/DS/gs