



# Earthwork Operations

## Construction Academy

**Dino Jameson**  
**Soils Field Operations Engineer**  
**State Materials Office**

# Geotechnical Engineering Unit



- **From beginning to end, Geotechnical Materials is involved with the life of a project:**

- Planning, Development, and Engineering Phase (PD&E)
- Design Phase
- Construction Phase
- Maintenance Phase





## Geotechnical Sections at State Materials



## Objectives

- Overview of Soils Mechanics
- Overview of Earthwork Lab/Field Testing
- Overview of Earthwork Standard Contract Documents
- Overview of Recording of Earthwork Construction Data
  - Earthwork Records System (ERS)
    - MAC-ERS
    - Non-Electronic Logbook
  - Brief Introduction to Plots Coding

## Soil Mechanics

- **Soil Mechanics is a discipline of Civil Engineering involving the study of the physical properties of soil.**
  - Some of these properties of soil are the grain-size distribution, permeability, compressibility, shear strength, and load bearing capacity.
- **Soils Engineering is the application of soil mechanics in real life scenarios**
- **Geotechnical Engineering is a subdiscipline of civil engineering that involves the application of soil mechanics and rock mechanics.**

## Soil Identification

- Soil particle size vary over a wide range and generally referred to as gravel, sand, silt, or clay, depending on the predominant size of particles within the soil.
- Peat and muck (dirt) may have visual characteristics of soil but are organic matter that are accumulated from decayed animals/vegetations.
- Several organizations have developed a soil classification system to describe soils by their particle size, consistency, and behavior.
- Massachusetts Institute of Technology (MIT), U.S. Department of Agriculture (USDA), ASTM - Unified Soil Classification System (USCS), AASHTO, etc.

# Soil Classification


- In construction operation, the Department uses AASHTO Soil Classification System to classify soil

General Classification	Granular Materials (35 Percent or Less Passing 75 μm)							Silt-Clay Materials (More Than 35 Percent Passing 75 μm)			
Group Classification	A-1		A-3	A-2				A-4	A-5	A-6	A-7
	A-1-a	A-1-b		A-2-4	A-2-5	A-2-6	A-2-7				A-7-5, A-7-6
Sieve analysis, percent passing:											
2.00 mm (No. 10)	50 max	—	—	—	—	—	—	—	—	—	—
0.425 mm (No. 40)	30 max	50 max	51 min	—	—	—	—	—	—	—	—
75 μm (No. 200)	15 max	25 max	10 max	35 max	35 max	35 max	35 max	36 min	36 min	36 min	36 min
Characteristics of fraction passing 0.425 mm (No. 40):											
Liquid limit	—	—	—	40 max	41 min	40 max	41 min	40 max	41 min	40 max	41 min
Plasticity index	6 max	NP	NP	10 max	10 max	11 min	11 min	10 max	10 max	11 min	11 min <sup>a</sup>
Usual types of significant constituent materials	Stone fragments, gravel and sand		Fine sand	Silty or clayey gravel and sand				Silty soils		Clayey soils	
General rating as subgrade	Excellent to Good							Fair to Poor			

<sup>a</sup> Plasticity index of A-7-5 subgroup is equal to or less than  $LL - 30$ . Plasticity index of A-7-6 subgroup is greater than  $LL - 30$ . (See Figure 2.)

# AASHTO Soil Classification


- The following two laboratory tests are performed in order to use the AASHTO soil classification system:
  - Sieve Analysis (AASHTO T88)
    - AASHTO T27/FM 1-T11 for material used for retaining wall systems
    - Atterberg Limits (AASHTO T89 & T90)
- In addition, AASHTO T 267 Organic Content





## Moisture-Density Relationship of Soil


- The amount of water in soil affects its load-carrying capacity.
- Very dry soil becomes powdery, very wet soil becomes mud, but the proper amount of water can act as a lubricant to bond soil particles together.
- In optimum moisture condition, the soil particles will be densely packed resulting in increased density)



**TOO DRY-**  
particles rest  
loosely against  
each other.



**PROPER MOISTURE-**  
moisture helps hold  
particles together.




**TOO WET-**  
particles tend  
to “float” in  
liquid.

## Proctor Theory

- The purpose of the Proctor test is to experimentally determine the optimal moisture content at which a given soil type will become most dense and achieve its maximum dry density.
- It establishes a density standard that a Contractor must achieve in the field represented as a compaction percentage for a given material.
- With a known volume (standard mold), the soil is compacted to the point where the air could be completely removed, simulating the effects of a in-situ (on site) conditions.
- From this, the dry density could be determined by measuring the weight of the soil after compaction, calculating the moisture content, and calculating the dry density.


# Proctor Curve



Proctor Data	
Dry Density (pcf)	Moisture (%)
109.0	9.0
110.4	10.0
111.5	11.0
110.0	12.0

# Proctor Curve

MAXIMUM DENSITY (B)  
at  
OPTIMUM MOISTURE  
CONTENT (A)




This is the maximum achievable density for the compactive effort.



## Nuclear Density/SPEEDY Moisture

- To determine the in-place density and moisture of the soil for comparison to the maximum dry density determined by the Proctor test



## Proctor Theory

- Determine Dry Density

$$\text{Dry Density} = \frac{\text{Wet Density}_{\text{gauge}}}{1 + \% \text{ Moisture}}$$

- Determine the Percent Maximum Density

$$\% \text{ Max. Density} = \frac{\text{Dry Density} \times 100}{\text{Proctor Maximum Density}}$$

## Earthwork Laboratory Tests

- **AASHTO M145 – Soil Classification**

- AASHTO T 88 – Gradation
- AASHTO T 89 – Liquid Limit
- AASHTO T 90 – Plastic Limit

- **FM1-T 267 Organic Content**

- **FM 1-T099/T180 Standard/Modified Proctor**

- **FM 5-515 – Limerock Bearing Ratio**

- **AASHTO T215 – Constant Head Permeability**

- **FM 5-550 – pH**

- **FM 5-551 – Resistivity**

- **FM 5-552 – Chlorides**

- **FM 5-553 – Sulfates**

Most  
Common

A red arrow points from the "Most Common" box to the first four items in the list: AASHTO M145, AASHTO T 88, AASHTO T 89, and AASHTO T 90.

## **Earthwork Field Tests**


- **FM 1-T 310 – Nuclear Density**
- **FM 5-507 – Moisture using SPEEDY**
- **Stabilizing Mixing Depth**
- **FM 5-534 – Rock Base Thickness**



## Objectives Check Point

- Overview of Soils Mechanics ✓
- Overview of Earthwork Lab/Field Testing ✓
- Overview of Earthwork Standard Contract Documents

# Governing Order of Contract Documents





# Earthwork Operation Standard Contract Documents

INDEX A-Z

Search FDOT...

Q Search

OFFICES

MAPS & DATA

CONTACT

ABOUT

PROJECTS

RESOURCES

NEWSROOM

CAREERS

Home / materials / administration / resources / library / publications / materialsmanual

Materials Manual

The Materials Manual contains the instructions needed to complete Quality Assurance and Materials Acceptance for Florida Department of Transportation contracts. This web page, which displays only the most recent versions of the files, has been divided into Volumes I and II as shown below. **Volume I (V1)** includes Department Personnel Responsibilities and **Volume II (V2)** includes Non-Department Personnel Responsibilities. For questions or comments regarding this page, or to receive notifications of updates to the Materials Manual, please contact [Cristina Croft](#) at (352) 955-6634.

Introduction [\(PDF-566 KB\)](#)

CHAPTER 2: Soils Materials and Foundations

Section	Title	Volume I	Volume II
Section 2.1	Structural Layer Coefficients for Flexible Pavement Base Materials	<a href="#">V1-Section 2.1 [PDF-142KB]</a>	N/A
Section 2.2	Soils and Foundations	<a href="#">V1-Section 2.2 [PDF-274KB]</a>	N/A
Section 2.3	Earthwork Operations	<a href="#">V1-Section 2.3 [PDF-167KB]</a>	N/A
Section 2.4	Polymer Slurry	N/A	<a href="#">V2-Section 2.4</a>



FDOT Roadway Design Office  
Topic No: 625-010-003



## 2025-26 STANDARD PLANS FOR ROAD CONSTRUCTION




Effective for Projects with Lettings in the Fiscal Year (FY) from July 1, 2025 through June 30, 2026

State of Florida Department of Transportation  
Office of Design  
Mail Station 32  
605 Suwannee Street  
Tallahassee, Florida 32399-0450

## Earthwork Related Standard Specifications


- 120 Embankment
- 125 Excavation for Structures and Pipes
- 145 Geosynthetic Reinforcement
- 160 Stabilizing
- 200 Rock Base
- 204 Graded Aggregate Base
- 285 Optional Base Course
- 290 Granular Subbase
- 455 Structures Foundations
- 514 Geosynthetic for Drainage Applications
- 522 Concrete Sidewalk and Driveways
- 548 Retaining Walls
- 914 Stabilization Materials
- 985 Geosynthetic Materials




[www.fdot.gov/programmanagement/specs.shtm](http://www.fdot.gov/programmanagement/specs.shtm)



## Two Types of Pavement System



Flexible Pavement



Rigid Pavement



## Two Types of Pavement System Details

- **Standard Plans, Index 120-001 – Embankment Utilization**
  - Sheet 1 – Flexible Pavement
  - Sheet 2 – Rigid Pavement, Asphalt Base Option
  - Sheet 3 – Rigid Pavement, Special Select Soil Option





FDOT Roadway Design Office  
Topic No: 625-010-003



Effective for Projects with  
Lettings in the Fiscal Year (FY)  
from July 1, 2025 through June 30, 2026

State of Florida Department of Transportation  
Office of Design  
Mail Station 32  
605 Suwannee Street  
Tallahassee, Florida 32399-0450

[www.fdot.gov/design/standardplans](http://www.fdot.gov/design/standardplans)



## Embankment Construction

- **120-8 Embankment Construction**
  - 120-8.1 General
  - 120-8.2 Dry Fill Method
  - 120-8.3 Hydraulic Method
  - 120-8.4 Reclaimed Asphalt Pavement (RAP) Method
- **120-10 Acceptance Program**





# LOTS

## 120-8.1 – LOT definition and maximum length

- LOTS cover both vertical and horizontal

Mainline pavement lanes, turn lanes, ramps, parking lots, concrete box culverts and retaining wall systems



A LOT is defined as a single lift of finished embankment not to exceed 500 feet.

Shoulder-only areas, shared use paths, and sidewalk areas



A LOT is defined as a single lift of finished embankment not to exceed 2000 feet.

# Maximum Compacted Lift Thickness

## ■ 120-8.2 Dry Fill Method

- 120-8.2.2 – Lists maximum lift thickness based on group number

**120-8.2.2 Maximum Compacted Lift Thickness Requirements:** Construct the embankment in successive layers with lifts up to a maximum listed in Table 120-1 below based on the embankment material classification group.

Table 120-1			
Group	AASHTO Soil Class	Maximum Lift Thickness	Thick Lift Control Test Section Requirements
1	A-3	12 inches	Not Needed
	A-2-4 (No. 200 Sieve $\leq$ 15%)		
2	A-1	6 inches without Control Test Section	Maximum of 12 inches per 120-8.2.3
	A-2-4 (No. 200 Sieve $>$ 15%)		
	A-2-5, A-2-6, A-2-7, A-4, A-5, A-6		
	A-7 (Liquid Limit $<$ 50)		

## Thicklift Test Section

- 120-8.2.3
- Notify the Engineer prior to beginning construction of a test section
- Construct a test section of the length of one full LOT
- Perform five QC tests at random locations within the test section
- All five QC tests and a Department Verification test must meet the density requirement
- Identify the test section with the compaction effort and soil classification in the Earthwork Records System (Density Logbook).

## Dewatering Methods & Hydraulic Method

### ■ 120-8.2.4 – Dewatering Equipment and Methods

- Must perform dewatering when encountering water table in backfill areas.
- Normal dewatering methods include, but not limited to, constructing shallow surface drainage trenches/ditches, using sand blankets, sumps and siphons.
- When normal dewatering methods results does not adequately remove the water, the Engineer may require the embankment material to be placed in the water in lifts specified in **120-8.2.5 Placing in Unstable Areas**.

### ■ 120-8.3 Hydraulic Method

- Rarely done by choice but mostly used when mother nature provides rain

## Reclaimed Asphalt Pavement (RAP) in Embankment Layer

- **Two methods for RAP usage in embankment**
  - Soil and RAP Mixture (120-8.4.2)
    - 4" of RAP with 8"-10" of Embankment Soil
  - Alternate Soil and RAP Layer Construction (120-8.4.3)
    - 6" - 12" of Embankment & 6" RAP alternate
    - Soil layer must have an LBR of 40 to prevent failure during compaction of the overlying RAP layer.
- **The Contractor must demonstrate feasibility with 500' test section**

## Reclaimed Asphalt Pavement (RAP) in Embankment Layer

- **Where is RAP prohibited?**
  - Construction areas that are below the seasonal high groundwater table elevation
  - Behind and below MSE Wall backfill
  - The upper 6 inches of the Embankment layer



# Embankment Construction

- **120-10 Acceptance Program**

- 120-10.1 General
  - 120-10.1.1 Equipment Comparison
  - 120-10.1.2 Density over 105%
- 120-10.2 Quality Control Tests
- 120-10.3 Department Verification
- 120-10.4 Reduced Testing Frequency
- 120-10.6 Verification Comparison Criteria and Resolution Procedures

# Initial Equipment Comparison

- 120-10.1.1
  - Before first density can be taken on the job, perform three-way comparison between IA to QC, IA to Verification, and QC to Verification.
  - Once gauge has been verified in a three-way comparison, then those verified gauges can be used to verify additional gauges on the project by performing a two-way comparison (QC to VT).
  - Ensure that the difference between any two computed wet densities does not exceed the limits in Table 120-2.

Table 120-2			
Condition	Comparison Type	Manufacturer	Tolerance
Condition 1: When both gauges in the comparison are Nuclear Density Gauges (NDG)	NDG to NDG	Same Manufacturer	2 lb/ft <sup>3</sup>
	NDG to NDG	Different Manufacturer	3 lb/ft <sup>3</sup>
Condition 2: When one of the gauges in the comparison is a Low-Activity Nuclear Density Gauge (L-NDG)	L-NDG to L-NDG	Same Manufacturer	2 lb/ft <sup>3</sup>
	L-NDG to L-NDG	Different Manufacturer	3 lb/ft <sup>3</sup>
	NDG to L-NDG	Same/Different Manufacturer	

## Low-Activity Nuclear Density Gauge (L-NDG)

- Commonly called EGauge
- Reference: FM 1-T310 – Florida Method of Test for In-Place Density of Soils and Soil Aggregates by Nuclear Methods
- Density gauge that uses lower levels of gamma radiation to determine the density of soil and soil aggregates (FM 1-T310, Section 5.1).
- It is “low activity” because the levels of radiation are lower than regular Nuclear Density Gauges (NDGs)
- Does not contain neutron source, therefore, no moisture measurements
- Moisture needs to be measured using another approved source for **all materials** (FM 1-T 310, Section 12.4.1)



## Quality Control Tests

### ■ 120-10.2 Quality Control Tests

- FM 1-T099 Standard Proctor
- AASHTO M145 Soil Classification
  - AASHTO T88 (gradation), AASHTO T89 (LL), AASHTO T90 (PL), and FM 1-T267 Organic Content
- FM 1-T310 In-place wet density by Nuclear Density Testing
  - 100% of the Standard Proctor, FM 5-507 SPEEDY
- Frequency

Table 120-3			
Test Name	Quality Control	Verification	Verification of Shoulder-Only Areas, Shared Use Paths, and Sidewalks
Standard Proctor Maximum Density	One per soil type	One per soil type	One per soil type
Density	One per LOT	One per four LOTS and for wet conditions, the first lift not affected by water	One per two LOTS
Soil Classification and Organic Content	One per Standard Proctor Maximum Density	One per Standard Proctor Maximum Density	One per Standard Proctor Maximum Density

## Department Verification & Reduced Testing

### ■ 120-10.3 Department Verification

- Lab tests one to one testing frequency (one per soil type)
  - Every test that QC runs, VT tests to verify test results
- Field Density test is reduced frequency for VT

### ■ 120-10.4 Reduced Testing Frequency

- Obtain Engineers written approval for the option to reduce QC density testing frequency to 1 per 2 LOTs
- Must have data for 12 consecutive verified LOTs where resolution testing performed was not required
  - If resolution testing was required, but the QC test data was upheld.
- Reduced testing frequency must not be used in construction of shoulder-only areas, shared use paths, sidewalks, and first and last lift.

## 120-10.6 Verification Criteria and Resolution Procedure

### ■ FM 1-T 099 Proctor

- Use QC's Proctor if QC and VT are within 4.5 pcf
- If not, perform resolution test (RT).
- Use QC's Proctor if QC and RT are within 4.5 pcf
- If not, use VT's Proctor

### ■ M145 Soil Classification, T88 gradation, T89 LL, T90 PL, and 1-T267 Organic Content must pass for both QC and VT

- If QC's test result fail any of the tests, reject the material for use as embankment
- If all test for QC passes and one or more fails on VT's test panel, then perform RT
- If RT passes all tests, then QC results upheld, and the Contractor may use the material for embankment portion.

### ■ T310 Field Density Testing

- QC must pass every LOT and VT verifies 4 LOTs by taking one random density test
- If VT passes, 4 LOTs verified and accepted.
- If not, QC performs a QR test within 5-foot radius of the failing VT test.
  - If QR passes, accept 4 LOTs
  - If QR fails, perform gauge comparison. If gauge comparison is in good status, then reprocess the entire 4 LOTs and retest using the same procedure above.



## Excavation and Embankment for Structures and Pipe


- **125-8 Backfilling**

- 125-8.3 Pipe Zones for Pipe  $\geq 12$ " I.D.
- 125-8.1 Lift Thickness


- **125-9 Acceptance Program**

- 125-9.2 Density Testing Requirements

## Pipe Zones 125-8.3




# Cover Height




# Density Requirements

- **Cover Zone Density**
  - Cover Height  $\leq 15''$
  - 100% of Standard Proctor
- **Top Zone Density**
  - Follow 120 Specification Criteria
  - 100% of Standard Proctor



# Density Requirements


- **Cover Zone Density**
  - Cover Height > 15"
  - 95% of Standard Proctor
- **Top Zone Density**
  - Follow 120 Specification Criteria
  - 100% of Standard Proctor



# Density Requirements

## ■ Density around Structures


- 100% of standard Proctor regardless of the depth
- For a distance of one pipe diameter but not less than 3' from the outside face of the structure





# Density Requirements

- **Cover Zone Density**
  - Cover Height > 15"
  - Structure and cover zone compacted in one operation
  - 100% of Standard Proctor



## Pipe Backfill Density

- **Compaction requirements are the same for all pipe types**
- **If the cover height  $\leq$  15 inches below base**
  - 100% standard Proctor within cover zone
- **If cover height is greater than 15 inches below base**
  - 95% standard Proctor within cover zone
- **Structure backfill requires 100% of standard Proctor regardless of the depth**
  - For a distance of one pipe diameter but not less than 3 feet from the outside face of the structure

## Pipe and Structure Compacted in One Operation

- 125-8.1.1 states “Backfill for structures and pipe compacted in one operation will be considered as one LOT within the cover zone”
- Since drainage structures require 100% density regardless of the depth, this requirement supersedes
- If pipe and structure are compacted in one operation, one density test that meets 100% density may represent both pipe and structure.
  - Density tests must be taken at random locations along structure and pipe

### 125-8 Backfilling.

#### 125-8.1 General Requirements for Structures and Pipe:

**125-8.1.1 General:** Backfill in the dry whenever normal dewatering equipment and methods can accomplish the needed dewatering. A LOT is defined as one lift of backfill material placement, not to exceed 500 feet in length or a single run of pipe connecting two successive structures, whichever is less. Backfill for structures and pipe compacted in one operation will be considered as one LOT within the cover zone. Backfill around structures compacted separately from the pipe will be considered as separate LOTs. Backfill on each side of the pipe for the first lift will be considered a separate LOT. Backfill on opposite sides of the pipe for the remaining lifts will be considered separate LOTs, unless the same compactive effort is applied. Same compactive effort is defined as the same type of equipment (make and model) making the same number of passes on both sides of the pipe. For multiple phases of backfill, a LOT shall not extend beyond the limits of the phase.

## Maximum Lift Thickness

- 125-8.1.6 – In the soil envelope, maximum allowed thickness of backfill is 6 inches
- 125-8.1.6.1 – Maximum allowable thick lift compaction requirements based on AASHTO Soil Class

Table 125-1					
Group	AASHTO Soil Class	Maximum Lift Thickness		Thick Lift Control Test Section Requirements	
		Within Cover Zone	Above Soil Envelope	Within Cover Zone	Above Soil Envelope
1	A-3	6 inches	12 inches	N/A	Not Needed
	A-2-4 (No. 200 Sieve $\leq$ 15%)				
2	A-1	6 inches without control test section		N/A	Maximum of 12 inches per 120-8.2.3
	A-2-4 (No. 200 Sieve $>$ 15%)				
	A-2-5, A-2-6, A-2-7, A-4, A-5, A-6				
	A-7 (Liquid Limit $<$ 50)				

- Same test section (test strip) requirements specified in 120

## Reduced Frequency Testing

- Number of passing density tests required before reduced frequency density testing is allowed;
  - Embankment: After 12 passing tests → 1 per 2 LOTs per 120-10.4
  - Pipe Backfill: After 6 passing tests → 1 per 2 LOTs per 125-9.1.1
    - Reduced frequency for pipe backfill in the trench box is reduced to one test per four LOTs
    - *Do not apply reduced testing frequency for the first and last lift of pipe*
  - LOTs are to be selected randomly when reduced frequency testing is performed

## Geosynthetic Reinforcement


- 145-1 Description
- 145-3 Material Requirements
- 145-4 Construction Requirements
- 145-5 Certification



# Geosynthetic Reinforcement



Soils generally fail in shear








## Geosynthetic Reinforcement

### ■ 145-1 Applications

- Geosynthetic reinforced soil slopes
- Geosynthetic reinforced foundations over soft soils
- Geosynthetic reinforced embankment



# Reinforced Soil Slopes




1. A  
2. 1  
3. 1

# Reinforced Foundations over Soft Soils



GEOSYNTHETIC REINFORCED FOUNDATIONS CONSTRUCTED ON SOFT SOILS

# Reinforced Embankment



## 145-3 Material Requirements

### ■ Backfill Materials

#### ■ Geosynthetic Reinforced Soil Slopes

- Free draining material
- Organic Content
  - Individual  $\leq 3.0\%$  & Average  $\leq 2.0\%$
- Liquid Limit  $\leq 15$ , PI  $\leq 6.0$

- pH between 5 & 10. If polyester based geosynthetic, then pH between 5 and 9.

#### ■ Reinforced Foundations over Soft soils

- Meet requirements 120
- Same pH requirements as reinforced soil slopes

#### ■ Reinforced Embankment

- Meet appropriate roadbed specifications (120, 160, 200, 204)
- Same pH requirements as reinforced soil slopes

Table 145-1	
Sieve Size	Percent Passing
3-1/2 inches	100
3/4 inch	70 to 100
No. 4	30 to 100
No. 40	15 to 100
No. 100	5 to 65
No. 200	0 to 15



# 145-3 Material Requirements

## ■ Geosynthetic

- Can only use products that are listed on the APL
  - FDOT PATH website  
<https://path.fdot.gov/Specifications>
  - Go to 985 for list of APL products

### 985-5 Structural.

**985-5.1 Applications:** Materials for reinforcement, separation and stabilization applications must be tested in accordance with and meet the physical requirements below. The ultimate tensile strength of all R-1 materials must be at least 4800 pounds per foot in both the machine and cross machine directions.

Table 985-7 Reinforcement, Separation and Stabilization Applications	
Type	Description
R-1	Geosynthetic Reinforced Soil (GRS-IBS)
R-2	Reinforcement of Foundations over Soft Soils
R-3	Reinforced Soil Slopes
R-4	Reinforced Embankment
R-5	Construction Expedient

## 145-4 & 145-5 Construction Requirements / Certification

- Ensure Contractor installs in accordance with Manufacturer's instructions
- At least **fourteen days prior to placement:**
  - Contractor to submit to the Engineer a certification
  - Two 8-inch by 10-inch samples of geosynthetic materials for product identification to the Engineer
- VT to send both certification and physical samples to SMO for approval
- **For backfill materials:** Submit to the Engineer a signed and sealed certification by a Professional Engineer registered in the State of Florida, that the pH meets the requirements of 145-3

## 160 Stabilizing

- 160-1 Description
- 160-2 Materials
- 160-3 Construction Methods
- 160-4 Acceptance Program

## ■ 160-1 Description

- 
- The diagram illustrates a cross-section of a highway pavement structure. The top layer is labeled "Shldr." (Shoulder) on both sides and "Lanes" in the center. The lane width is indicated as "Varies". The shoulder width is also indicated as "Varies". The top surface has a slope of "0.06" on the shoulders and "(0.02-0.03)" in the lanes. The base layer is labeled "S" and has a thickness of "48\"\*\" on the shoulders and "12\"\*\" in the lanes. The subgrade is labeled "S" and has a slope of "1:6 Std." on the left and "1:2 C" on the right. A red arrow on the right points upwards, labeled "Increasing Stiffness".

## 160-2 Stabilizing Materials

- Commercial Material
- Local Materials
- RAP or RAP Blended Material
- Existing Base

## Commercial Material

- If Commercial material is used as a stabilizer, then the material must be obtained from an approved production facility and the product must be "Certified for FDOT" as specified in 914-2.1 and Aggregate Rule 1-103, FAC.
- The delivery tickets must be collected and kept with the CEI's office for records.



## Local Materials

- **Local material must be tested at the source (440A) before spreading on the roadway**
  - Atterberg Limits
    - Liquid Limit  $\leq 40$
    - Plastic Index  $\leq 10$
  - AASHTO T267 Organic Content
    - 3 Individual Organic Content  $\leq 4\%$
    - Average of 3 individual samples  $\leq 2.5\%$

## RAP or RAP Blended Material

- When RAP is milled and windrowed back on the same project (Engineer Witness), no further testing is needed.
- If no Engineer witness, then it is RAP or RAP Blended Material
  - Engineer will visually inspect the stockpile to ensure the source contains RAP
  - Source (440A) testing must be performed at the source to prove that the organic content is high due to asphalt content
- After Engineer's approval in writing, the Contractor may spread and mix the material
- *After mixing*, FM 5-563 (Asphalt Content) test must be performed to ensure that the AC limit doesn't exceed 4.0%
- Failure may indicate too much Asphalt or the presence of a material that is truly high organic





## Existing Base

- Inform the Engineer of the location of existing base that will be excavated and stockpiled to be used as stabilizer
- Obtain the Engineer's approval in writing before using Existing Base



## Granular Subbase

- The Engineer may allow, at no additional cost to the Department, the substitution of 6 inches of Granular Subbase
  - Must meet the requirements of 290-2 & 290-3
  - The 6" substitution is only when 12" of Type B Stabilization requiring a Limerock Bearing Ratio (LBR) value of 40 is specified
  - The correlation between design structural number and subbase substitution is **not** linear

## Acceptance Program for Mixed Materials

- Uses modified Proctor instead of standard Proctor
- LBR testing required
- Organic Content (Ind.  $\leq 4.0\%$ , Avg.  $\leq 2.5\%$ )
  - When RAP is used as the stabilizer, Asphalt Content  $\leq 4.0\%$
- Mixing depth
  - Report and record depth be to the nearest 0.25 inches
  - The difference between the individual measured depth thickness on the roadway and the Plan target thickness must not exceed 2 inches
  - The difference between the LOT average (average of the three individual measured depth thickness) and the plan target thickness must not exceed 1 inch.
  - No under-tolerance of mixing depth is allowed
- Density Requirements
  - Minimum density at any location of 98% of the modified Proctor

## 200 Rock Base

- 200-1 Description
- 200-2 Materials
- 200-6 Compacting and Finishing Base
- 200-7 Acceptance Program
- 200-8 Priming

## 200-1 & 200-2

### ■ Optional Base Group (OBG)

- 15 Groups for Non-Limited Use
- 8 Groups for Limited Use (Not used on FDOT)

- **The Contractor may use more than one source of base rock on a single Contract provided that a single source is used throughout the entire width and depth of a section of base.**
- **Obtain approval from the Engineer before placing material from more than one source.**
- **Intermittent placement or “blending” of sources is not permitted.**

Table 285-1  
Optional Base Groups 1 through 7

Base Materials	Base Group (Base Group Pay Item)						
	1 (701)	2 (702)	3 (703)	4 (704)	5 (705)	6 (706)	7 (707)
Limerock, LBR 100	4"	5"	5-1/2"	6"	7"	8"	8-1/2"
Cemented Coquina, LBR 100	4"	5"	5-1/2"	6"	7"	8"	8-1/2"
Shell Rock, LBR 100	4"	5"	5-1/2"	6"	7"	8"	8-1/2"
Bank Run Shell, LBR 100	4"	5"	5-1/2"	6"	7"	8"	8-1/2"
Calcarenite, LBR 100	4"	5"	5-1/2"	6"	7"	8"	8-1/2"
Recycled Concrete Aggregate, LBR 150 <sup>(1)</sup>	4"	5"	5-1/2"	6"	7"	8"	8-1/2"
Graded Aggregate Base, LBR 100	4-1/2"	5-1/2"	6-1/2"	7-1/2"	8-1/2"	9"	10"
Type B-12.5	4" <sup>(3)</sup>	4" <sup>(3)</sup>	4" <sup>(3)</sup>	4" <sup>(3)</sup>	4-1/2"	5"	5-1/2"
B-12.5 and 4" Granular Subbase, LBR 100 <sup>(2)</sup>	-	-	-	-	-	-	-
RAP Base	5"	-	-	-	-	-	-

(1) Do not use on interstate roadways.

(2) The construction of both the subbase and Type B-12.5 will be bid and used as Optional Base. Granular subbases include limerock, cemented coquina, shell rock, bank run shell, recycled concrete aggregate and graded aggregate base. All subbase thicknesses are 4" minimum prior to adding the required prime coat.

(3) Based on minimum practical thickness.

(4) To be used for widening, three feet or less.

## 200-2 Materials

- **OBG**

- **Existing Rock**

- Meeting the requirement of 200- 2.2.
- The existing rock must be material that was previously “Certified for FDOT”
- Notify the Engineer in writing
- Submit process control plan
- Stockpile and test for LBR at the source (stockpile) at a frequency specified in the Specs
- Tested again at the roadway after spreading for Proctor

## 200-6 Compacting and Finishing Base

- **Construct the base in multiple courses of equal thickness**
  - Individual courses shall not be greater than 6 inches or less than 3 inches
- **Thicklift allowed if approved by test section**
  - Construct in accordance with 200-5 Spreading Rock
  - 8-inch maximum lift thickness using thicklift
  - Five QC nuclear density tests at random locations within the test section
    - At each test location, test the bottom 6 inches in addition to the entire course thickness
    - One VT test at random location
    - All 5 QC tests and the VT test must meet minimum percent compaction (98% of Modified Proctor)
  - The minimum density required on the thicker lift will be the average of the five QC test results obtained on the thicklift
  - If source changes construct new thicklift test section

## 200-7 Acceptance Program

### ■ Test and Testing Frequency

Table 200-1 Mainline Pavement Lanes, Turn Lanes, Ramps, Parking Lots, Concrete Box Culverts and Retaining Wall Systems		
Test Name	Quality Control	Verification
Modified Proctor Maximum Density	One per eight consecutive LOTs	One per 16 consecutive LOTs
Density	One per LOT	One per four LOTs
Roadway Surface and Cross Slope	One per LOT	One per two LOTs
Roadway Thickness	Three per LOT	Witness




## 200-7.2.3 Pit Proctor

- Use the “Pit Proctor” value in lieu of the traditional modified Proctor testing
- Effective 2015, Pit Proctor program was introduced
  - Optional for Contractor
  - Contractor notifies the Engineer in writing of the option to use the Pit Proctor process
- Pit Proctor values are supplied by the Department and come from testing done at the mines
- The Pit Proctor values are updated by SMO the first day of each calendar quarter based on previous quarter test results
  - Posted on the following website:  
<https://www.fdot.gov/materials/laboratory/geotechnical/aggregates/pitproctor/index.shtm>



# Pit Proctor

- Pit Proctor is a quarterly process which is documented at the top of the report. The information on the report is only valid for the time frame noted “Valid from...”



**Pit Proctor Quarterly Report**

Generated: 1/11/2022 8:44:18 AM

Valid from 1/1/2022 to 3/31/2022


FDOT State Materials Office, 5007 N.E. 39th Avenue, Gainesville, FL 32609 (352) 955-6600

District: 01

Facility ID	Facility Name	Product	Process	Material Description	* Est. Opt. Moisture (%)	Pit Proctor (pcf)
-------------	---------------	---------	---------	----------------------	--------------------------	-------------------

- Density tests must use current quarter Pit Proctor value to calculate percent density compaction regardless of when the Contractor brought the material to the job
- QC reports the Pit Proctor value into MAC and IV tests every 16 LOTs to verify the accuracy of the Pit Proctor
  - IV Proctor can’t be higher than 4.5 pcf of Pit Proctor

# Pit Proctor Flow Chart



## Quality Control and Verification Testing

- **Thickness and Surface Testing**

- Considered deficient if the measured depth is over 1/2 inch less than the specified thickness

- **Density Requirements**

- Minimum density in any LOT of 98% of modified Proctor maximum density



## 514 Geosynthetic for Drainage Application

- 514-1 Description
- 514-2 Material
- 514-4 Acceptance Criteria

# Drainage Applications

## ■ 514-1 Description / 514-2 Material

- Geosynthetics used in drainage, slope protection, and material separation applications
- Can only use products that are listed on the APL
  - FDOT PATH website  
<https://path.fdot.gov/Specifications>
  - Go to 985 for list of APL products

Table 985-1 Drainage Applications		
Geotextile Type	Description	Standard Plans Index
D-1	Revetment (Special)	
	Rock, Rubble without bedding stone	
	Ditch Pavement (Rubble Riprap) without bedding stone	524-001
D-2	Revetment (Standard)	
	Articulating Block	
	Gabions	524-001
	Rock, Rubble, and Broken Concrete with bedding stone	
	Ditch Pavement (Rubble Riprap) with bedding stone	524-001
	Joint Cover for Mechanically Stabilized Retaining Wall with Coarse Aggregate Backfill	
	Joint Cover for Mechanically Stabilized Retaining Wall Supporting Spread Footing Foundations	
D-3	Underdrain: Types II, III, and V	440-001
	French Drain	443-001
	Sheet Piling Filter	
	Filter Fabric Jacket (Culvert)	430-001
	Box Culvert Joints	400-289 and 400-291
	Concrete Pavement Subdrainage	446-001
	Joint Cover for Mechanically Stabilized Retaining Wall with Sand or Limerock Backfill	
D-4	Slope Pavement	
	Ditch Pavement (Sand-Cement Riprap or Concrete)	524-001
D-5	Coarse Aggregate Wrap	
	Separation Geotextile	
	Cast-In-Place Retaining Wall	

# Drainage Applications

- Determine class type for the in-place soil type being used with the geosynthetic (Table 985-2) for drainage applications D-1, D-2, & D-3
- APL has the detailed information for the approved class types

Table 985-2 Geotextile Selection	
In-situ Soil Type or Drainage Application	Class for Type D1, D2, D3 Materials
< 15% passing a No. 200 Sieve*	a
15% to 50% passing a No. 200 Sieve*	b
> 50% passing a No. 200 Sieve*	c
> 50% passing a No. 200 Sieve* with Plastic Index >7	d
MSE Joint Cover for Sand or Limerock Backfill	e
MSE Joint Cover for Coarse Aggregate Backfill	f

\*as per AASHTO T88.

## Mirafi FW300 (APL Product)

Supplier: TenCate Geosynthetics

- **Model Number:**
- **APL Number:** 985-007-035
- **Specification:** Geosynthetic Materials
- **Product Type:** Drainage Geotextiles, D-2
- **BABA Eligible:** Eligible
- **Comment:** Approved for D-2(f).
- **Fabrication:** Buy America Category: Construction Material - Plastic or Polymer Based

## Mirafi 160N (APL Product)

Supplier: TenCate Geosynthetics

- **Model Number:**
- **APL Number:** 985-008-003
- **Specification:** Geosynthetic Materials
- **Product Type:** Drainage Geotextiles, D-3
- **BABA Eligible:** Eligible
- **Comment:** Approved for D-3 (a, b, c, d, e) for all contracts. || NTPEP GTX-2018-01-062
- **Fabrication:** Buy America Category: Construction Material - Plastic or Polymer Based

## 514-4 Acceptance Criteria

- Ensure Contractor installs in accordance with Manufacturer's instructions
- At least **fourteen days prior to placement:**
  - Contractor to submit to the Engineer a certification
  - Two 8-inch by 10-inch samples of geosynthetic materials for product identification to the Engineer
- VT to send both certification and physical samples to SMO for approval
- This applies to **ALL** drainage materials used on the job



## 548 Retaining Wall Systems

- 548-1 Description
- 548-2 Materials
- 548-3 APL
- 548-8 Construction Requirement
- 548-9 Acceptance Program
- 548-10 Certification

## Mechanically Stabilized Earth (MSE) Walls



## Retaining Wall Systems

### ■ 548-1 Description

- Permanent and temporary retaining wall systems
- Sheet pile wall and C-I-P walls are not part of this Section

### ■ 548-2 Materials

- 548-2.6 Backfill Material
  - Coarse Aggregate at least one foot above the DHW shown in the Plans
    - Size No 57 through Size No 89 (unless restricted in the Plans)
  - Flowable fill can only be used when shown in the Plans
    - Metallic wall components must be completely encapsulated by the flowable fill
  - Select backfill must meet 105 and 120.
    - Gradation must be using FM 1-T27/ FM 1-T011, in lieu of AASHTO T88.
    - $LL \leq 15$ ,  $PI = NP$ , & Organic Content (Individual  $\leq 3.0\%$  & Average  $\leq 2.0\%$ )
  - Electro-chemical testing required

## 548-2 Backfill Material Requirement

### ■ T27/T11 Gradation

Table 548-2 Gradation Limits	
Sieve Size	Percent Passing
3-1/2 inches	100
3/4 inch	70-100
No. 4	30-100
No. 40	15-100
No. 100	0-65
No. 200	0-12

### ■ Electro-chemical testing

#### Metallic Reinforcement

Test	Criteria
pH	5.0 – 10.0
Resistivity	> 3,000 ohm-cm
Soluble chloride content	< 100 PPM
Soluble sulfate content	< 200 PPM

#### Geosynthetic Reinforcement

Test	Geosynthetic Type	Criteria
pH	Polyester	5.0 – 9.0
	Non-Polyester	5.0 – 10.0


## Retaining Wall Systems

### ■ 548-3 APL

- Entire system must be on the APL under 548

### ■ 548-8 Backfill Placement

- A LOT is defined as a single lift of finished embankment not to exceed 500 feet in length or cumulative length of continuous, interconnected walls
- Backfill within 3 feet from the panels and backfill beyond 3 feet from the panels are separate LOTs



## Additional LOT Details

- Strips up to 8 feet wide between two retaining wall volumes constructed with the same material in one operation may be considered as one LOT with the retaining wall volumes.
- Overlapping retaining wall volumes may be considered one LOT, excluding the 3 feet width behind the panels.




Figure 58 . Paralell walls, with a narrow gap between reinforcements

## Rolling Pattern

- **Within 3' of all MSE Wall Backfill Types**
  - Achieve compaction of all backfill types within three feet of the back of the wall face using a power operated roller or plate weighing less than 1,000 pounds
- **Coarse Aggregate Backfill**

Equipment Weight Limit	Min # of Passes
Between 600 and 1000 pounds	3 passes
Greater than 1000 pounds	2 Passes



## Acceptance of Compaction for Backfill

### ■ 548-9.4 Acceptance Criteria

- Within 3 feet of the wall face – minimum 90% of the modified Proctor maximum dry density
- Beyond 3 feet of the wall face – minimum 95% of the modified Proctor maximum dry density

### ■ 548-9.4.1 Optional Acceptance Criteria for A-3 and A-2-4 Materials

- Within 3 feet of the wall face – minimum 95% of the standard Proctor maximum dry density
- Beyond 3 feet of the wall face – minimum 100% of the standard Proctor maximum dry density

## Retaining Wall Systems

### ■ 548-10 Certification

- For backfill materials: Submit to the Engineer a signed and sealed certification by a Professional Engineer registered in the State of Florida, that the electro-chemical properties meet the requirements of 548-2.6.2
- Submit all test reports to the Engineer necessary to document compliance with the Specifications, at least ten days prior to wall construction.
- Submit a certificate of compliance certifying that the retaining wall materials, backfill and construction practices comply with this Section.
- For SBW systems, the Engineer will randomly select samples of each type of block used in the segmental block retaining wall system and review a copy of the certified test report corresponding the sample at a frequency of one sample per type of block for each wall.
- Acceptance of furnished material will be based on the certificate



# Earthwork Records System (ERS)



## Earthwork Records System

- ERS, also known as density logbook, is a group of logbooks with pertinent field data put together for earthwork construction
- The electronic logbook (MAC-ERS), provide as-built records of the pavement substructure
  - Graphical representation of the materials used to build the earthwork layers
  - Densities achieved for each construction type (i.e., roadway, MSE walls, pipe backfill, etc.)
- ERS is used as the acceptance method for material certification
- District Materials Office initially provides the MAC-ERS training
- The training is provided for project personnel that will have an upcoming project in MAC-ERS
- Training videos and instructions manual are available from the following website:
  - <https://www.fdot.gov/materials/mac>

## Responsibilities

### Quality Control

- Plot roadway and drainage sheets
  - Data entry to generate plots in MAC
- Maintain the QC ERS throughout the project.
- Take QC densities
- Sample, split and test for Proctors
- Retain resolution and verification samples
- Sample for all QC lab tests
- QC takes resolution density tests
- Meet the requirements of the contract.

### Verification

- Verify Contractor's test results
- Review ERS for completeness and accuracy.
- Provide the reference gauge for comparisons on new gauges brought to the project
- Sample for LBR
- Verification density testing
- Witness mixing depth checks for stabilized subgrade
- Witness surface and depth checks for base

### District Materials IA

- Assist & train project personnel in interpreting the Earthwork Contract Documents
- Provide the reference nuclear density gauge for initial comparison
- Perform Independent Assurance (IA) on ERS to ensure all deficiencies are resolved before final acceptance
- Verify personnel working in Earthwork are CTQP qualified and perform IA technicians.
- Perform random field inspection on ongoing construction projects

## Don't forget...

- **Contact the Earthwork Team at the District Materials Office if any support is needed**
- **Check with the Materials Office about:**
  - Paper Logbooks (when and if needed)
  - Coding elevations from Plans
  - Using DLB Plot Program (when and if needed)
  - MAC plotting questions





# Plot Coding


## Roadway and Drainage Plots



## Required for Coding Roadway



- Highest proposed pavement elevation
- Lowest existing ground elevation
- Code for unsuitable material
- Locate shoulder break points and draw the 1V:2H control line
- Code thickness of Asphalt, Base, & Subgrade
- Code Shoulder Base, Shoulder Subgrade, Sidewalk, etc.


## Required for Coding Roadway



Code Critical points for both Left and Right Roadways from each Cross Section

# Determining the 2:1 Slope






## Required for Coding Drainage

- Flow line
- Top & invert structure elevation
- Length & size of pipe
- These values are manually read from the Plans; this information is rarely given in one place.
  - May require cross referencing with plan/profile view or summary of drainage structures.


# Required for Coding Drainage

Plot Coding



Some structure tops & bottoms must be scaled from cross sections. We need to find the lengths of pipe.

# Required for Coding Drainage





# Find the Errors on the Density Report

Florida Department of Transportation

Project FIN: 123456789  
Type of Const: Embankment FROM STATION 30+00 TO STATION 35+00

CONTRACTOR - QC DENSITY RECORDS  
Earthwork Density Report

Page 12

LOT No.	RF	Date	TIN	Gauge Serial No.	STD. Dns/Mst Count	Max. Dns. / Sample No.	Test No.	Station	Offset	Lift No.	Test Depth	Sol. Dns/Mst Count	Wet Dens.	% Moist.	Dry Dens.	% Max Dens.	Status Disp.
1-12		2/10/2017	P14725874	369	2012 112	119 B001Q		30+00	18' RT B/L	1	12"	1223 732	132.1	10.1	127.9	100.8	P
2-12		2/10/2017	P14725874	369	2012 112	119 B001Q		31+00	20' RT B/L	2	12"	1223 732	139.2	8.8	127.9	107	P
12-3		2/10/2017	P14725874	369	2012 112	119 B001Q		31+50	13' RT B/L	3	12"	1223 732	130.7	12.5	116.2	98	P
4-12		2/10/2017	P14725874	369	2012 112	119 B001Q		33+00	19' RT B/L	4	12"	1223 732	131.0	9.2	120.0	100	P
5-12		2/10/2017	P14725874	369	2012 112	119 B001Q		34+50	16' RT B/L	5	12"	1223 732	128.9	9.5	117.7	98	P
Stabilized Subgrade																	
1-12		2/12/2017	P14725874	369	2299 209	121.8 S001Q		32+56	10' RT C/L	1	12"	2823 326	129.9	6.5	122.0	100	P
Base																	
1-12		2/12/2017	P14725874	369	2299 209	119 B001Q		33+89	8' RT C/L	1	10"	2942	125.9	6.9	117.8	99	P

Disposition Letter Code: V - LOTS Verified by Verification Test R - LOTS Verified by Resolution Procedure N - LOTS Not Verified and Resolution Initiated

\*From district 3 Density Workshop



## Earthwork Density Report

FDOT State Materials | 5007 NE 39th Ave. | Gainesville, FL 32609 | (352) 955-6600

Generated: 11/7/2023 1:55:24 PM

Contract ID: [REDACTED] Let Date: 6/15/2022

**Yellow highlight** indicates: sample pending finalization, gauge company does not match technician company, small density/moisture count, lift thickness  $\neq$  test depth, QC/QR sample with >105% max. density, target compaction override, or comparison package comparing samples on same lift with different Proctors.

**Red font indicates:** unqualified tech, density/moisture count error, failing test result, or a gauge with one of the following issues: (1) incorrect units, (2) missing calibration parameter document, (3) missing OR zero-valued parameter values for corresponding test depth, (4) unrealistic parameter values, or (5) duplicate gauge calibration. (For more details on gauge errors, run the 'ERS - Gauge Error' report)

**Red highlight** indicates a resolution sample used as a Proctor, non-Proctor sample used as a Proctor, or a failing comparison package. **Green highlight** indicates an upheld resolution.

#	MAC Sample ID	Test Date	Sample Level	Initiated User	Gauge SN		$\gamma_{max}$ (pcf)	$(\gamma)_{opt}$ (%)	Elev. (ft)	Station / Pipe Dist. (ft)	Offset	Lift #	Lift Thick. (in) <sup>1</sup>	Test Depth (in)	$\gamma_{soil}$ Count	$\gamma_{wet}$ (pcf)	$\gamma_{dry}$ (pcf)	$\gamma_{max}$ (%)	Comparison Package				
	FDOT Sample #	TAT		Tested By (TIN)	$\gamma_{std.}$ Count	$(\gamma)_{std.}$ Count	Proct. Sample #	$(\gamma)_{soil}$ Count							$(\gamma)$ (%)	% Trgt Cmpct.							
ERS Project: <span style="background-color: #f08080; padding: 2px;"> </span> 3-52-01																				Ardaman & Associates, Inc. [QC], Greenman-Pedersen, Inc. (GPI) [QC], RS&H, Inc. [VT], District 3 Materials Office [IA]			
Drainage																							
S-534 to S-515 (11+35 to 482+75)																							
Spec ID: 120																							
Embankment																							
1	1163514	6/16/2023	QC	V. Scott	76794		107.3	12.4	44.1	182.50	2' L of C/L of Pipe	2	6	6	2731	116.3	108.1	101	166218				
	PH001-T001	4		H40049897	2678	634	E0006Q (1035166)								113	7.6		100					
2	1163516	6/16/2023	QC	V. Scott	76794		107.3	12.4	45.2	125.20	2' R of C/L of Pipe	2	6	6	2719	116.5	106.9	100	166218				
	PH001-T002	4		H40049897	2678	634	E0006Q (1035166)								131	9.0		100					
3	1163518	6/16/2023	QC	V. Scott	76794		107.3	12.4	45.1	154.60	2' R of C/L of Pipe	3	6	6	2604	118.5	109.3	102	166218				
	PH001-T003	4		H40049897	2678	634	E0006Q (1035166)								125	8.4		100					
4	1163520	6/16/2023	QC	V. Scott	76794		107.3	12.4	45.9	135.30	2' R of C/L of Pipe	4	6	6	2678	118.2	109.4	102	166218				
	PH001-T004	4		H40049897	2678	634	E0006Q (1035166)								634	8.0		100					
5	1182630	6/16/2023	VT	J. Toure	20484		107.3	12.4	45.9	143.20	3' L of C/L of Pipe	4	6	6	1593	115.4	106.8	100	166218				
	PH001-T004	24		P65010491	1577	689	E0006Q (1035166)								129	8.1		100					
6	1163524	6/16/2023	QC	V. Scott	76794		107.3	12.4	45.8	170.70	2' L of C/L of Pipe	5	6	6	2584	118.9	109.8	102	166219				
	PH001-T005	4		H40049897	2678	634	E0006Q (1035166)								124	8.3		100					
7	1163527	6/16/2023	QC	V. Scott	76794		107.3	12.4	46.7	145.90	2' R of C/L of Pipe	6	6	6	2542	119.7	110.6	103	166219				
	PH001-T006	4		H40049897	2678	634	E0006Q (1035166)								123	8.2		100					
8	1163531	6/22/2023	QC	V. Scott	76794		107.3	12.4	47.0	162.60	2' L of C/L of Pipe	7	6	6	2857	114.3	107.1	100	166219				
	PH001-T007	0		H40049897	2678	634	E0006Q (1035166)								102	6.7		100					
	1182633	6/16/2023		J. Toure	20484		107.3	12.4			3' R				1623	115.0		100					



### S-205 to S-206 (363+17 to 363+17)

Spec ID: 120

Embankment

1	1068557 PH001-T001	2/1/2023 4	VT	R. Kincaid K52372178	14149 1952 515	106.0 E0004Q (1035156)	12.8	60.2	27.20	3' L of C/L of Pipe	1	6	6	2399 64	110.1 5.0	104.9	99 95	165550
2	1068353 PH001-T001	1/31/2023 5	QC	J. Hill H40049897	75683 2596 680	106.0 E0004Q (1035156)	12.8	60.2	4.10	2' L of C/L of Pipe	1	6	6	3105 95	1092.0 5.7	1033.1	975 100	165550
3	1068358 PH001-T002	1/31/2023 5	QC	J. Hill H40049897	75683 2596 680	106.0 E0004Q (1035156)	12.8	60.0	13.60	2' R of C/L of Pipe	1	6	6	3114 105	109.0 6.5	102.3	97 95	165550
12	1060081 T0010	11/22/2022 45	VT	L. Brueckhei.. G62077361	14149 1943 525	105.4 E0001Q (1009961)	12.2	58.3	189.80	4' L of C/L of Pipe	9	6	6	1883 54	108.4 2.6	105.7	100 95	145354
13	1032427 T0010	11/22/2022 5	QC	J. Hill H40049897	76794 2646 651	105.4 E0001Q (1009961)	12.2	59.0	345.80	3' L of C/L of Pipe	9	6	6	3174 82	108.9 4.9	103.8	98 95	145354
14	1094259 PH001-T0011	11/22/2022 82	QC	J. Hill H40049897	75683 2646 651	105.4 E0001Q (1009961)	12.2	58.5	70.80	3' L of C/L of Pipe	10	12	12	85 737	111.9 5.0	106.6	101 100	164047
15	1094265 PH001-T0012	11/22/2022 82	QC	J. Hill H40049897	75683 2646 651	105.4 E0001Q (1009961)	12.2	59.9	149.90	4' L of C/L of Pipe	11	12	12	711 83	112.9 4.8	107.7	102 100	164047
18	1249615 PH002-T007	10/18/2023 1	VT	J. Roberts R16343690	14149 1918 525	105.4 E0001Q (1009961)	12.2	60.3	-3.10	4' L of C/L of Pipe	7		6	2185 177	113.2 6.8	106.0	101 100	177942
19	1039564 T008	12/5/2022 5	QC	J. Hill H40049897	76794 2694 662	105.4 E0001Q (1009961)	12.2	61.0	72.50	3' L of C/L of Pipe	7	12	6	696 83	113.9 4.7	108.8	103 95	177939
20	1092655 PH002-T008	12/5/2022 71	QC	J. Hill H40049897	75683 2694 662	105.4 E0001Q (1009961)	12.2	61.0	-4.20	4' R of C/L of Pipe	8		6	2838 90	115.2 5.2	109.5	104 100	177942
21	1039569 T009	12/5/2022 5	QC	J. Hill H40049897	76794 2694 662	105.4 E0001Q (1009961)	12.2	62.2	37.50	3' L of C/L of Pipe	8	12	6	82 694	113.9 4.6	108.9	103 95	177940
22	1092632 PH001-T0010	12/5/2022 71	QC	J. Hill H40049897	75683 2694 662	105.4 E0001Q (1009961)	12.2	62.9	22.10	3' R of C/L of Pipe	9	12	12	685 77	114.4 4.2	109.8	104 100	177940



# Questions?

