Equipment Checklist FM 1-T085 Specific Gravity and Absorption of Coarse Aggregate

	Ρ	F	N/A	
Apparatus				
Balance is of sufficient capacity, with a readability of 1 g, an accuracy of 0.1% or 1.0 g of the sample mass, and conforms to the requirements of AASHTO M 231, Class G5				
Suitable apparatus for suspending the sample container in the water from the center of the balance				
Wire basket of No. 6 or finer mesh of sufficient size to handle the sample				
Watertight Tank – In which the hanger and container clear the sides of water tank when in use				
Tank equipped with an overflow outlet for maintaining a constant water level				
Suspension wire is of the smallest practical size for suspending the container				
Sieves – Sieve cloth is mounted on substantial frames, constructed as to prevent loss of material during sieving, and conforms to the requirements of AASHTO M 92				
Oven – An oven of appropriate size capable of maintaining a uniform temperature of 110 \pm 5 C (230 \pm 9 F)				
	Balance is of sufficient capacity, with a readability of 1 g, an accuracy of 0.1% or 1.0 g of the sample mass, and conforms to the requirements of AASHTO M 231, Class G5 Suitable apparatus for suspending the sample container in the water from the center of the balance Wire basket of No. 6 or finer mesh of sufficient size to handle the sample Watertight Tank – In which the hanger and container clear the sides of water tank when in use Tank equipped with an overflow outlet for maintaining a constant water level Suspension wire is of the smallest practical size for suspending the container Sieves – Sieve cloth is mounted on substantial frames, constructed as to prevent loss of material during sieving, and conforms to the requirements of AASHTO M 92 Oven – An oven of appropriate size capable of maintaining a uniform temperature of 110 ±	aratus Balance is of sufficient capacity, with a readability of 1 g, an accuracy of 0.1% or 1.0 g of the sample mass, and conforms to the requirements of AASHTO M 231, Class G5 Suitable apparatus for suspending the sample container in the water from the center of the balance Wire basket of No. 6 or finer mesh of sufficient size to handle the sample Watertight Tank – In which the hanger and container clear the sides of water tank when in use Tank equipped with an overflow outlet for maintaining a constant water level Suspension wire is of the smallest practical size for suspending the container Sieves – Sieve cloth is mounted on substantial frames, constructed as to prevent loss of material during sieving, and conforms to the requirements of AASHTO M 92 Oven – An oven of appropriate size capable of maintaining a uniform temperature of 110 ± 5 C (230 ± 9 F)	aratus Image: Second Secon	

Remarks:

Date:	Technician:	IA Observer:
Dale.		

Technician's E-mail Address: _

Employer's/Supervisor's E-mail Address: _____