Equipment Checklist FM 5-509 Rolling Straight Edge

	Р	F	N/A
atus			
Rolling Straight Edge: 15 ft w/readout gauge with low and high reading marks to the nearest one sixteenth inch			
Manual Straight Edge: 15 ft length and not deficient in the excess of one sixteenth inch			
Shims: Four clean three-sixteenth inch shims			
Shims: Four clean three-eights inch shims			
String Line: String line to check deficiency of manual straight edge to less than one sixteenth inch			
	Rolling Straight Edge: 15 ft w/readout gauge with low and high reading marks to the nearest one sixteenth inch Manual Straight Edge: 15 ft length and not deficient in the excess of one sixteenth inch Shims: Four clean three-sixteenth inch shims Shims: Four clean three-eights inch shims String Line: String line to check deficiency of manual straight edge to less than one	atus Rolling Straight Edge: 15 ft w/readout gauge with low and high reading marks to the nearest one sixteenth inch Manual Straight Edge: 15 ft length and not deficient in the excess of one sixteenth inch Shims: Four clean three-sixteenth inch shims Shims: Four clean three-eights inch shims String Line: String line to check deficiency of manual straight edge to less than one	atus Rolling Straight Edge: 15 ft w/readout gauge with low and high reading marks to the nearest one sixteenth inch Manual Straight Edge: 15 ft length and not deficient in the excess of one sixteenth inch Shims: Four clean three-sixteenth inch shims Shims: Four clean three-eights inch shims String Line: String line to check deficiency of manual straight edge to less than one

Remarks:

 Date:
 ______Technician:
 IA Observer:

Technician's E-mail Address: _____

Employer's/Supervisor's E-mail Address: _____