Concrete Related Specifications & Documents

Summary of Changes 01/2015 – 01/2017





Section 346 Portland Cement Concrete



346-1 Description

- Changed name of Producer listing to match Materials Acceptance and Certification System (MAC)
- Administrative changes in wording to match MAC



346-2.2 Types of Cement

- Added Type IL cement for use in all classes of concrete and as an alternate to Type II (MH) in mass concrete
- Restricted high alkali cement in extremely aggressive environments or in mass concrete



346-2.2 Types of Cement cont'd

- Clarified the percent by weight of individual components for blended cement (Type IS, IP, IL)
- When ternary blends are used, clarified the test requirements
- Designated the surface resistivity values for ternary blends in the various environments



346-2.2 Types of Cement cont'd

 Clarified Table 1 by adding Type IL cement to the moderately and extremely aggressive environment columns. Added ternary blend cements to the extremely aggressive environment column



346-2.3 Pozzolans and Slag

- Deleted the requirement for fly ash or slag in class II (3400) and class I (3000) concrete used in a slightly aggressive environment
- Deleted any references to ternary blend cements and moved information to 346-2.2



346-2.4 Coarse Aggregate Gradation

 Added requirement for input from the District Materials Office with producer Quality Control Plan acceptance when using size #8 or #89 in a concrete design mix



346-2.5.2 Air Entrainment Admixtures

 Clarified the use of an air entrainment admixture for dry cast concrete



346-2.5.5 Corrosion Inhibitor Admixture

 Clarified precast concrete when using a nonchloride admixture types C or E



346-3.1 General

- Clarified the air content range for all classes of concrete
- Clarified various acronyms
- Added footnote g to table 2 and reference g in the column for target slump value
- Placed footnotes a thru f in table format



346-3.2 Drilled Shaft Concrete

- Clarified ambient temperature conditions for drilled shaft concrete for summer and normal conditions
- Clarified requirement to perform slump loss test at the anticipated ambient temperature



346-3.3 Mass Concrete

- Clarified the requirement for the Mass Concrete Control Plan
- Clarified the duties of the Specialty Engineer
- Clarified reduced monitoring of the elements
- Clarified what a Mass Concrete Control Plan is not required for

346-3.4 Flowing Concrete for Precast/Prestressed Concrete

 Deleted requirement to perform surface resistivity test



346-5 Sampling and Testing Methods

346-5 Table 5

- Updated the Method column
- Added ASTM C1758 to the Method column
- Added footnote requiring the concrete cylinders to be delivered to the lab in their molds and the lab to demold the cylinders



346-6 Quality Control

346-6.1 General

 Updated the requirements to meet the new Specification 105. Deleted requirement for the narrative



346-7.3 On-site Batching and Mixing

 Deleted requirement for the narrative in the Contractor's Quality Control Plan



346-7.5 Concreting in Hot Weather

Clarified the high end of the temperature requirement



346-7.6 Adding Water to Concrete at the Placement Site

- Clarified where water may be added
- Clarified what happens when the slump is outside the tolerance range



346-7.7 Sample Location

- Deleted requirement for the narrative in the Contractor's Quality Control Plan
- Clarified the requirements for the sample correlation



346-8 Plastic Concrete Sampling and Testing

- Clarified QC sampling frequency increase when five loads in two days of production for the same mix design are outside the specified tolerances
- Deleted reference to amending the Contractor's QC plan



346-9.1 General

Clarified the test age for compressive strength



346-9.2 Sampling Frequency

 Deleted reference to amending the Contractor's QC plan



346-9.2.1 Reduced Frequency for Acceptance Tests

 Clarified exception for the precast/prestress production facility



346-9.5 Resolution Procedure

- Clarified the comparison results for the verification cylinders and the verification hold cylinder
- Expanded the test window for the QC and V hold cylinders
- Deleted reference to the Contractor's Quality Control Plan



346-10 Investigation of Low Strength Concrete and Structural Adequacy

346-10.1 General

- Clarified and reorganized this subsection
- Engineer will determine whether to core or require a structural analysis
- Before taking core samples the Engineer must approve



346-10 Investigation of Low Strength Concrete and Structural Adequacy

346-10.2 Investigation and Determination of Structural Adequacy

- Clarified the requirements for determining whether to make an investigation at no additional cost to the Department
- Clarified the core strength limit



346-10 Investigation of Low Strength Concrete and Structural Adequacy

346-10.3 Coring for Determination of Structural Adequacy

 Clarified the material to be used to repair core holes



Questions?







Section 347 Portland Cement Concrete – Class NS



347-2.1 General

 Added recycled asphalt pavement (RAP) may be used and the quantity to be used



347-2.4.2 Aggregate Storage

- Deleted requirement for aggregate type to be identified
- Deleted the access for the Engineer to sample aggregate



347-3 Production, Mixing and Delivery

347-3.1 Concrete Production Requirements

- Identified the type of production facility approved to produce for the Department
- Clarified the moisture test requirement and the time frames
- Clarified the title of agency the scale company must be registered with



347-3 Production, Mixing and Delivery

347-3.3 Delivery

Defined the allowable time for delivery to include placement



347-4 Control of Quality

347-4.1 Concrete Mix Design

 Clarified the submittal process and the requirements to accompany the submittal



347-4 Control of Quality

347-4.3 Records

 Clarified the records which are required to retained at the production facility



347-5 Certification and Acceptance

347-5.1 General

- Clarified when the delivery ticket must be furnished
- Clarified the reference to the Contract Documents
- Deleted the option for the Engineer to accept the concrete



Questions







Section 921 Portland Cement and Blended Cement



921-1 General

921-.1.1 Type of Cement

 Added type IL blended cement and deleted type IP(MS)



921-1 General

921-.1.2 Alkali Content

- Deleted only
- Deleted alkali silica reactive test for both coarse and fine aggregate
- When high alkali cement is used new test requirements are spelled out



921-1 General

921-.1.3 Heat of Hydration

- Added type IL cement requiring a heat of hydration
- Deleted reference to ASTM C186 and the requirement at seven days
- Added a reference to ASTM C1702 and the three day requirement

921-2 Terminology

Placed definitions in alphabetical order



921-5 Quality Control Plan

921-5.1 General

- Changed copy of the monthly mill test report to monthly mill test report
- Changed FDOT work to Department work



921-5 Quality Control Plan

921-5.2 Acceptance of Portland Cement

- Deleted the word printed
- Changed the word provided to submitted



921-5 Quality Control Plan

921-5.5 Sampling of Cement

 Deleted the 10 pound size and added the one quart size



Questions







Section 923Water for Concrete



923-2 Evaluation of Water for Concrete

923-2.1 General

 Deleted provide and added submit to the producers test data submittal



923-3.1 Testing

Added acronym for Standard Methods



923-3.2 Recycled and Reclaimed Water

- Table 1 -- Added Standard Method 2540B to the test method column and deleted AASHTO T26 from the test method column
- Table 1 Increased the maximum (%) for total chlorides in the maximum (%) column
- Table 1 Redefined total sulfates in the chemical test column

923-3.3 Open Bodies of Water and Well Water

- Renamed the Alkalinity Calculated in terms of Calcium Carbonate by deleting Acidity or
- Table 2 -- Added Standard Method 2320B and 2540E to the test method column and deleted AASHTO T26 from the test method column
- Table 2 Increased the maximum (%) for total chlorides in the maximum (%) column

923-3.3 Open Bodies of Water and Well Water Cont'd

 Table 2 – Deleted total sulfates in the chemical test column as a requirement



Questions







Section 924 Admixtures for Concrete



924-2 Acceptance of Admixtures

924-2.2 Certification

 Administrative change – deleted the word provide and added submit



924-2 Acceptance of Admixtures

924-2.7 For Corrosion Inhibitors

 Administrative change – deleted the word furnish and added submit, also deleted the word with



Questions







Section 929 Pozzolans and Slag



929-1 Basis for Source Approval

929-1.1 General

- Administrative change added the word Section and deleted the -3
- Changed name of Producer listing to match Materials Acceptance and Certification System (MAC)



929-1 Basis for Source Approval

924-1.2 Approved Laboratory

- Clarified paragraph for ease of reading
- Added requirement for proficiency sample results to be forwarded to the State Materials Office



929-2 Fly Ash

- 924-2.2 Fly Ash (Class F)
 929-2.2.1 Petroleum Coke Class F
- Deleted test method ASTM C1012, ASTM C1202, ASTM G109, and FM 5-522
- Added test method FM C1012 and FM 5-578



929-2 Fly Ash

924-2.2 Fly Ash (Class F) 929-2.2.2 Bark Ash Class F

 Added requirements for improved results when tested and compared to ASTM C618 Class F



929-2 Fly Ash

929-2.3 Fly Ash (Class C)

- Added requirements for improved results when tested and compared to ASTM C618 Class C
- Added other durability test in accordance with 929-2.2.1



929-2 Metakaolin

929-4.1 General

- Deleted the requirement for a crystalline silica on the material safety data sheet
- Deleted test method ASTM C1012, ASTM C1202, ASTM G109, and FM 5-522
- Added test method FM C1012 and FM 5-578



929-2 Metakaolin

929-4.1 General

Clarified requirement for an independently approved testing laboratory



Questions









9.2.1 Purpose

Administrative changes in wording to match MAC



9.2.2 Authority

Administrative change in reference only



9.2.3 Scope

Administrative change for clarity and consistency with other Material Manuals



9.2.4 References

Administrative change for clarity and consistency with other Material Manuals



9.2.5 General Information

Administrative changes in wording to match MAC



- 9.2.6 Concrete Producers Roles and Responsibilities
- 9.2.6.3.1 Wetting Coarse Aggregate Stockpiles, Storage Bins and Silos
- Administrative changes in wording to match MAC



- 9.2.6 Concrete Producers Roles and Responsibilities
- 9.2.6.8 Batching Accuracy
- Administrative changes in wording to match MAC



9.2.6 Concrete Producers Roles and Responsibilities

- 9.2.6.9 Substitution of Materials
- Added requirement for approval of substitution before concrete placement
- Administrative changes in wording to match MAC



9.2.6 Concrete Producers Roles and Responsibilities

- 9.2.6.9 Substitution of Materials Cont'd
- Added approval of substitution of fly ash, mix may contain only one fly ash and require a new mix number
- Deleted cement and added cementitious



9.2.6 Concrete Producers Roles and Responsibilities

- 9.2.6.9 Substitution of Materials Cont'd
- Moved wording for clarification
- Deleted the requirement for a chloride test for a fly ash or aggregate substitution new mix design



9.2.7 Design Mixes

- Relocated items to be included with mix design submittals for clarity
- Clarified air content requirement



9.2.7 Design Mixes Cont'd

- Clarified the specification reference
- Clarified where proposed design mixes verified out of state should be sent to
- Deleted requirement to verify hot weather mix design for slab replacement mixes



- 9.2.7 Design Mixes
- 9.2.7.1 Concrete trial mix temperature between 68 to 86 degrees F (standard temperature mixes)
- Clarified air content range



- 9.2.7 Design Mixes
- 9.2.7.2 Concrete trial mix temperature of 94 degrees F (hot weather mixes)
- Clarified air content range



- 9.2.7 Design Mixes
- 9.2.7.4 Concrete trial mix for Specification Section 353 (slab replacement)
- Clarified procedure and test to be performed during verification procedure
- Added time frame for adding the accelerator after completion of initial mixing

9.2.12 Quality Control Program

Administrative changes in wording to match MAC



9.2.13 Personnel

Changed certified to qualified personnel



- 9.2.13 Personnel
- 9.2.13.2 Qualified Technicians
- Added the word qualified to title of subsection



- 9.2.13 Personnel
- 9.2.13.3 Concrete Production Facility Manager of Quality Control
- Clarified the title of the NRMCA qualification
- Administrative changes in wording to match MAC



9.2.14 Records

- Administrative changes in wording to match MAC
- Deleted requirement for the absorption worksheet to be retained



- 9.2.15 Sampling and Testing of Materials
- 9.2.15.1 General
- Administrative changes in wording to match MAC
- Deleted requirement for the absorption test in Table 1
- Deleted records retention time frame



- 9.2.15 Sampling and Testing of Materials
- 9.2.15.1 General Cont'd
- Deleted plant absorption data to confirm aggregate producer's value



- 9.2.15 Sampling and Testing of Materials
- 9.2.15.2 Chloride Testing
- Deleted plant chloride certification requirement
- Added requirement to enter chloride data into the Department's material data base and the time frame for entering data



- 9.2.15 Sampling and Testing of Materials
- 9.2.15.2 Chloride Testing
- Administrative changes in wording to match MAC
- Updated SMO contact for accepting chloride testing laboratories
- Updated SMO contacts for submitting failing chloride results

9.2.18 Forms

Updated Appendix B



Questions

- Contact
 - State Materials Office
 - Michael Bergin,
 - 352-955-6666
 - michael.bergin@dot.state.fl.us
 - Donnie Bagwell,
 - 352-955-6645
 - donald.bagwell@dot.state.fl.us

