

ROCK BASE – ACCEPTANCE PROGRAM.

(REV 9-16-09) (FA 11-9-09) (1-14)

SUBARTICLE 200-7.2.2 (Page 206) is deleted and the following substituted:

200-7.2.2 Frequency: Conduct QC sampling and testing at a minimum frequency listed in the table below. The Engineer will perform verification sampling and tests at a minimum frequency listed in the table below.

| Mainline Pavement Lanes, Turn Lanes, Ramps, Parking Lots, Concrete Box Culverts and Retaining Wall Systems | | |
|--|-----------------------------------|-----------------------------|
| Test Name | Quality Control | Verification |
| Modified Proctor Maximum Density | One per eight consecutive LOTs | One per 16 consecutive LOTs |
| Density | One per LOT | One per eight LOTs |
| Roadway Surface | Ten per LOT | Witness |
| Roadway Thickness | Three per LOT | Witness |

| Shoulder-Only, Bike/Shared Use Path and Sidewalk Construction | | |
|---|---------------------------------|-------------------|
| Test Name | Quality Control | Verification |
| Modified Proctor Maximum Density | One per two LOTs | One per four LOTs |
| Density | One per LOT | One per two LOTs |
| Surface | Five per 500 feet | Witness |
| Thickness | Three per 1000 consecutive feet | Witness |