


0

0



FRENCH DRAIN SYSTEM

GENERAL NOTES

- Pipe shall be any of the optional types permitted in Section 443 of the Specifications unless otherwise restricted in the plans. Dissimilar types of pipe will not be permitted. in a continuous run of pipe.
- 2. Concrete pipe shall be placed with the slots positioned on sides.
- 3. Alianment joints are standard (aaskets not required). Recorrugation of metal pipe ends not required.
- 4. The contractor may submit other methods of providing slots having equal or greater area of opening, for approval by the Engineer,
- 5. Filter fabric shall be Subsurface Drainage type meeting the requirements of Section 985. All filter fabric joints shall lap a minimum of one (1) foot.
- The standard cross section shall be constructed unless other section(s) described or detailed in the plans.
- 7. For supplemental details see Index No. 280.
- 8. The contractor shall take the necessary precautions to prevent contamination of the trench with sand, sill and foreign materials,
- 9. The I2" diameter weep hale shall be eliminated, when the bottom of the inlet is below the normal water table, unless otherwise shown in the plans.
- 10. French drains following the hypical cross section shall be poid for under the contract unit price for French Drains, IF. The unit price shall include the cost of pipe, pipe plugs, pipe fittings, corner aggregate and filter fack in pipe, and the cost for french exceeding, bootfill and composition. The unit price shall also include the cost for disposal of supulse accorded inderfals and cost for restoration of prement removed or damaged by french drain construction, but shall not include payments for items paid for elsewhere.

French drains with a significantly different cross section shall be paid for under the contract unit prices for separate items as follows:

- (a) Slotted or Perforated Pipe Culvert, LF, Unit price
 - shall include cost for nine, nine pluas and fittings in place.
- (b) Ballast Rock (French Drain Aggregate), CY, Unit price shall include cost for coarse aggregate in place, and cost for trench excavation, backfill and compaction. The unit price shall also include the cost for disposal of surplus excavated materials and cost for restoration of pavement removed or damaged by french drain construction, but shall not include payment for items paid for
- (c) Plastic Filter Fabric (Subsurface), SY, Unit price shall be for cost of fabric in place. Quantity shall be determined by plan neat dimensions of the fabric envelope.


DESIGN NOTES

- I. Pipe invert should be at or above the water table whenever possible.
- 2. French drains with minor dimensional changes or otherwise different from the standard cross-section shall be either described or detailed in the plans.
 - French drains with significantly different cross-sections shall be detailed in the plans.

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION

FRENCH DRAIN

	Names	Dates	Approved By S & Mchemra				
esigned By	ws	09/85					
Irawn By	RWR	09/83	Revision	Sheet No.	Index No.		
hecked By	ECR	09/83	00	I of 2	285		



FRENCH DRAIN									
	Names	Dates	Approved By & a Mchemons						
Dealgned By			State Brainage Engineer						
Drawn By			Revision	Sheet No.	Index No.				
Checked By			00	2 of 2	285				

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION ROAD DESIGN
