


Note: Numbers shown inside modules indicate mass in pounds of sand. All modules are approximately 3' in diameter with heights ranging from 3' to 3'-9".

INERTIAL CRASH CUSHION ARRAYS



0

0

Pallet Shall Be Constructed Of Wood Or Other Frangible Or Resilient Materials Other Than Metals, And, Shall Be Sufficiently Durable To Support Modules For Their Expected Period Of Uses Wood Pallet Detail Shown.

INERTIAL MODULE PALLET

NOTES FOR TEMPORARY INERTIAL CRASH CUSHIONS

- 1. The crash cushion arrays shown on this index can be used on the Slate highway system only for shielding temporary converted barrier wall approach mods (of where called for by the plans, or to!) where the use of realrier/lev cards bushions is decidered indexible by the Engineer Appearament use of inertial modes will require site specific design. These arrays can not be substituted for realrierlive crash cushions called for in the plans without expressed approach gother Engineer and, such approved substitutions are not eligible for VEEP considerations.
- Inertial crash cushions are goting type crash cushions, and a clear runout area book of the array must be provided. The arrays shown can be used for outer roadway applications, exclusive of pore areas, and for median applications where the median width is sufficient to provide Clear zone width between the book side mobile and the near lane of the apposition furfic.
- Inertial crash cushion modules shall be installed in occordance with the manufacturer's specifications and recommendations, and can be constructed of either new or functionally sound used modules.
- 4. Anchorage of barrier wall end segment is not required.
- 5. A yellow post mounted Type I Object Marker shall be centered 3' in front of the nose of all crash cushion arrays. Mounting hardware shall be in accordance with Index Nos. II860 and II865. The cost of the Object Marker shall be included in the cost of the modules.
- 6. Temporary inertial crash cushions are to be paid for per module under the contract unit price for Impact Attenuator Modules (Inertial) (Temporary), EA.

00 | 10f | 2

TEMPORARY INERTIAL CRASH CUSHIONS FOR SHIELDING ENDS OF TEMPORARY CONCRETE BARRIER WALL