



GENERAL NOTES

- All vehicles, equipment, workers (except flaggers), and their activities are restricted at all times to one side of the roadway.
- Minimum length of work area is 200'. Maximum length to be determined by the Engineer, but in no case to exceed the length of one-half ($\frac{1}{2}$) days operation or 2 miles whichever is less.
- If the work operation does not exceed 60 minutes, traffic control will be in conformance with Index No. 607.
- Additional one-way control may be effected by the following means:
 (1) Flag-carrying vehicle; (2) Official vehicle;
 (3) Pilot vehicles; (4) Traffic signals.
 When flaggers are the sole means of one-way control the flaggers shall be in sight of each other or in direct communication at all times.
- The first two warning signs shall have an 18" x 18" orange flag and a Type B light attached and operating at all times. Mesh signs may be used for (Daylight Only) operations. Type B Lights and Orange Flags are not required.
- The FLAGGER legend sign may be substituted for the symbol sign.
- The ONE LANE ROAD AHEAD and FLAGGER signs are to be removed or fully covered when no work is being performed and the highway is open to two-way traffic.
- Arrows denote direction of traffic only and do not reflect pavement markings.
- Longitudinal dimensions are to be adjusted to fit field conditions. See Index No. 600.
- When a side road intersects the highway on which work is being performed additional traffic control devices shall be erected in accordance with other applicable TCZ indexes.
- For general TCZ requirements and additional information, refer to Index No. 600.

TYPICAL APPLICATIONS

Pavement Repair
 Pavement Surfacing
 Utility Work
 Delineator Maintenance
 Crack Sealing
 Core Boring

CONDITIONS

WHERE ANY VEHICLE, EQUIPMENT, WORKERS OR THEIR ACTIVITIES REQUIRE AN INTERMITTENT OR CONTINUOUS MOVING OPERATION ON THE PAVEMENT WHERE THE AVERAGE SPEED OF MOVEMENT IS LESS THAN 4 MILES PER HOUR

SYMBOLS

- Work Area
- Sign With 18" x 18" (Min.) Orange Flag And Type B Light
- Type I Or Type II Barricade Or Vertical Panel Or Cone Or Tubular Marker Or Drum
- Work Zone Sign
- Flagger

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION ROAD DESIGN			
TRAFFIC CONTROL THROUGH WORK ZONES			
TWO-LANE, TWO-WAY • RURAL			
MOVING OPERATIONS - DAYLIGHT ONLY			
Drawn By	DATE	Approved By	
Drawn By	DATE	Checked By	DATE
Checked By	DATE	of 1	606