



R*: See SUPERELEVATION Index No. 600.

GENERAL NOTES

1. The first two warning signs shall have an 18" x 18" (min.) orange flag and a Type B light attached and operating at all times.
2. For speed sign applications see Index No. 600.
3. Where the tangent distance (T) exceeds 600', spacing between cones or tubular markers may be increased to 50' or spacing between Type I or Type II barricades, vertical panels or drums may be increased to 100' within limits of the tangent, or post mounted delineators at 50' centers may be substituted for the barricades, vertical panels or drums.
4. On the existing pavement all existing markings within the realignment which conflict with the revised traffic pattern are to be removed and removable pavement markings used for marking a new centerline and edge lines.
5. Where the tangent distance (T) exceeds 600' and no passing or stopping sight distance restrictions exist, the yellow reflectORIZED markings used to indicate the centerline of the traveled way may be replaced with yellow reflectORIZED markings in a broken pattern. For raised pavement marker application see Index No. 600 and Index No. 17352.
6. Arrows denote direction of traffic only and do not reflect pavement markings.
7. Longitudinal dimensions are to be adjusted to fit field conditions. See Index No. 600.
8. When a side road intersects the highway on which work is being performed additional traffic control devices shall be erected in accordance with other applicable TCZ indexes.
9. If temporary structures are required on the diversion traffic control will be in conformance with Index No. 650.
10. For general TCZ requirements and additional information refer to Indexes Nos. 600 and 17352.
11. If posted speed for Work Zone is 45 mph or less use * ROAD WORK 1/2 MILE * and space accordingly.

When Other Construction Or Maintenance Operations Occur Within 1 mile, Signs To Be Omitted And Signing To Be Coordinated In Accordance With Index No. 600.

TYPICAL APPLICATIONS
 Bridge Construction
 Subgrade Restoration
 Culvert Repair Or Construction

CONDITIONS
 WHERE ANY VEHICLE, EQUIPMENT, WORKERS OR THEIR ACTIVITIES REQUIRE THE CLOSURE OF BOTH LANES AND A TEMPORARY DIVERSION IS CONSTRUCTED

SYMBOLS

- Work Area
- Sign With 18" x 18" (Min.) Orange Flag And Type B Light
- Type I Or Type II Barricade Or Vertical Panel Or Drum (With Steady Burning Light At Night Only).
- Type III Barricade (With Flashing Light)
- Work Zone Sign

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
 ROAD DESIGN

TRAFFIC CONTROL THROUGH WORK ZONES
TWO-LANE, TWO-WAY RURAL TEMPORARY CONNECTION DAY OR NIGHT OPERATIONS

Designed By	DATE	APPROVED BY	DATE
Drawn By	DATE	Checked By	DATE
Checked By	DATE	Scale	Sheet No.
		1 of 1	609