



SLIP BASE AND FOOTING DETAIL




SLEEVE & BASE PLATE DETAILS



Stub Size Equals Min. Sleeve Size Or Longer

STUB DETAIL



0.04" Thick Alum. Strip-2 Req'd Per Base

BOLT KEEPER DETAIL

SLIP BASE DETAILS

Column Size	Sleeve I.D. (Max)	Sleeve Height H	Weld	Base Plate	Radius R	Base Bolt Size	Base Bolt Length	Ft-lbs In-lbs	Hole Size A
4 x $\frac{1}{2}$	4 $\frac{1}{2}$	6	3 $\frac{1}{2}$	8	3 $\frac{1}{2}$	3 $\frac{1}{2}$	3	29 355	3 $\frac{1}{2}$
4 $\frac{1}{2}$ x $\frac{1}{2}$	4 $\frac{1}{2}$	6	3 $\frac{1}{2}$	8	3 $\frac{1}{2}$	3 $\frac{1}{2}$	3 $\frac{1}{2}$	29 355	3 $\frac{1}{2}$
5 x $\frac{1}{2}$	5 $\frac{1}{2}$	7	3 $\frac{1}{2}$	8	3 $\frac{1}{2}$	3 $\frac{1}{2}$	3 $\frac{1}{2}$	29 355	3 $\frac{1}{2}$
6 x $\frac{1}{2}$	6 $\frac{1}{2}$	8	3 $\frac{1}{2}$	9	1 $\frac{1}{2}$	3 $\frac{1}{2}$	3 $\frac{1}{2}$	48 580	3 $\frac{1}{2}$
8 x $\frac{1}{2}$	8 $\frac{1}{2}$	10	4	11	1	4	3 $\frac{1}{2}$	53 640	3 $\frac{1}{2}$

Note: Unless noted otherwise, all dimensions are in inches.

#### NOTES

1. Work this Standard with Standard Index Numbers IIB60 and IIB65.
2. To determine column (post) size and footing requirements use the required Sign Identification Number and Sign Height (H). Designs for Heights (H) lower than those listed in the Table are included in Standard Index Number IIB65.
3. Single Column installations are not allowed for heights (H) exceeding the maximum height shown in the Table, and for sign profiles (Sign Identification Numbers) without any design tabulated. In this event, the sign(s) will have to be supported by multiple columns (posts) featuring breakaway devices. See Standard Index Number 9535.
4. The Column (Post) material shall be aluminum. The size is given as outside diameter and wall thickness. Columns (posts) larger than 3 $\frac{1}{2}$  x  $\frac{1}{2}$  shall be non-frangible and shall be installed with breakaway supports and will have concrete footings and slip bases.
5. The foundation size is given as outside diameter and depth.
  - a) Fragile Supports Foundations for Fragile Supports do not require concrete. The column (post) shall be driven into the ground to the depth indicated. b) Breakaway Foundation for Breakaway Foundations. The column support shall be set in a concrete foundation, sized as shown in the table. The first dimension indicates the diameter and the second dimension the depth into the ground. In all cases the ground is to be considered as undisturbed earth, road material, or properly compacted fill.
6. SLIP BASE NOTES :
  - a) The inside diameter (I.D.) of the sleeve shall be no more than  $\frac{1}{8}$ " larger than the Outside Diameter (O.D.) of the Column.
  - b) The sleeve bolts shall be 12  $\frac{1}{2}$  with locknuts. The bolts shall be galvanized steel (ASTM A-307) or Aluminum Association Alloy 2024-T4 or 6061-T6 (ASTM B-201).
  - c) The base bolts, nuts and washers shall be high strength bolts and shall have an electroplated zinc coating SC3, Type II applied in accordance with ASTM B-83.
  - d) An alternate cast base of aluminum alloy 256 and T6 temper in lieu of the fabricated base may be submitted for approval by the Engineer. If a cast base is used the stub will be the same as the column and will be bolted to the casting.
  - e) Assemble the slip base connection in the following manner : Connect column to sleeve using two (2) 1 $\frac{1}{2}$   $\frac{1}{2}$  machine bolts. Assemble top base plate to stub base plate using high strength bolts with three (3) hardened washers per bolt. One (1) washer per bolt and two (2) bolt keeper plates go between the base plates. Use lockwashers if required by the engineer. Tighten all bolts to maximum possible with a 12" to 15" wrench to bed the washers and shims and to clear the bolt threads. Loosen each bolt one (1) turn and retighten to the prescribed torque (see table). Bolts shall be tightened with properly calibrated wrenches under the supervision of the project engineer.
  - f) Burr threads at junction with nut using a center punch to prevent nut loosening.
  - g) Use galvanized steel shims to obtain a tight fit between the column face and the sleeve. Place shims in all quadrants between the 3 $\frac{1}{2}$  x  $\frac{1}{2}$  sleeve bolts. The shim length shall be 1" shorter than the height of the sleeve.

#### COLUMN SIZE, COLUMN HEIGHT & COLUMN FOOTINGS

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION  
ROAD DESIGN

#### SINGLE COLUMN GROUND SIGNS

Approved By	(Signature)
Designated By	DES 10/14/14
Drawn By	DOOR 10/14/14
Checked By	PES 10/14/14
State Structure Design Register No.	10863
Sheet No.	1 of 2
Index No.	


80 M.P.H.  
LOADING

COL. SIZE	$2 \times \frac{1}{2}$	$2\frac{1}{2} \times \frac{1}{2}$	$3 \times \frac{1}{2}$	$3\frac{1}{2} \times \frac{1}{2}$	$4 \times \frac{1}{2}$	$4\frac{1}{2} \times \frac{1}{2}$	$5 \times \frac{1}{2}$	$6 \times \frac{1}{2}$	$8 \times \frac{1}{2}$
FOUNDATION	$0 \times 4-6$	$0 \times 4-9$	$0 \times 4-9$	$0 \times 6-0$	$2-0 \times 4-0$	$2-0 \times 4-0$	$2-0 \times 4-3$	$2-0 \times 5-0$	$2-0 \times 5-6$
HEIGHT (FT.)									
Sign Identification Number	(+)	to	(+)	to	(+)	to	(+)	to	(+)
1		14	14	17	17	24	24	25	
2		14	14	20	20	25			
3				17	17	25			
4		7	7	11	11	21	21	25	
5									
6				12	12	21	21	25	
7				6	6	14	14	17	17
8				17	17	21	21	25	
9									
10				19	19	25			
11				14	14	25			
12				12	12	21	21	25	
13					13	13	17	17	20
14				14	14	25			
15				12	12	23	23	25	
16				12	12	24	24	25	
17				12	12	21	21	25	
18				8	8	16	16	20	20
19					14	14	18	18	22
20					11	11	14	17	17
21				7	7	11	11	21	21
22				10	10	16	16	23	23
23				9	9	19	19	23	23
24				9	9	17	17	21	21
25				12	12	24	24	25	
26				12	12	23	23	25	
27				12	12	21	21	25	
28				12	12	22	22	25	
29				12	12	21	21	25	
30				11	11	20	20	24	24
31				9	9	17	17	21	21
32				8	8	16	16	20	20
33				11	11	19	19	23	23
34				9	9	17	17	21	21
35				10	10	18	18	22	22
36				8	8	16	16	20	20
37					12	12	16	16	20
38					11	11	15	15	18
39					11	11	13	13	17
40									
41					10	10	11	11	13
42						10	10	11	11
43							13	13	20
44							20	20	25
45							20	20	25
46							20	20	25
47							20	20	25
48							19	19	25
49							18	18	25
50							17	17	25
51							17	17	25
52							17	17	25

COL. SIZE	$2 \times \frac{1}{2}$	$2\frac{1}{2} \times \frac{1}{2}$	$3 \times \frac{1}{2}$	$3\frac{1}{2} \times \frac{1}{2}$	$4 \times \frac{1}{2}$	$4\frac{1}{2} \times \frac{1}{2}$	$5 \times \frac{1}{2}$	$6 \times \frac{1}{2}$	$8 \times \frac{1}{2}$
FOUNDATION	$0 \times 4-6$	$0 \times 4-9$	$0 \times 4-9$	$0 \times 6-0$	$2-0 \times 4-0$	$2-0 \times 4-0$	$2-0 \times 4-3$	$2-0 \times 5-0$	$2-0 \times 5-6$
HEIGHT (FT.)									
Sign Identification Number	(+)	to	(+)	to	(+)	to	(+)	to	(+)
53						16	16	25	
54						15	15	25	
55						14	14	25	
56						9	9	13	13
57							13	13	24
58							12	12	24
59							12	12	23
60							12	12	23
61							8	8	13
62								12	12
63								12	12
64							6	6	12
65									11
66									11
67									10
68									10
69									10
70									9
71									9
72									9
73									8
74									8
75									7
76									7
77									13
78									7
79									12
80									12
81									11
82									13
83									13
84									10
85									10
86									10
87									11
88									12
89									12
90									19
91									19

The Column Size is O.D. x Wall Thickness in Inches

The Foundation Size is O.D. x Depth in feet & inches.  
A zero O.D. means that a concrete foundation is not necessary.

COLUMN SIZE , COLUMN HEIGHT & COLUMN FOOTINGS		Approved By	
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION ROAD DESIGN			
SINGLE COLUMN GROUND SIGNS			
Names	Date	Approved By	
Designed By	DES / / / /	State Structure Design Engineer	
Drawn By	DOD / / / /	Sheet No.	
Checked By	FES / / / /	Index No.	2 of 2
M.P.H. WIND LOADING			