



LENGTH OF ACCESS LANES (m)		
Grade	D ₁	D ₂
2% or less	180	470
3 to 4% Upgrade	160	705
3 to 4% Downgrade	215	280

NOTES

1. A lane closure analysis will be required to determine the times of day that this crossover can be in operation.
2. Arrows denote direction of traffic only and do not reflect pavement markings.

SYMBOLS

- Work Area
- Work Zone Sign
- Cone Or Tubular Marker
- Advance Warning Vehicle

Maximum Spacing Between Cones And Tubular Markers Shall Be 7.5 m.

$$L (\text{Min.}) = \frac{WS}{1.6}$$

S = Existing Posted Speed (km/h)

THE SEALED RECORD OF THIS STANDARD IS ON FILE IN THE ROADWAY DESIGN OFFICE.

TEMPORARY CROSSOVER FOR MEDIAN WIDTHS FROM 15.3 m TO < 22.5 m

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION 605 SUWANNEE STREET TALLAHASSEE, FLORIDA 32399-0450		
TRAFFIC CONTROL THROUGH WORK ZONES TEMPORARY CROSSOVER		
INTERIM STANDARD	APPROVED BY <i>James A. Mills</i> James A. Mills, P. E. #16344	INDEX NO. 0631
THIS SHEET REPLACES INDEX NO. 631 (SHEET 2 OF 2) OF THE METRIC ROADWAY AND TRAFFIC DESIGN STANDARDS, BOOKLET DATED JANUARY 2000.	REVISION NO. 00	SHEET NO. 2 of 2