



**SIGNAL PLACEMENT AT RAILROAD CROSSING
(2 - LANE DESIGN)**




**SIGNAL PLACEMENT AT RAILROAD CROSSING
(4 - LANE DESIGN)**




Note :
Arrows denote direction of travel not lane indication


FIGURE 1
Gate Length Requirements
See Note 6 Sheet 3




TYPE I



TYPE II



TYPE III




TYPE IV

* When 10' is deemed impracticable the control device can be located as close as 2' from the edge of a paved shoulder but not less than 6' from the edge of the near traffic lane.

Note :
Two separate foundations may be required (one for signals, one for gate), depending on type of equipment used.


- General Notes**
- No guardrail is proposed for signals; however, some form of impact attenuation device may be specified for certain locations.
 - Advance flasher to be installed when and if called for in plans or specifications.
 - Top of foundation shall be no higher than 4" above finished shoulder grade.
 - Type of traffic control device
 - I Flashing signals
 - II Flashing signals with cantilever
 - III Flashing signals with gate
 - IV Flashing signals with cantilever & gate
 - V Gate
 - Class of traffic control devices
 - I Flashing signals - one track
 - II Flashing signals - multiple tracks
 - III Flashing signals and gates - one track
 - IV Flashing signals and gates - multiple tracks

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION				
RAILROAD GRADE CROSSING TRAFFIC CONTROL DEVICES				
Names	Dates	Approved By		
Designed By	4-76	<i>Charles Scott</i> State Traffic Standards Engineer		
Drawn By		Revision	Sheet No.	Index No.
Checked By	4-76	00	1 of 4	17882



ACUTE ANGLE (AND RIGHT ANGLE)

**SIGNAL PLACEMENT AT RAILROAD CROSSING
(2 LANES, CURB & GUTTER)**




OBTUSE ANGLE


**SIGNAL PLACEMENT AT RAILROAD CROSSING
(2 LANES, CURB & GUTTER)**

GENERAL NOTES


1. The location of flashing signals and stop lines shall be established based on future (or present) installation of gate with appropriate track clearances.
2. Where plans call for railroad traffic control devices to be installed in curbed medians, the minimum median width shall be 12'-6".
3. Location of railroad traffic control device is based on the distance available between face of curb & sidewalk. 0' to 6' - Locate device outside sidewalk. Over 6' - Locate device between face of curb and sidewalk.
4. Stop line to be perpendicular to edge of roadway, approx. 15' from nearest rail; or 8' from and parallel to gate when present.




TYPE I




TYPE II



TYPE III



TYPE IV




TYPE V

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
**RAILROAD GRADE CROSSING
TRAFFIC CONTROL DEVICES**


Names	Dates	Approved By		
Designed By	4-76	Charles A. Scott State Traffic Standards Engineer		
Drawn By		Revision	Sheet No.	Index No.
Checked By	4-76	00	2 of 4	17882

RAILROAD CROSSING AT TWO (2) - LANE ROADWAY



Stop Bar Perpendicular To Edge Of Travel Way Or 8' From & Parallel To Gate When Present



Stop Bar Perpendicular to Edge Of Travel Way Or 8' From & Parallel To Gate When Present.



RELATIVE LOCATION OF CROSSING TRAFFIC CONTROL DEVICES



NOTES:

1. When computing pavement message, quantities do not include transverse lines.
2. Placement of sign W10-1 in a residential or business district, where low speeds are prevalent, the W10-1 sign may be placed a minimum distance of 100' from the crossing. Where street intersections occur between the R/R pavement message and the tracks an additional W10-1 sign and additional pavement message should be used.
3. Recommended location for sign FTP-38, 100' Urban & 300' Rural in advance of the crossing.
4. A portion of the pavement markings symbol should be directly opposite the W10-1 sign.
5. Recommended location for FTP-38 A or B signs, 100' urban and 300' rural. See index 17355 for sign details.


* 6. Gate Length Requirements

For two-way undivided sections:

The gate should extend to within 1' of the center line. On multilane approaches the maximum gate length may not reach to within 1' of the center line. For those cases, the distance from the gate to the center line shall be a maximum of 4'.

For one-way or divided sections:

The gate shall be of sufficient length such that the distance from the gate tip to the inside edge of pavement is a maximum of 4'.




SPEED MPH	" A " IN FT
60	550
55	450
50	375
45	300
40	225
35	150
30	100
URBAN	50 MIN.

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION


RAILROAD GRADE CROSSING TRAFFIC CONTROL DEVICES

Names	Dates	Approved By		
Designed By	10-77	C. Clark A. Scott State Traffic Standards Engineer		
Drawn By		Revision	Sheet No.	Index No.
Checked By		00	3 of 4	17882



RAILROAD GATE ARM LIGHT SPACING

Specified Length Of Gate Arm	Dimension "A"	Dimension "B"	Dimension "C"
14 Ft.	6"	36"	5'
15 Ft.	18"	36"	5'
16-17 Ft.	24"	36"	5'
18-19 Ft.	28"	41"	5'
20-23 Ft.	28"	4'	5'
24-28 Ft.	28"	5'	5'
29-31 Ft.	36"	6'	6'
32-34 Ft.	36"	7'	7'
35-37 Ft.	36"	9'	9'
38 And Over	36"	10'	10'



**MEDIAN SIGNAL GATES FOR
MULTI LANE UNDIVIDED URBAN SECTIONS**
(THREE OR MORE DRIVING LANES IN ONE DIRECTION, 45 mph OR LESS)

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION				
RAILROAD GRADE CROSSING TRAFFIC CONTROL DEVICES				
Names	Dates	Approved By		
Designed By	10-85	<i>Charles A. Scott</i> State Traffic Standards Engineer		
Drawn By	10-85	Revision	Sheet No.	Index No.
Checked By		00	4 of 4	17882