



Maximum spacing between cones and tubular markers shall be 25'
 Maximum spacing between Type I or Type II barricades or vertical panels or drums shall be based on the speed limit as follows:
 15' up to 25 MPH; 30' for 30 - 40 MPH;
 50' for 45 MPH and greater.

When Other Construction Or Maintenance Operations Occur Within 1 mile, Sign(s) To Be Omitted And Signing To Be Coordinated In Accordance With Index No. 600.

Cones Or Tubular Markers At 25' Centers For First 250' Thereafter At 50' Centers Or Either Type I Or Type II Barricades Or Vertical Panels Or Drums At 50' Centers For First 25' Thereafter At 100' Centers.

GENERAL NOTES

- All vehicles, equipment, workers (except flaggers) and their activities are restricted at all times to one side of the roadway.
- If the work operation does not exceed 60 minutes, traffic control will be in conformance with Index No. 607.
- When four or more work vehicles enter the through traffic lanes in a one hour period or less, the advanced FLAGGER sign shall be substituted for the WORKERS sign. For location of flaggers and FLAGGER signs, see Index No. 603
- The first two warning signs shall have a 18" x 18" (min.) orange flag and a Type B light attached and operating at all times.
 Mesh signs may be used for (Daylight Only) operations
 Type B Lights and Orange Flags are not required.
- The WORKERS legend sign may be substituted for the symbol sign.
- All signs shall be post mounted if the work operation time exceeds 12 hours.
- $L (min) = \frac{WS}{2}$ for speeds ≥ 45 mph
 $= \frac{WS^2}{120}$ for speeds ≤ 40 mph
- Arrows denote direction of traffic only and do not reflect pavement markings.
- Longitudinal dimensions are to be adjusted to fit field conditions. See Index No. 600.
- WORKERS sign to be removed or fully covered when no work is being performed.
- When a side road intersects the highway on which work is being performed additional traffic control devices shall be erected in accordance with other applicable TCZ Indexes.
- For general TCZ requirements and additional information refer to Index No. 600.

Where:
 W = Width of shoulder in feet, 8' minimum.
 S = Posted speed limit (mph)

SYMBOLS

- Work Area
- Sign With 18" x 18" (Min.) Orange Flag And Type B Light
- Type I Or Type II Barricade Or Vertical Panel Or Drum (With Steady Burning Light At Night Only).
 (Tubular Markers May Be Used During Daylight Only).
 Cones May Be Used -See Index 600).
- Work Zone Sign

TYPICAL APPLICATIONS

- Utility Work
- Culvert Extensions
- Side Slope Work
- Guardrail Work
- Landscaping Work
- Cleaning Drainage Structures
- Reworking Ditches
- Sign Installation And Maintenance
- Shoulder Repair

CONDITIONS

WHERE ANY VEHICLE, EQUIPMENT, WORKERS OR THEIR ACTIVITIES ENCROACH THE AREA CLOSER THAN 15' BUT NOT CLOSER THAN 2' TO THE EDGE OF PAVEMENT

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION				
TRAFFIC CONTROL THROUGH WORK ZONES				
TWO-LANE, TWO-WAY • RURAL DAY OR NIGHT OPERATIONS				
Names	Dates	Approved By		
Designed By	12/87	Roadway Design Engineer		
Drawn By	12/87	Revision	Sheet No.	Index No.
Checked By	12/87	00	1 of 1	602