

UTILITY PIPES THRU FRENCH DRAIN

FRENCH DRAIN SYSTEM

STANDARD CROSS SECTION (ENLARGED)

GENERAL NOTES

- Pipe shall be any of the optional types permitted in Section 443 of the Specifications unless otherwise restricted in the plans. Dissimilar types of pipe will not be permitted in a continuous run of pipe.
- 2. Concrete pipe shall be placed with the slots positioned on sides.
- 3. Alignment joints are standard (gaskets not required). Recorrugation of metal pipe ends not required.
- 4. The contractor may submit other methods of providing slots having equal or greater area of opening, for approval by the Engineer.
- 5. Filter fabric shall be Subsurface Drainage type meeting the requirements of Section 985. All filter fabric joints shall lap a minimum of one (1) foot.
- 6. The standard cross section shall be constructed unless other section(s) described or detailed in the plans.
- 7. For supplemental details see Index No. 280.
- 8. The contractor shall take the necessary precautions to prevent contamination of the trench with sand, silt and foreign materials.
- 9. French drains following the typical cross section shall be paid for under the contract unit price for French Drains, LF. The unit price shall include the cost of pipe, pipe plugs, pipe fittings, coarse aggregate and filter fabric in place, and the cost for trench excavation, backfill and compaction. The unit price shall also include the cost for disposal of surplus excavated materials and cost for restoration of pavement removed or damaged by french drain construction, but shall not include payments for items paid for elsewhere.

French drains with a significantly different cross section shall be paid for under the contract unit prices for separate items as follows:

- (a) Slotted or Perforated Pipe Culvert, LF. Unit price shall include cost for pipe, pipe plugs and fittings in place.
- (b) Ballast Rock (French Drain Aggregate), CY. Unit price shall include cost for coarse aggregate in place, and cost for trench excavation, backfill and compaction. The unit price shall also include the cost for disposal of surplus excavated materials and cost for restoration of pavement removed or damaged by french drain construction, but shall not include payment for items paid for elsewhere.
- (c) Plastic Filter Fabric (Subsurface), SY. Unit price shall be for cost of fabric in place. Quantity shall be determined by plan neat dimensions of the fabric envelope.

DESIGN NOTES


- I. Pipe invert should be at or above the water table whenever possible.
- 2. French drains with minor dimensional changes or otherwise different from the standard cross-section shall be either described or detailed in the plans.

French drains with significantly different cross-sections shall be detailed in the plans.

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION


FRENCH DRAIN


	Names	Dates	1/			
Designed By	MPS	09/83	State Drainage Engineer			
Drawn By	RWR	09/83	Revision	Sheet No.	Index No.	
Checked By	EGR	09/83	04	1 of 2	285	




ELLIPTIC	ELLIPTICAL PIPE					
_	Slot Cut					
Pipe Size	Opening C					
	Min.	Мах.				
14"x23"	10"	12"				
19"x30"	<i>14</i> "	<i>1</i> 6"				
24"x38"	<i>14</i> "	<i>16</i> "				
29"x45"	20"	22"				
34"x53"	20"	22"				
38"x60"	20"	22"				

ROUND PIPE						
Slot Cut						
Opening C						
Min.	Мах.					
12"	/4"					
12"	14"					
<i>16"</i>	18"					
16"	18"					
22"	24"					
22"	24"					
22"	24"					
24"	26"					
24"	26"					
24"	26"					
24"	26"					
	Slot Oper C Min. 12" 16" 22" 22" 22" 24" 24"					







SIDE VIEW




SECTION AA



SECTION BB





OPTION A - ROUND PIPE

OPTION B - ROUND OR ELLIPTICAL PIPE

SLOTTED PIPE OPTIONS

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION

FRENCH DRAIN

	Names	Dates	Approve	. //	
Designed By			State Drainage Engineer		
Drawn By			Revision	Sheet No.	Index No.
Checked By			00	2 of 2	285