



Maximum Spacing Between Cones And Tubular Markers Shall Be 25'  
 Maximum Spacing Between Type I Or Type II Barricades Or Vertical  
 Panels Or Drums Shall Be Based On The Speed Limit As Follows:  
 15' Up To 25 MPH; 30' For 30-40 MPH; 50' For 45 MPH And Greater.

Cones Or Tubular Markers At 25' Centers For First 250'  
 Thereafter At 50' Centers Or Either Type I Or Type II Barricades  
 Or Vertical Panels Or Drums At 50' Centers For First 250'  
 Thereafter At 100' Centers.

### GENERAL NOTES

- All vehicles, equipment, workers (except flaggers) and their activities are restricted at all times to one side of the roadway.
- If the work operation does not exceed 60 minutes, traffic control will be in conformance with Index No. 607.
- When four or more work vehicles enter the through traffic lanes in a one hour period or less, the advanced FLAGGER sign shall be substituted for the WORKERS sign. For location of flaggers and FLAGGER signs, see Index No. 603.
- The first two warning signs shall have a 18" x 18" (min.) orange flag and a Type B light attached and operating at all times.  
 Mesh signs may be used for (Daylight Only) operations  
 Type B Lights and Orange Flags are not required.
- The WORKERS legend sign may be substituted for the symbol sign.
- All signs shall be post mounted if the work operation time exceeds 12 hours.
- $L (min) = \frac{WS}{2}$  for speeds  $\geq 45$  mph  
 $= \frac{WS^2}{120}$  for speeds  $\leq 40$  mph  
 Where:  
 W = Width of shoulder in feet, 8' minimum.  
 S = Posted speed limit (mph)
- Arrows denote direction of traffic only and do not reflect pavement markings.
- Longitudinal dimensions are to be adjusted to fit field conditions. See Index No. 600.
- WORKERS sign to be removed or fully covered when no work is being performed.
- When a side road intersects the highway on which work is being performed additional traffic control devices shall be erected in accordance with other applicable TCZ Indexes.
- For general TCZ requirements and additional information refer to Index No. 600.

### TYPICAL APPLICATIONS

- Utility Work
- Culvert Extensions
- Side Slope Work
- Guardrail Work
- Landscaping Work
- Cleaning Drainage Structures
- Reworking Ditches
- Sign Installation And Maintenance
- Shoulder Repair

### CONDITIONS

WHERE ANY VEHICLE, EQUIPMENT,  
 WORKERS OR THEIR ACTIVITIES  
 ENCROACH THE AREA CLOSER  
 THAN 15' BUT NOT CLOSER THAN  
 2' TO THE EDGE OF TRAVEL WAY.

### SYMBOLS

- Work Area
- Sign With 18" x 18" (Min.) Orange Flag And Type B Light
- Type I Or Type II Barricade Or Vertical Panel Or Drum (With Steady Burning Light At Night Only).  
 (Tubular Markers May Be Used During Daylight Only.  
 Cones May Be Used - See Index No. 600.)
- Work Zone Sign

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION				
TRAFFIC CONTROL THROUGH WORK ZONES				
<b>TWO-LANE, TWO-WAY • RURAL DAY OR NIGHT OPERATIONS</b>				
Names	Dates	Approved By		
Designed By	12/87			
Drawn By	12/87	Roadway Design Engineer		
Checked By	12/87	Revision	Sheet No.	Index No.
		04	1 of 1	602