



Maximum Spacing Between Cones And Tubular Markers Shall Be 25'
 Maximum Spacing Between Type I Or Type II Barricades Or Vertical
 Panels Or Drums Shall Be Based On The Speed Limit As Follows:
 15' Up To 25 MPH; 30' For 30-40 MPH; 50' For 45 MPH And Greater.

Cones Or Tubular Markers At 25' Centers For First 250'
 Thereafter At 50' Centers Or Either Type I Or Type II Barricades
 Or Vertical Panels Or Drums At 50' Centers For First 250'
 Thereafter At 100' Centers.

GENERAL NOTES

- All vehicles, equipment, workers and their activities are restricted at all times to one side of the roadway.
- If the work operation encroaches on the through traffic lanes or when four or more work vehicles enter the through traffic lanes in a one hour period a flagger shall be provided and a FLAGGER sign shall be substituted for the WORKERS sign. The flagger shall be positioned at the point of vehicle entry or departure from the work area.
- This TCZ plan also applies to work performed in the median more than 2' but less than 15' from the edge of either pavement.
- The first two warning signs, each side, shall have a 18" x 18" (min.) orange flag and a Type B light attached and operating at all times. Mesh signs may be used for (Daylight Only) operations. Type B Lights and Orange Flags are not required.
- The WORKERS legend sign may be substituted for the symbol sign.
- $L (min) = \frac{WS}{2}$ for speeds ≥ 45 mph
 $= \frac{WS^2}{120}$ for speeds ≤ 40 mph
- Arrows denote direction of traffic only and do not reflect pavement markings.
- Longitudinal dimensions are to be adjusted to fit field conditions. See Index No. 600.
- When work is being performed on a multilane undivided roadway the signs normally mounted in the median (as shown) shall be omitted.
- WORKERS signs to be removed or fully covered when no work is being performed.
- END ROAD WORK signs required only when work exceeds one daylight period.
- When a side road intersects the highway on which work is being performed additional traffic control devices shall be erected in accordance with other applicable TCZ Indexes.
- If the work operation is less than 60 minutes, signs, barricades, vertical panels, cones, tubular markers, or drums will not be required provided vehicles in the work area have warning light(s) operating.
- For general TCZ requirements and additional information refer to Index No. 600.

TYPICAL APPLICATIONS

- Utility Work
- Culvert Extensions
- Side Slope Work
- Guardrail Work
- Landscaping Work
- Cleaning Drainage Structures
- Reworking Ditches
- Sign Installation And Maintenance
- Shoulder Repair

CONDITIONS

WHERE ANY VEHICLE, EQUIPMENT, WORKERS OR THEIR ACTIVITIES ENCROACH THE AREA CLOSER THAN 15' BUT NOT CLOSER THAN 2' TO THE EDGE OF TRAVEL WAY.

SYMBOLS

- Work Area
- Sign With 18" x 18" (Min.) Orange Flag And Type B Light
- Type I Or Type II Barricade Or Vertical Panel Or Drum (With Steady Burning Light At Night Only). (Tubular Markers May Be Used During Daylight Only. Cones May Be Used - See Index No. 600.)
- Work Zone Sign

Where:
 W = Width of lateral transition in feet, 8' minimum.
 S = Posted speed limit (mph)

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION				
TRAFFIC CONTROL THROUGH WORK ZONES				
MULTILANE DIVIDED OR UNDIVIDED RURAL • DAY OR NIGHT OPERATIONS				
Names	Dates	Approved By		
Designed By	12/87	Roadway Design Engineer		
Drawn By	12/87	Revision	Sheet No.	Index No.
Checked By	12/87	04	1 of 1	611