



GENERAL NOTES

1. Work operations shall be confined to two way left turn lane, leaving the adjacent lanes open to traffic.
2. The first two warning signs, each side, shall have an 18" x 18" (min.) Orange Flag and a Type B light attached and operating at all times. Mesh signs may be used for (Daylight Only) operations, Type B Lights and Orange Flags are not Required.
3. Advance Warning Vehicle will have an Advanced Warning Arrow Panel in the Warning Mode.
4. Longitudinal dimensions are to be adjusted to fit field conditions. See Index No. 600.
5. When a side road intersects the highway on which work is being performed additional traffic control devices shall be erected in accordance with other applicable TCZ Indexes.
6. For general TCZ requirements and additional information, refer to Index No. 600.

TYPICAL APPLICATIONS

Pavement Repair
Utility Work

CONDITIONS

WHERE ANY VEHICLE, EQUIPMENT, WORKERS OR THEIR ACTIVITIES ARE BEING CONDUCTED IN THE TWO WAY LEFT TURN LANE.

SYMBOLS

- Work Area
- Type I Or Type II Barricade Or Vertical Panel Or Drum (With Steady Burning Light At Night Only). (Tubular Markers May Be Used During Daylight Only. Cones May Be Used - See Index No. 600.)
- Work Zone Sign
- Work Vehicle With Flashing Beacon (optional)
- Advance Warning Vehicle Equipped With Advance Warning Arrow Panel And Truck Mounted Attenuator
- Sign With 18" x 18" (Min.) Orange Flag And Type B Light

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION				
TRAFFIC CONTROL THROUGH WORK ZONES				
TWO WAY LEFT TURN LANE CLOSURE				
Designed By	Names	Dates	Approved By	
Drawn By			Roadway Design Engineer	
Checked By			Revision	Sheet No. Index No.
			04	1 of 1 628