



**UNSIGNALIZED**

**SIGNALIZED**

**SYMBOLS**

- Work Area
- Sign With 18" x 18" (Min.) Orange Flag And Type B Light
- Type I Or Type II Barricade Or Vertical Panel Or Drum ( With Steady Burning Light At Night Only ).  
(Tubular Markers May Be Used During Daylight Only. Cones May Be Used - See Index No. 600.)
- Channelizing Device ( See Index No. 600 )
- Work Zone Sign
- Flagger
- Stop Bar
- Lane Identification + Direction of Traffic

**GENERAL NOTES**

1. All vehicles, equipment, workers ( except flaggers ) and their activities are forbidden in lane and intersection areas reserved for traffic.
2. The FLAGGER legend sign may be substituted for the symbol sign.
3. When vehicles in a parking zone block the line of sight to TCZ signs, the signs shall be post mounted and located in accordance with Index No. 17302.
4. If the work space extends across a crosswalk, the crosswalk should be closed using the information in Index No. 660.
5. Flaggers shall be located where they can control more than one direction of traffic.  
Flaggers shall be in sight of each other or in direct communication at all times.
6. Maximum spacing between channelizing devices shall be not greater than 20'.
7. Temporary signal phasing modifications are to be approved by the District Traffic Operations Engineer prior to the beginning of work.
8. For general TCZ requirements and additional information refer to Index No. 600.

**DURATION NOTES**

1. ROAD WORK AHEAD AND END ROAD WORK sign may be omitted if all of the following conditions are met:
  - a) Work operations are 60 minutes or less.
  - b) Speed is 45 mph or less.
  - c) No sight obstructions to vehicles approaching the work area for a distance equal to A plus B
  - d) Vehicles in the work area have high-intensity, rotating, flashing, oscillating, or strobe lights operating.
  - e) Volume and complexity of the roadway has been considered.

| DISTANCE BETWEEN SIGNS |              |     |
|------------------------|--------------|-----|
| Speed                  | Spacing (ft) |     |
|                        | A            | B   |
| 40 mph or less         | 200          | 200 |
| 45 mph                 | 350          | 350 |

**CONDITIONS**

WHERE ANY VEHICLE, EQUIPMENT, WORKERS OR THEIR ACTIVITIES ENCROACH ON THE PAVEMENT REQUIRING THE CLOSURE OF A PORTION OF ONE OR MORE TRAFFIC LANES IN AN INTERSECTION.



2006 FDOT Design Standards

**TWO-LANE TWO-WAY, WORK IN INTERSECTION**

Last Revision 07/01/05  
Sheet No. 1 of 1  
Index No. 604