

This Pier Protection Barrier has been structurally evaluated to be equivalent or greater in strength to other safety shape traffic barriers which have been crash tested to NCHRP Report 350 TL-5 criteria. This barrier meets the requirements of the AASHTO LRFD Bridge Design Specifications for a barrier used for bridge pier protection.



**GENERAL NOTES:**

- Concrete shall be Class III or IV unless otherwise called for in the plans. Exposed concrete surfaces shall have a Class 3 surface finish in accordance with Section 521 of the Specifications, unless another finish is called for in the plans. The surfaces shall have a Class 5 Applied Finished Coating in accordance with Section 400 only when called for in the plans.
- Construct Pier Protection Barrier continuous without transverse contraction or expansion joints. Transverse construction joints may be used at a spacing greater than or equal to 40'. Provide longitudinal reinforcing steel continuous across construction joints.
- When the Pier Protection Barrier is installed adjacent to Roadway or Shoulder pavement, compact the top 12" of the subgrade to at least 100% of the density as defined in the AASHTO T-99 specifications.
- Isolate Barrier Wall Inlets, Index 218, from Pier Protection Barriers and Footings with 1" expansion material.
- On roadways designated for reverse laning, mark all downstream barrier ends that are not shielded or outside the clear zone with Type 3 Object Markers. Include the cost of the Object Marker in the cost of the Pier Protection Barrier.
- Payment: Pier Protection Barrier and Crash Wall to be paid for under the contract unit price for Shoulder Concrete Barrier Wall (Rigid-Shoulder 42"), LF, or Shoulder Concrete Barrier Wall (Rigid-Shoulder 54"), LF.

**INSTRUCTIONS TO DESIGNER:**


- As used in this standard, setback distance is as defined by LRFD. See PPM and Index 700 for minimum recoverable terrain and horizontal clearance requirements.
- Establish the offset from the Pier Protection Barrier to the bridge pier, column or pile bent based on project constraints.
- Determine the required Pier Protection Barrier height, i.e. 42" or 54", in accordance with the requirements of the LRFD Bridge Design Specifications and the Structures Design Guidelines.
- Determine the appropriate limiting stations of the Pier Protection Barrier and its end treatment(s) using the Pier Protection Barrier Length of Advancement diagrams provided.
- Select Pier Protection Barrier terminal treatment for design speeds greater than or equal to 50 mph:
  - Terminated outside of the clear zone of any approach traffic;
  - Terminated within a shielded location;
  - Terminal protection by the use of a crash cushion system; or,
  - Terminated in conjunction with a suitably designed transition to another barrier.
- Determine the appropriate footing configuration(s) (T, Front Cantilever or Back Cantilever) for a continuous run of Pier Protection Barrier using the Pier Protection Barrier Footing Layout Schematics. Select the footing configuration(s) based on traffic control needs and locations of piers, pier footings, utilities, drainage structures, etc. as shown. Footing configurations along a continuous run of Pier Protection Barrier may be intermixed as shown.
- Designate the Pier Protection Barrier height, footing configuration(s) and limiting stations on the Plan-Profile sheets, e.g.:
 

Begin 42" Pier Protection Barrier with Front Cantilever Footing, Sta. 100+00.00
- Indicate Crash Wall locations (when required) and lengths on the Plan-Profile sheets. Designate Crash Wall height to match height of adjacent Pier Protection Barrier.
- In absence of continuous concrete barrier, determine guardrail requirements in accordance with Indexes 400 and 410.
- Show Cross Sections as required to locate Pier Protection Barrier, Crash Wall (when required) and footings adjacent to bridge piers, columns or footings, drainage structures, utilities, etc.
- Prepare Traffic Control Plans to accommodate Pier Protection Barrier, Crash Wall (when required) and footing construction.
- Include length(s) of Crash Walls (measured along front face) in length of Pier Protection Barrier for payment.
- Although intended for shielding bridge piers, the Pier Protection Barrier can be used on a project specific basis to shield other critical roadside objects when deemed necessary or appropriate.




**PLAN VIEW**  
**PIER PROTECTION BARRIER FOOTING LAYOUT SCHEMATICS**

Design Speed mph	X (Length Of Advancement) Ft.
≤ 45	= 16 (D-d)
≥ 50	= 13 (D-d)



(LEFT SIDE OPPOSITE HAND)  
**ONE-WAY TRAFFIC**



**DETAIL 'A'**  
(Guardrail not shown for clarity)


**NOTE:**

Length of Advancement determined from the diagrams and equations shown establishes the location of the upstream beginning length of need for a Pier Protection Barrier, however, the Length of Advancement for the combination of Pier Protection Barrier and required guardrail can be no less than that required by other details of Index 400.

**Equation Variables:**

D = Distance in feet from the near edge of the near approach traffic lane to either (a) the back of pier, when the pier is located inside the Setback Distance or (b) the Setback Distance, when the pier extends to or goes beyond the Setback Distance. For left side piers on two-way undivided facilities, D is measured from the inside edge of the near approach traffic lane.

d = Distance in feet from the near edge of the near approach traffic lane to the Pier Protection Barrier gutter line at its intersection with the departure line or the face of guardrail at its intersection with the departure line. For left side hazards on two-way undivided facilities, d is measured from the inside edge of the near approach traffic lane.



**TWO-LANE TWO-WAY TRAFFIC**

**NOTE:**

See Index 400 for Clear Zone and Horizontal Clearance Length of Advancement Diagrams.

PPB = Pier Protection Barrier


**LENGTH OF ADVANCEMENT DIAGRAMS - PIER PROTECTION BARRIER WITH GUARDRAIL CONTINUATION**




2008 FDOT Design Standards

**PIER PROTECTION BARRIER**

Last Revision	Sheet No.
07/01/06	2 of 10
Index No.	
<b>411</b>	




( LEFT SIDE OPPOSITE HAND )  
**ONE-WAY TRAFFIC**



**TWO-LANE TWO-WAY TRAFFIC**

NOTES:  
See Index 400 for Clear Zone and Horizontal Clearance Length of Advancement Diagrams.  
PPB = Pier Protection Barrier  
  
See Notes on Sheet 2.




**LENGTH OF ADVANCEMENT DIAGRAMS - PIER PROTECTION BARRIER WITH CONCRETE BARRIER WALL CONTINUATION**



2008 FDOT Design Standards

**PIER PROTECTION BARRIER**

Last Revision	Sheet No.
07/01/06	3 of 10
Index No.	
411	



NOTES:  
See Index 400 for Clear Zone and Horizontal Clearance Length of Advancement Diagrams.  
PPB = Pier Protection Barrier  
See Notes on Sheet 2.



**LENGTH OF ADVANCEMENT DIAGRAMS - PIER PROTECTION BARRIER WITH CRASH WALL AND GUARDRAIL CONTINUATION**



2008 FDOT Design Standards

**PIER PROTECTION BARRIER**

Last Revision	Sheet No.
07/01/06	4 of 10
Index No.	
<b>411</b>	



NOTES:  
 See Index 400 for Clear  
 Zone and Horizontal Clearance  
 Length of Advancement Diagrams.  
 PPB = Pier Protection Barrier

See Notes on Sheet 2.

**LENGTH OF ADVANCEMENT DIAGRAMS - PIER PROTECTION BARRIER WITH CRASH WALL  
AND CONCRETE BARRIER WALL CONTINUATION**




2008 FDOT Design Standards

**PIER PROTECTION BARRIER**

Last Revision	Sheet No.
07/01/06	5 of 10
Index No.	
<b>411</b>	

\* 12" x 12" x 1/4" galvanized steel back-up plate with 5/8" post bolts (either 17" or 21" long) and nuts with 5/8" plain round washers under nuts.

\*\* Attach thrie-beam terminal connector to Pier Protection Barrier with a 21" x 12" x 5/8" thrie-beam terminal connector plate and 5-1/8" x 15" long HS hex bolts and nuts with 5/8" plain round washers under heads and nuts.




NOTES

1. The Pier Protection Barrier radial segments are intended for use on approach and trailing ends of both one-way and two-way facilities. The guardrail connections shown on this sheet apply to one-way approaches and to the approaching and trailing ends of two-lane two-way facilities. On trailing ends of two-way multilane and one-way facilities the end connection on Index 410, Sheet 2 may be used.

For guardrail connections, see Index 410, Sheet 20.

2. Refer to Index No. 400 Detail J for additional guardrail information.




FOR USE WITH EITHER  
1:10 OR 1:15  
GUARDRAIL TRANSITIONS  
**STANDARD THRIE-BEAM  
OFFSET BLOCK  
(FIELD TRIMMED)**

ARC LENGTH (Ft.)	DISTANCE "x" (Ft.)	OFFSETS "y" "y" (Ft.)
4	4.00	0.06
8	7.99	0.26
12	11.98	0.58
16	15.96	1.02
20	19.91	1.60
21	20.91	1.76
24	23.85	2.30
25	24.83	2.49

Note: Barrier may be constructed in chords having lengths  $\le 4$  feet.

**FLARED END TREATMENT - PIER PROTECTION BARRIER WITH GUARDRAIL CONTINUATION**



NOTE:  
PPB = Pier Protection Barrier.



**END TREATMENT - PIER PROTECTION BARRIER WITH CONCRETE BARRIER WALL CONTINUATION**





2008 FDOT Design Standards

**PIER PROTECTION BARRIER**

Last Revision	Sheet No.
07/01/06	6 of 10
Index No.	
<b>411</b>	



END TRANSITION AND TAPERED TOE DETAILS - PIER PROTECTION BARRIER WITH GUARDRAIL CONTINUATION



- NOTES:  
1. See Sheet 9 for Footing Details.  
2. See Sheet 8 for Cross Sections.

ESTIMATED 42" PPB QUANTITIES		
ITEM	UNIT	QUANTITY
Concrete	CY/LF	0.141
Reinforcing Steel (w/out Bars 5V)	LB/LF	33.10

ESTIMATED 54" PPB QUANTITIES		
ITEM	UNIT	QUANTITY
Concrete	CY/LF	0.172
Reinforcing Steel (w/out Bars 5V)	LB/LF	48.74

NOTE:  
PPB = Pier Protection Barrier.


END TRANSITION DETAILS - PIER PROTECTION BARRIER WITH GUARDRAIL OR CONCRETE BARRIER WALL CONTINUATION

BILL OF REINFORCING STEEL		
MARK	SIZE	LENGTH
P	5	7'-6"
R	5	6'-7"
S	8	As Reqd.
42" PPB T1 & T2	8	13'-0"
54" PPB T1 & T2	8	21'-0"
V	5	9'-2"

REINFORCING STEEL NOTES:  
 1. All bar dimensions in the bending diagrams are out to out.  
 2. Bars 8S may be continuous or spliced at the construction joints. Lap splices for Bars 8S shall be a minimum of 4'-0".  
 3. The Contractor may utilize Welded Wire Reinforcement when approved by the Engineer. Welded Wire Reinforcement shall conform to ASTM A497.


NOTE: PPB = Pier Protection Barrier

**CONVENTIONAL REINFORCING STEEL BENDING DIAGRAMS**



**TRANSITION BARS 8T1 & 8T2**

**TRANSITION STIRRUP BARS 5P To Be Field Cut (10 of each required per Railing End Transition)**





**STIRRUP BAR 5P**

**STIRRUP BAR 5R**


**STIRRUP BAR 5V**

**END STIRRUP BAR 5V To Be Field Cut (Two required per Barrier End Transition w/ Tapered Toe)**




**BARRIER DETAILS**






SECTION A-A TYPICAL SECTION THRU BACK CANTILEVER FOOTING




SECTION B-B TYPICAL SECTION THRU T FOOTING



SECTION C-C TYPICAL SECTION THRU FRONT CANTILEVER FOOTING


BILL OF REINFORCING STEEL			REINFORCING STEEL NOTES: 1. All bar dimensions in the bending diagrams are out to out. 2. Lap splices for Bars 5B shall be a minimum of 2'-2". 3. The Contractor may use Welded Wire Reinforcement when approved by the Engineer. Welded Wire Reinforcement shall conform to ASTM A 497.
MARK	SIZE	LENGTH	
A	5	6'-8"	
B	5	As Req.	
U	5	14'-0"	




ESTIMATED BARRIER FOOTING QUANTITIES		
ITEM	UNIT	QUANTITY
Concrete	CY/LF	0.335
Reinforcing Steel (w/ Bars 5V) Cantilever Footing	LB/LF	64.32
Reinforcing Steel (w/ Bars 5V) T Footing	LB/LF	63.01

- NOTES:
- Provide 3" lip when optional construction joint is used. Omit 3" lip adjacent to Barrier Wall Inlets and as required to provide 2" min. clear between Cantilever Footing and adjacent Pier Footing or Column.
  - See Sheets 7 & 8 for Barrier Details.

BARRIER FOOTING DETAILS




**PLAN VIEW**  
(Concrete Barrier Wall Continuation shown, Guardrail Continuation similar)



**VIEW G-G**

\* Match height of adjacent Pier Protection Barrier




BILL OF REINFORCING STEEL		
MARK	SIZE	LENGTH
B	5	As Reqd.
C	5	6'-4" / 7'-4"
E	5	4'-8"
U	5	11'-0"

REINFORCING STEEL NOTES:  
 1. All bar dimensions in the bending diagrams are out to out.  
 2. Lap splices for Bars 5B shall be a minimum of 2'-2".  
 3. The Contractor may use Welded Wire Reinforcement when approved by the Engineer. Welded Wire Reinforcement shall conform to ASTM A 497.

ESTIMATED CRASH WALL & FOOTING QUANTITIES		
ITEM	UNIT	QUANTITY
Concrete (Footing)	CY/LF	0.260
Concrete (42" Crash Wall)	CY/LF	0.389
Concrete (54" Crash Wall)	CY/LF	0.500
Reinforcing Steel (42" Crash Wall)	LB/LF	66.06
Reinforcing Steel (54" Crash Wall)	LB/LF	70.23

NOTES:  
 1. Provide 3" lip when optional construction joint is used.  
 2. See Sheet 8 for Barrier Details and Sheet 9 for Barrier Footing details.



**SECTION H-H**

**CRASH WALL & FOOTING DETAILS**

NOTE:  
PPB = Pier Protection Barrier