

CONDITIONS


WHERE ANY VEHICLE, EQUIPMENT, WORKERS
OR THEIR ACTIVITIES ENCROACH ON THE
PAVEMENT REQUIRING THE CLOSURE OF ONE
TRAFFIC LANE, FOR WORK AREAS LESS THAN
200' DOWNSTREAM FROM AN INTERSECTION
FOR A PERIOD OF MORE THAN 60 MINUTES.

CONDITIONS

WHERE ANY VEHICLE, EQUIPMENT, WORKERS OR THEIR ACTIVITIES ENCROACH ON THE PAVEMENT REQUIRING THE CLOSURE OF ONE TRAFFIC LANE, FOR WORK AREAS 200' OR MORE DOWNSTREAM FROM AN INTERSECTION FOR A PERIOD OF MORE THAN 60 MINUTES.

SYMBOLS

Work Area



Type I Or Type II Barricade Or Vertical Panel
Or Drum (With Steady Burning Light At Night Only)

(Tubular Markers May Be Used During Daylight Only. Cones May Be Used - See Index No. 600.)

- Type I Or Type II Barricade Or Vertical Panel Or Drum (with Flashing Light At Night Only)
- ₩ork Zone Sign
- ☐ Flagger
- ⇒ Lane Identification + Direction of Traffic

- Work operations shall be confined to one travel lane, leaving the opposing travel lane open to traffic.
- When vehicles in a parking zone block the line of sight to TCZ signs or when TCZ signs encroach on a normal pedestrian walkway, the signs shall be post mounted and located in accordance with Index No. 17302.
- 3. If work area is confined to an outside auxiliary lane, the work area shall be barricaded and the FLAGGER signs replaced by ROAD WORK AHEAD signs. Flaggers are not required.
- 4. Flaggers shall be in sight of each other or in direct communication at all times.

- 5. The FLAGGER legend sign may be substituted for the symbol sign.
- 6. The maximum spacing between devices shall be no greater
- 7. For general TCZ requirements and additional information, refer to Index No. 600.
- 8. The two channelizing devices directly in front and directly at the end of the work area is occupied only by a vehicle with activated high-intensity rotating, flashing, oscillating, or strobe lights.

Sheet No.

1of 1