

CONDITIONS

WHERE ANY VEHICLE, EQUIPMENT, WORKERS OR THEIR ACTIVITIES ENCROACH ON THE PAVEMENT REQUIRING THE CLOSURE OF ONE TRAFFIC LANE, FOR WORK AREAS LESS THAN 200' DOWNSTREAM FROM AN INTERSECTION FOR A PERIOD OF MORE THAN 60 MINUTES.

CONDITIONS

WHERE ANY VEHICLE, EQUIPMENT, WORKERS OR THEIR ACTIVITIES ENCROACH ON THE PAVEMENT REQUIRING THE CLOSURE OF ONE TRAFFIC LANE, FOR WORK AREAS 200' OR MORE DOWNSTREAM FROM AN INTERSECTION FOR A PERIOD OF MORE THAN 60 MINUTES.

GENERAL NOTES

SYMBOLS



Work Area



Sign With 18" x 18" (Min.) Orange Flag And Type B Light

- Channelizing Device (See Index No. 600)
- Work Zone Sign
- Flagger
- ⇒ Lane Identification + Direction of Traffic

- 1. Work operations shall be confined to one travellane, leaving the opposing travellane open to traffic.
- 2. When vehicles in a parking zone block the line of sight to TCZ signs or when TCZ signs encroach on a normal pedestrian walkway, the signs shall be post mounted and located in accordance with Index No. 17302.
- 3. If work area is confined to an outside auxiliary lane, the work area shall be barricaded and the FLAGGER signs replaced by ROAD WORK AHEAD signs. Flaggers are not required.
- 4. Flaggers shall be in sight of each other or in direct communication at all times.

- 5. The FLAGGER legend sign may be substituted for the symbol sign.
- 6. The maximum spacing between devices shall be no greater than 25.
- 7. For general TCZ requirements and additional information, refer to Index No. 600.
- 8. The two channelizing devices directly in front and directly at the end of the work area may be omitted provided vehicles in the work area have high-intensity rotating, flashing, oscillating, or strobe lights operating.

DURATION NOTES

- 1. RDAD WORK AHEAD sign may be omitted if all of the following conditions are met:
- a) Work operations are 60 minutes or less.
- b) Speed is 45 mph or less.
- c) No sight obstructions to vehicles approaching the work area for a distance of 600 feet.
- d) Vehicles in the work area have high-intensity, rotating, flashing, oscillating, or strobe lights operating.
- e) Volume and complexity of the roadway has been considered.



2010 FDOT Design Standards

07/01/09

Sheet No. 1 of 1 Index No.