

Index 861 Bridge Pedestrian/Bicycle Railing (Aluminum)

Design Criteria

See Instructions for *Design Standards* [Index 862](#).

Design Assumptions and Limitations

Bridge Pedestrian/Bicycle Railing is limited to use on bridges with expansion joint thermal movements not exceeding 5". Scheme 3 is limited to bridge retrofit applications where additional sidewalk width is required.

See Instructions for *Design Standards* [Index 862](#) for additional information.

Plan Content Requirements

In the Structures and/or Roadway Plans:

Provide railing layout Control Drawings in the Plans to show post spacing, curb joint, V-groove, deck joint, expansion joint locations and Scheme number.

For existing bridge retrofits special end treatment details may be required for perpendicular or flared wingwalls at Begin and End Bridge. Provide existing railing removal details when required.

Include cross references to *Design Standards* Index 861 as appropriate.

When either Index 851 or 861 are acceptable, include cross references to both indexes and use Pay Items 515-2-1BB or 515-2-1BB as appropriate.

Payment

Item number	Item description	Unit Measure
515-2-1BB	Pedestrian, Bicycle Railing, Non Specified, 42" (Type ___)	LF
515-2-1BB	Pedestrian, Bicycle Railing, Non Specified, 54" (Type ___)	LF
515-2-3BB	Pedestrian, Bicycle Railing, Aluminum Only, 42" (Type ___)	LF
515-2-3BB	Pedestrian, Bicycle Railing, Aluminum Only, 54" (Type ___)	LF