




* These dimensions are measured perpendicular to the end of beam




END VIEW



ELEVATION AT END OF BEAM
(Flanges Not Shown For Clarity)
(End 1 Shown, End 2 Similar)



SECTION A-A FOR CONVENTIONAL REINFORCING
(Showing Bars 5K, 5Y & 5Z Only)



END 1

ELEVATION


END 2

CONVENTIONAL REINFORCING
BAR BENDING DETAILS

BILL OF REINFORCING STEEL

| MARK | NOTE NUMBERS | SIZE | NUMBER REQUIRED | LENGTH (NOTE 1) |
|------|----------------|---------------|-----------------|-----------------|
| A | — | 5 | 8 | 24'-0" |
| C1 | 9, 10 & 11 | 3 | 16 (End 1) | Varies |
| C2 | 9, 10 & 11 | 3 | 16 (End 2) | Varies |
| D1 | 9, 10, 11 & 14 | 3 | 32 (End 1) | Varies |
| D2 | 9, 10, 11 & 14 | 3 | 32 (End 2) | Varies |
| D3 | 9 & 14 | 3 | See Table | 4'-3" |
| K | 2, 9, 11 & 13 | 5 | See Table | 6'-5" |
| M1 | 9 & 10 | 4 | 14 (End 1) | Varies |
| M2 | 9 & 10 | 4 | 14 (End 2) | Varies |
| M3 | 9 | 4 | See Table | 3'-8" |
| N | 3 & 4 | 3/8" Ø Strand | 4 | Dim. L |
| Y | 9 & 11 | 5 | 12 | 4'-9" |
| Z | 2, 9, 11 & 13 | 5 | 10 | 5'-11" |





BENDING DIAGRAMS (See Note 1)



- NOTES:
- A. Work this Index with Index No. 20010 - Typical Florida-I Beam Details and Notes and the Florida-I Beam - Table of Beam Variables in Structures Plans.
 - B. For referenced notes, see Index No. 20010.
 - C. For Dimensions A, B, C, D, L, R & V1 and number of spaces S1 thru S4, see Florida-I Beam - Table of Beam Variables in Structures Plans.

6/29/2012 12:48:48 PM r0960rh C:\p\projects\standards\structures\2013book\20063-1of2.dgn

ALTERNATE REINFORCING STEEL (WELDED WIRE REINFORCEMENT) DETAILS



NOTES:
 a. See Sheet 1 for placement details & Table of Beam Variables in Structures Plans for variables S1, S2, S3, S4 & V1.
 b. Place Conventional Reinforcement Bars 5A & 3C as shown on Sheet 1. Place additional Bars 5Y as shown in Section A-A for Welded Wire Reinforcement. Bars 5Z will not be used with the WWR Option.
 c. Pieces may be fabricated in multiple length sections.
 d. For beams with skewed end conditions, Pieces D-1, D-2 & M-1 shall not be used; Conventional Reinforcement Bars D1, D2, C1, C2, M1 & M2 shall be used. See Index No. 20010 Skew Details and Note 9 for placement details. Shift Pieces K & Bars 5Y to accommodate skewed end conditions and align with Bars C and D.

LEGEND:
 EF = Each Face
 FF = Front Face
 BF = Back Face

C:\projects\standards\structures\2013book\20063-2of2.dgn
 rd960r/h
 12:48:50 PM
 6/29/2012

| | | | | | |
|---------------------------|--------------|--------------------------------------|---|--------------------|----------------|
| LAST REVISION 07/01/10 | DESCRIPTION: | FDOT DESIGN STANDARDS 2013 | FLORIDA-I 63 BEAM - STANDARD DETAILS | INDEX NO. 20063 | SHEET NO. 2 |
| REVISION | | | | | |