

DISTANCE BETWEEN SIGNS						
Speed	Spacir	Spacing (ft.)				
Jecu	Α	В				
40 mph or less	200	200				
45 mph	350	350				
50 mph or greater	500	500				

l able I							
Device Spacing							
Max. Distance Between Devices (ft.)							
Speed (mph)	Cones or Tubular Markers		Type I or Type II Barricades or Vertical Panels or Drums				
	Taper	Tangent	Taper	Tangent			
25	25	50	25	50			
30 to 45	25	50	30	50			
50 to 70	25	50	50	100			

*Midway between signs.

GENERAL NOTES

Work Area



Sign With 18" x 18" (Min.) Orange Flag And Type B Light

SYMBOLS

- Channelizing Device (See Index No. 600)
- Work Zone Sign
- Lane Identification + Direction of Traffic

≥ DESCRIPTION:

- 1. When four or more work vehicles enter the through traffic lanes in a one hour period or less (excluding establishing and terminating the work area), the advanced FLAGGER sign shall be substituted for the WORKERS sign. For location of flaggers and FLAGGER signs, see Index No. 603.
- 2. SHOULDER WORK sign may be used as an alternate to the WORKER symbol sign only on the side where the shoulder work is being performed.
- 3. When a side road intersects the highway within the TTC zone, additional TTC devices shall be placed in accordance with other applicable TCZ Indexes.
- 4. For general TCZ requirements and additional information, refer to Index No. 600.

DURATION NOTES

- 1. Signs and channelizing devices may be omitted if all of the following conditions are met:
- a. Work operations are 60 minutes or less.
- b. Vehicles in the work area have high-intensity, rotating, flashing, oscillating, or strobe lights operating.

Table II Taper Length - Shoulder

Taper Length - Shoulder						
Speed						
(mph)	8'	10'	12'	Notes		
	Shldr.	Shldr.	Shldr.			
25	28	35	42			
30	40	50	60	$L = \frac{WS^2}{}$		
35	55	68	82	60		
40	72	90	107			
45	120	150	180			
50	133	167	200			
55	147	183	220			
60	160	200	240	L=WS		
65	173	217	260			
70	187	233	280			

minimum shoulder width

 V_3L = Length of shoulder taper in feet

W = Width of total shoulder in feet (combined paved and unpaved width)

S = Posted speed limit (mph)

CONDITIONS

WHERE ANY VEHICLE, EQUIPMENT, WORKERS OR THEIR ACTIVITIES ENCROACH THE AREA CLOSER THAN 15' BUT NOT CLOSER THAN 2' TO THE EDGE OF TRAVEL WAY.

INDEX

NO.

602

LAST REVISION 07/01/12

2015 FDOT DESIGN STANDARDS

SHEET NO. 1 of 1