

- ALL EXISTING BUILDING STRUCTURE AND ENVELOPE TO REMAIN UNLESS OTHERWISE NOTED.
- REMOVE ALL DETERIORATED BUILDING COMPONENTS AS NOTED.
- CONTRACTOR TO NOTIFY OWNER OF ANY DAMAGE TO COMPONENTS SCHEDULED TO REMAIN.
- FIELD VERIFY ALL DIMENSIONS

EXISTING STRUCTURE TO REMAIN

REPLACE EXISTING PLYWOOD

AS REQUIRED. MATCH EXISTING THICKNESS

SELF-ADHERING SHEET UNDERLAYMENT

NEW 1 1/4" 22 GAUGE METAL R-PANEL

INSIDE CLOSURE PER MANUFACTURER RECOMMENDED PRACTICE

NEW ALUMINUM FASCIA WITH DRIP

EDGE EXTENDED BEYOND PANEL CLOSURE

ALUMINUM GUTTER AND DOWNSPOUT

PAINT EXPOSED BLOCKING TO MATCH EXISTING

REPLACE EXISTING BLOCKING

AS REQUIRED. MATCH EXISTING THICKNESS

ALUMINUM FASCIA AND DRIP EDGE BEHIND GUTTER

NEW ALUMINUM SOFFIT

