

## Index 700-010 Single Column Ground Signs

### Design Criteria

**AASHTO LRFD Specifications for Structural Supports for Highway Signs, Luminaires and Traffic Signals (LRFDLTS-1); Structures Manual (SM)**, Volume 3, FDOT Modifications to LRFDLTS-1; **Structures Manual (SM)** Introduction, I.6 References; **FDOT Design Manual (FDM)**

Both fabricated and cast base assemblies were impact tested by the **Texas Transportation Institute (TTI)**, College station, TX on February 10, 2003, and both alternate assemblies were determined to be compliant with the performance recommendations of the **National Cooperative Highway Research Program (NCHRP) Report 350**.

### Design Assumptions and Limitations

See notes on **Index 700-010**, **FDM 230**, **FDM 261**, and the **Structures Manual (SM)**, Volume 3.

**Index 700-010** contains instructions for the contractor to select the appropriate post size given the sign dimensions in the Plans.

The rectangular unidirectional slip-base sign support system can be used with any single post up to a mass of 45 lb/ft.

Foundation designs are based on the following conservative soil criteria which cover the majority of soil types found in Florida:

Classification = Cohesionless (Fine Sand)

Friction Angle = 30 degrees

Unit Weight = 50 pcf (assumed submerged)

### Plan Content Requirements

See the **FDM 325**.

### Payment

Item number	Item Description	Unit Measure
700-1-1B	Single Post Sign (F&I, Ground Mount)	AS

See the **BOE** and **Specification 700** for additional information on payment, pay item use and compensation.