


TWO-WAY TRAFFIC



ONE-WAY TRAFFIC END TRANSITION APPLICATION DETAILS

THRIE-BEAM GUARDRAIL TRAILING END TRANSITION

REVISION 07/01/15

FDOT


STANDARD PLANS


TEMPORARY DETOUR BRIDGE THRIE-BEAM GUARDRAIL


INDEX


SHEET 2 of 6

102-240











PLAN VIEW OF TRANSITION BLOCK (GUARDRAIL NOT SHOWN FOR CLARITY)




ELEVATION OF TRANSITION BLOCK (GUARDRAIL AND POSTS NOT SHOWN FOR CLARITY)

ESTIMATED QUANTITIES		
ITEM	UNIT	QUANTITY
Concrete Class NS	CY	0.4
Reinforcing Steel	LB	61
Guardrail (Reset)	LF	12.5



END VIEW A-A



#3 STIRRUP (FIELD BEND)

NOTES:

REINFORCING STEEL: Reinforcing steel shall be ASTM A615, Grade 60.

ANCHOR RODS: Steel Anchor Rods shall be ASTM A36, ASTM A709 Grade 36 or ASTM A615 Grade 60 hot-dip galvanized in accordance with Specification Section 962.

REVISION 07/01/13

DESCRIPTION:

FDOT