

## SYMBOLS:




DESCRIPTION:

- Channelizing Device (See Index 102-600)
- Work Zone Sign
- Type III Barricade
- Crash Cushion
- Lane Identification and Direction of Traffic

## NOTES:

- 1. This Index applies to multilane roadways, except with undivided roadways with 6 or more lanes, where the work requires the closure of the lanes in one direction and diversion is provided to convert the opposing traffic lanes to temporary two-way travel.
- 2. L = Taper Length
- B = Buffer Length
- X = Work Zone Sign Distance
- R = Radius of Curve
- See Index 102-600 for "L", "B", "X", channelizing device spacing values. See Plans for "R" values.
- 3. For undivided roadways with a tangent distance "T" less than 600', use "Double Reverse Curve" signs (W24-1A) instead of the first pair of "Reverse Curve" signs (W1-4B) and omit the second pair of "Reverse Curve" signs.
- 4. If the paved shoulder is less than 4' in width, omit the taper and channelizing devices shown on the paved shoulder.
- 5. Temporary Lane Separator may be used in lieu of Temporary Barrier for speed limits of 45 mph or less.



## NOTE:

Temporary pavement markings may be omitted when the work operation is in place for 3 days or less.

## SYMBOLS:

Work Area

■ Channelizing Device (See Index 102-600)

₩ork Zone Sign

Type III Barricade

Crash Cushion

Lane Identification and Direction of Traffic

REVISION 11/01/21

DESCRIPTION:

