Index 102-660 Sidewalk Closure & Index 102-661 Bicycle Lane Closure

Design Criteria

Manual on Uniform Traffic Control Devices (***MUTCD***); ***FDOT Design Manual (FDM)***

Design Assumptions and Limitations

See the ***Standard Plans Instructions*** for the ***102 Series – Temporary Traffic Control (TTC)***.

Indexes 102-660 and 102-661 provide rudimentary typical applications for sidewalk closures and bicycle lane closures, respectively. The primary purpose of ***Indexes 102-660*** and ***102-661*** is to establish minimum requirements for work zone signs and channelizing devices, and include scenarios that complement the pedestrian and bicycle accommodation guidelines provided in ***FDM 240***. Use these Indexes as a guide in establishing project specific pedestrian and bicycle accommodations in the ***TTC*** Plans.

Index 102-660, Pedestrian Detour - Option 2:

- For locations where sufficient length of low-profile barrier cannot be provided, Longitudinal Channelizing Devices can be used.
- This option should only be used when Option 1 is not feasible.

Plan Content Requirements

See ***FDM 922***.

Payment

Item number	Item Description	Unit Measure
102-4	Pedestrian and Bicycle Special Detour	LS

See the ***BOE*** and ***Specifications 102*** for information on payment, pay item use, and compensation.