

Index 521-660 Light Pole Pedestal - Bridge

Design Criteria

AASHTO LRFD Bridge Design Specifications; Structures Design Guidelines (SDG)

Design Assumptions and Limitations

Use this Index with Index 521-422, 521-423, 521-427, 521-428, 521-820, 515-021, 521-510 as appropriate.

Anchor Bolts were designed for Design Wind, Bridge Deck Height (above MLW), Luminaire Mounting Height, and Luminaire Arm Lengths of Standard Index 715-002 Light Poles with a maximum 40 foot luminaire mounting height.

Design of the additional bridge deck reinforcement is based on the minimum transverse top deck reinforcing required by the ***SDG***. The nominal load capacities given should be greater than the computed light pole loads calculated using the LRFD LTS Extreme Event I limit state.

Axial Dead Load = 1.56 kip

Wind Load Moment about Bridge Transverse Axis = 40.6 kip-ft

Wind Load Moment about Bridge Longitudinal Axis = 28.3 kip-ft

Dead Load Moment about Bridge Longitudinal Axis = 1.69 kip-ft

Torsion about Pole Axis = 3.56 kip-ft

Maximum Shear = 1.38 kip

Locate pedestals near a substructure support to minimize vibration of the light poles due to traffic live loads. Locate the centerlines of pedestals a minimum 3'-10" away from centerlines of open joints in railings and ends of railings.

Plan Content Requirements

In the Structures Plans:

Show Light Pole Pedestals on Plan and Elevation, Superstructure and Approach Slab Supplemental Detail sheets. Use stations or longitudinal dimensions along bridge to define pedestal locations. Include anchor bolt diameters.

Payment

No separate payment is made for Light Pole Pedestals. See Payment Note on the ***Standard Plan***.