Index 630-010 Conduit Details - Embedded

Design Criteria

NFPA National Electric Code; ***Structures Detailing Manual (SDM)***; ***AASHTO LRFD Bridge Design Specifications***; ***NCHRP Report 350*** or ***AASHTO Manual for Assessing Safety Hardware (MASH)*** and FDOT Structures Design Guidelines ***(SDG)***

Design Assumptions and Limitations

This standard can be used for electrical service for highway or navigation lighting and ITS applications.

The details for installing three 2" diameter conduits and associated Embedded Junction Boxes (EJBs) in traffic railings (as shown) have been determined to be crashworthy in accordance with the requirements of ***MASH*** and the ***AASHTO LRFD Bridge Design Specifications,*** for ***Standard Plans*** Index 521-422, 521-423, 521-427, 521-428, 521-509, 521-510, 521-511 and 521-512.

The details for installing two 2" diameter conduits and associated Embedded Junction Boxes (EJBs) in median traffic railings (as shown) have been determined to be crashworthy in accordance with the requirements of ***MASH*** and the ***AASHTO LRFD Bridge Design Specifications,*** for ***Standard Plans*** Index 521-426.

Plan Content Requirements

The maximum number of conduits is 3 in each concrete railing. Refer to ***SDG*** 6.7.1 for more guidance.

Provide supplemental designs, notes, details, wiring diagrams and wiring specifications in the plans as required to complement this Standard.

In the Structures and/or Retaining Wall Plans:

Designate each conduit and include supplemental plan details as shown in the following table:

Conduit Usage and Limits	Plan Requirements
Present use	Show supplemental project specific details and requirements to coordinate with conduit beyond bridge or retaining wall. Coordinate with the ITS, Lighting, etc. plans as required.
Future use with conduit limits consistent with limits shown on the Standard	Designate conduit as "Future Use", no additional plan details required to show conduit limits.

Future use with conduit limits not consistent with limits shown on the Standard	Show supplemental project specific details and requirements to coordinate with conduit beyond bridge or retaining wall. Coordinate with the ITS, Lighting, etc. plans as required.

For EJBs located within Traffic Railings, specify in the plans the type of EJBs required: EJB "A" - multiple raceways; EJB "B" - single raceways. Generally, multiple raceway EJBs can be used where services contained within individual raceways (conduits) can share a common Junction Box. Single raceway EJBs should be used where it is desirable or required that services contained within individual raceways (conduits) be isolated from each other.

Specify the type of fittings required at Expansion Joint locations on bridges: Expansion Fittings or Expansion / Deflection Fittings. Generally, Expansion Fittings can be used for bridges on tangent or large radius curved alignments where little or no transverse movement is expected at the Expansion Joints. Expansion / Deflection Fittings are typically required for bridges on curved alignments or combined curved and tangent alignments where transverse movement is expected at Expansion Joints.

For electrical service, specify the use of THWN or XHHW conductors.

Payment

Include pay items for Embedded Conduit and Embedded Junction Boxes. Conduit pay item includes Expansion and Expansion/Deflection Fittings and all associated hardware required to complete the installation.

Item Number	Item Description	Unit of Measure
630- 2-16	Conduit, Furnish & Install, Embedded	LF
635- 3- 13	Junction Box, Furnish & Install, Embedded	EA