

Index 706-001 Typical Placement of Raised Pavement Markers

Design Criteria

Manual on Uniform Traffic Control Devices (MUTCD), 2009 V. 2.16

Usage Criteria

Standard RPM Placement:

See [Specification 706](#). RPMs are used to supplement pavement markings for longitudinal delineation on all roadways as shown on **Index 706-001**, Sheet 1.

Index 706-001, Sheet 2 shows RPM placement at traffic channelizing locations and should be used at all such locations on Arterial and Collector roadways.

Optional RPM Placement:

Using RPMs to delineate median openings, islands, and traffic separators on Arterials and Collectors, as shown on **Index 706-001**, Sheets 3 and 4, is optional.

See **Index 711-003**, for additional RPM requirements on Limited Access Facilities.

Plan Content Requirements

In the Signing and Pavement Marking Plans:

Standard RPMs – No project specific details or quantities are required.

Optional RPMs – If used, specify the details for delineation of median openings, islands, and traffic separators (e.g. Index 706-001, Detail “C”).

Payment

| Item number | Item Description | Unit Measure |
|-------------|------------------------|--------------|
| 706-1 | Raised Pavement Marker | EA |
| | | |

See the [BOE](#) and [Specifications 706](#) for additional information on payment, pay item use and compensation.