
Index 700-120 Enhanced Highway Signing Assemblies

ORIGINATION

Date: 6/5/24

Name: Ronald Meyer

Phone: 580-7840

Email: Ronald.meyer@dot.state.fl.us

COMMENTARY

Sheets 7 and 8: The 11th Edition MUTCD, Section 2A.12 (12) states:Flashing LED units shall not be used within the legend or border of a Speed Limit sign to indicate that the displayed speed limit is in effect.

Sheet 10, 13, and 14: Where LED units are used along the edge of a sign, at least one LED unit shall be placed along each edge of the sign, in addition to one LED unit at each corner of the sign, so that the distinct outline of the sign shape is recognized under nighttime viewing conditions. The LED units along each side of the sign shall be spaced approximately equidistantly. For a circular sign shape, the number of LED units shall clearly form the appearance of a circle and not be perceived as some other shape.

COMMENTS AND RESPONSES

BLACK = Industry Review Comments **BLUE** = Standard Plans Response **GREEN** = Change Made to Index

Name: David Zeller

Date: 7/23/24

COMMENT: Sheets 10 and 11 specify the "expressway" or "oversize" versions of the referenced signs, which are seldom used. If this index is intended to also apply to the standard versions of these signs, dimensions should not be shown.

RESPONSE: Thank you for your comment. However, this is outside the scope of this change. We will consider this for future changes.

CHANGE MADE TO INDEX: No

Response Date: 7/31/24