

SECTION 525
ASPHALTIC CONCRETE CURB

525-1 Description.

Construct an asphaltic concrete curb on a previously laid pavement at the locations shown in the plans.

525-2 Materials.

Use Type S-I asphaltic concrete mixture.

525-3 Construction Methods.

Sufficiently roughen the surface of the roadway pavement at the locations where the curb will be constructed to provide suitable bonding of the pavement and the curb.

Lay the curb by a machine or by other methods to provide the required cross-section. The Engineer may allow variation in the plan cross-section for using the particular machine, provided the Contractor obtains the equivalent cross-sectional area and the specified height of curb. Provide appropriate compaction as directed by the Engineer.

525-4 Method of Measurement.

The quantity to be paid for will be the length plan quantity, in feet [meters], completed and accepted. Any additions or deletions thereto as authorized by the Engineer will be determined by plan dimensions, station-to-station dimensions, final measurement, or any combination thereof, as measured along the face of the completed and accepted curb.

525-5 Basis of Payment.

Price and payment will be full compensation for all work specified in this Section, including all materials and incidentals necessary to complete the work.

Payment will be made under:

Item No. 525-	1-	Asphaltic Concrete Curb - per foot.
Item No. 2525-	1-	Asphaltic Concrete Curb - per meter.