

		MELT	CAT 350	ET 2000	ET Plus	SKT	FLEAT	SoftStop	SRT	X-Lite	X-Tension
Height	27"	x	x	x	x	x	x		x	x	x
	31"					x	x	x	x	x	x
Head Shape	Square Head			x		x					
	Rectangular Head				x		x	x		x	
	Full Return Buffered End Section	x									
	Partial return Buffered End Section								x		
Head Mount Type	Extrusion Head Type			x	x	x	x	x			
	Tension Extrusion Head Chute Design							x			
	Direct Mount Head Type	x	x						x	x	x
	Double Face Smooth Nose Plate (wraparound)		x								
Head Miscellaneous	Flanges on All sides of head			x							
	Flanges on Side of Head Only				x						
	Secondary Struts in Head Unit					x					
	Square Tube on Top of Head						x				
	Single Strut on Extrusion Head			x	x						
	Dual Strut on Extrusion Head					x	x				
Extrusion Direction	Diaphragm Plate	x									
	Extrudes Away from Traffic					x					
Installation Type	Extrudes Toward Traffic						x				
	Flared Installation	x					x		x	x	x
Miscellaneous	Parallel Installation		x	x	x	x		x		x	x
	Dual Tension Cables (In Panel)										x
	DBL Faced Guardrail		x								
	Slotted Rail								x		
	Slider Bracket at connection to Guardrail									x	x
	Shear Bolts									x	
	Offset block at 2nd Post	x									
	6 - Steel tube foundations		x								
	6 - Wood CRT Posts	x									
	Steel Posts Only							x	x		
	C-Channel Post Strut			x					x		
	Single Angle Strut				x						
	Tension Rods (No Strut)									x	
	2 Ancorage Cables		x								
Forward Anchorage							x			x	