

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

TRUCK TRACTOR TRAILER (TTT) MAP #1

This list should be used in conjunction with the Overweight Routing Maps at <http://www.fdot.gov/maintenance/OWODPermits.shtm>.

Restricted structures indicated on these maps are not allowed to be crossed.

(Minimum 10 ft. spacing required between groupings unless otherwise noted)

	MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
	5	51 FT	112K	25K	50K	60K	60K
	6	51 FT	112K	25K	50K	60K	66K
	6	62 FT	118K	25K	50K	60K	66K
	7	51 FT	122K	25K	40K	60K	66K
	* 7	62 FT	127K	25K	40K	60K	66K
	* 8	68 FT	137K	25K	40K	60K	66K
	9	75 FT	145K	25K	40K	60K	66K
	9	** 90 FT	152K	22K	40K	40K	40K
	10	** 90 FT	162K	22K	40K	50K	50K
SEALED CONTAINER	5	51 FT	100K	25K	50K	66K	66K

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

* 1000 POUNDS MAY BE ADDED FOR EACH ADDITIONAL FOOT OF OUTER BRIDGE UP TO 5,000 POUNDS MAXIMUM.

** MINIMUM 13' 1" REQUIRED BETWEEN GROUPINGS.

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

TRUCK TRACTOR TRAILER (TTT) MAP #2

This list should be used in conjunction with the Overweight Routing Maps at <http://www.fdot.gov/maintenance/OWODPermits.shtm>.

Restricted structures indicated on these maps are not allowed to be crossed.

(Minimum 10 ft. spacing required between groupings unless otherwise noted)

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
* 6	51 FT	122K	25K	50K	66K	69K
7	55 FT	137K	25K	44K	66K	72K
* 7	62 FT	142K	25K	44K	66K	72K
* 8	68 FT	152K	25K	44K	66K	72K
8	75 FT	160K	25K	44K	66K	72K
9	75 FT	160K	25K	44K	66K	72K

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

* 1000 POUNDS MAY BE ADDED FOR EACH ADDITIONAL FOOT OF OUTER BRIDGE UP TO 5,000 POUNDS MAXIMUM.

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

TRUCK TRACTOR TRAILER (TTT) MAP #3

This list should be used in conjunction with the Overweight Routing Maps at <http://www.fdot.gov/maintenance/OWODPermits.shtm>.

Restricted structures indicated on these maps are not allowed to be crossed.

(Minimum 10 ft. spacing required between groupings unless otherwise noted)

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
** 9	90 FT	185K	22K	44K	54K	54K
** 9	95 FT	195K	22K	44K	54K	54K
** 10	95 FT	197K	22K	44K	54K	54K
** 11	100 FT	199K	22K	44K	54K	54K

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

** MINIMUM 13' 1" REQUIRED BETWEEN GROUPINGS

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

TRUCK CRANES (UNDER OWN POWER) MAP #1

This list should be used in conjunction with the Overweight Routing Maps at <http://www.fdot.gov/maintenance/OWODPermits.shtm>.

Restricted structures indicated on these maps are not allowed to be crossed.

(Minimum 10 ft. spacing required between groupings unless otherwise noted)

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MIN. FT BETWEEN GROUPINGS	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
2	10 FT	10	55K	27.5K	55K	N/A	N/A
3	12 FT	8	66K	22K	44K	N/A	N/A
3	15 FT	10	70K	27.5K	55K	N/A	N/A
4	17 FT	9	88K	22K	44K	44K	N/A
4	18 FT	10	75K	27.5K	55K	55K	N/A

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

AXLE WEIGHTS CANNOT EXCEED 605 LBS. PER INCH OF TIRE WIDTH OR PERMITTED AXLE WEIGHT.

VEHICLES RANGING BETWEEN 80,000 AND 146,000 LBS. WHICH DO NOT MEET THE CONFIGURATIONS SHOWN IN THIS CHART WILL REQUIRE FURTHER REVIEW BY THE DEPARTMENT FOR CONSIDERATION OF PERMIT ISSUANCE.

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

TRUCK CRANES (UNDER OWN POWER) MAP #2

This list should be used in conjunction with the Overweight Routing Maps at <http://www.fdot.gov/maintenance/OWODPermits.shtm>.

Restricted structures indicated on these maps are not allowed to be crossed.

(Minimum 10 ft. spacing required between groupings unless otherwise noted)

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MIN. FT BETWEEN GROUPINGS	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
4	20 FT	8	95K	25K	50K	50K	N/A
4	21 FT	8	96K	25K	50K	50K	N/A
4	22 FT	8	97K	25K	50K	50K	N/A
4	20 FT	10	85K	27.5K	55K	55K	N/A
4	16 FT	8	88K	22K	44K	66K	N/A

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

AXLE WEIGHTS CANNOT EXCEED 605 LBS. PER INCH OF TIRE WIDTH OR PERMITTED AXLE WEIGHT.

VEHICLES RANGING BETWEEN 80,000 AND 146,000 LBS. WHICH DO NOT MEET THE CONFIGURATIONS SHOWN IN THIS CHART WILL REQUIRE FURTHER REVIEW BY THE DEPARTMENT FOR CONSIDERATION OF PERMIT ISSUANCE.

*AXLE CODE 161 IS NOT INCLUDED IN THE “PUBLIC” WEIGHT RESTRICTIONS CHARTS. THIS IS STILL A VALID CODE, BUT SHOULD ONLY BE USED WHEN THE CUSTOMER’S REQUEST SPECIFICALLY FITS THIS CODE AND NO OTHER CODE.

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

TRUCK CRANES (UNDER OWN POWER) MAP #3

This list should be used in conjunction with the Overweight Routing Maps at <http://www.fdot.gov/maintenance/OWODPermits.shtm>.

Restricted structures indicated on these maps are not allowed to be crossed.

(Minimum 10 ft. spacing required between groupings unless otherwise noted)

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MIN. FT BETWEEN GROUPINGS	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
5	32 FT	8	100K	22K	44K	66K	66K
5	20 FT	8	97K	22K	44K	66K	66K
5	* 25 FT	10	100K	22K	44K	66K	66K
6	30 FT	8	105K	20K	40K	60K	66K
6	31 FT	8	106K	20K	40K	60K	66K
6	30 FT	10	105K	22K	44K	66K	66K
6	51 FT	8	108K	22K	44K	66K	66K
7	35 FT	10	110K	22K	44K	66K	66K
7	** 51 FT	8	118K	22K	44K	66K	66K
8	* 51 FT	8	122K	22K	44K	66K	66K
8	* 40 FT	10	113K	22K	44K	66K	66K
9	51 FT	10	125K	20K	40K	60K	66K

*/**/** 1,000 pounds may be added to gross weight for each additional foot of outer bridge

* 5,000 pounds maximum

** 4,000 pounds maximum

*** 3,000 pounds maximum

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

AXLE WEIGHTS CANNOT EXCEED 605 LBS. PER INCH OF TIRE WIDTH OR PERMITTED AXLE WEIGHT.

VEHICLES RANGING BETWEEN 80,000 AND 146,000 LBS. WHICH DO NOT MEET THE CONFIGURATIONS SHOWN IN THIS CHART WILL REQUIRE FURTHER REVIEW BY THE DEPARTMENT FOR CONSIDERATION OF PERMIT ISSUANCE.

WEIGHT RESTRICTIONS CHART FOR WRECKER PERMIT VEHICLES

All configurations shown on this page shall operate under TTT Map #1.
For the latest map updates, go to <http://www.fdot.gov/maintenance/OWODPermits.shtm>.

Restricted structures indicated on TTT Map #1 are not allowed to be crossed.

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MIN. BETWEEN GROUPINGS	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
5	51 FT	10 FT	112K	25K	50K	60K	60K
7	67 FT	10 FT	132K	25K	50K	60K	60K

No speed restrictions or maximum radius of travel restrictions apply to the vehicles above.

THE DISABLED VEHICLE IS RESTRICTED TO LEGAL AXLE WEIGHT LIMITS FOR ALL CONFIGURATIONS SHOWN BELOW.

HEAVY WRECKER (HW) CONFIGURATION	MIN. BETWEEN GROUPINGS	WRECKER MAX SINGLE AXLE WEIGHT	WRECKER MAX AXLE GROUP WEIGHT	MAXIMUM RADIUS OF TRAVEL	MAXIMUM SPEED WHEN CROSSING STRUCTURES
HW-1	21 FT	25K	60K	100 MILES	40 MPH
HW-2 *	21 FT	45K	90K	50 MILES	30 MPH

***When traveling under configuration HW-2, no other traffic is allowed and one (1) Qualified Escort is required at all times and must operate at the rear of the load to straddle lanes when crossing all non-restricted structures.**

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds