

Drainage Geotextile - FDOT APL Data Form

Date of Application: <input style="width: 150px;" type="text"/> Type of geotextile company: <input style="width: 150px;" type="text"/> Company Name: <input style="width: 150px;" type="text"/>	Contact: <input style="width: 150px;" type="text"/> Phone: <input style="width: 150px;" type="text"/> Email: <input style="width: 150px;" type="text"/>
--	--

Product Name: <input style="width: 150px;" type="text"/> Product Structure: <input style="width: 150px;" type="text"/> Drainage type(s): <input type="checkbox"/> D-1 <input type="checkbox"/> D-2 <input type="checkbox"/> D-3 <input type="checkbox"/> D-4 <input type="checkbox"/> D-5	Is the product a woven monofilament geotextile? <input type="checkbox"/> Yes <input type="checkbox"/> No Is the product a woven geotextile? <input type="checkbox"/> Yes <input type="checkbox"/> No Does the product contain slit film? <input type="checkbox"/> Yes <input type="checkbox"/> No
--	--

ATTACH CERTIFIED INDEPENDENT TEST RESULTS TO JUSTIFY SUBMITTED VALUES

Test Name / Designation	Grab				Trapezoidal Tear		50 mm Puncture	Permittivity	Apparent Opening Size	Mass/Area	UV Resistance
	ASTM D4632				ASTM D4533		ASTM D6241	ASTM D4491	ASTM D4751	ASTM D5261	ASTM D4355
Units	MD		XD		MD	XD	Strength (lbs)	1/sec.	mm	oz/yd²	% Strength Retained @ 500 hours
	Strength (lbs)	Strain (%)	Strength (lbs)	Strain (%)	Strength (lbs)						
Mean*											
COV(%)*											
MARV											

**From independent test results*

Method of Acceptance for UV Resistance:

Lightest Product:

Required Attachments: Product photo showing significant features of the product and product label photo.