



MAC Quick Sheet  
April 8, 2024

ERS Sample Numbering System

**Proctor Samples**

Proctor samples become parent samples to ERS field density samples. In order to ensure that the Proctor sample numbers are available for ERS field density samples and they are identifiable, the following FDOT Sample Numbering system should be used on Proctor samples.

| Spec. ID | Material Type                       |  | Example                  |
|----------|-------------------------------------|--|--------------------------|
| 120(125) | Embankment/Pipe Backfill            |  | E 0 0 1 Q                |
| 145      | Geosynthetic Reinforcement Backfill |  | G 0 0 1 Q                |
| 160      | Stabilizing                         | Local Stabilizing Material (440A)  | C 0 0 1 Q                |
|          |                                     | Stabilized Subgrade<br>* Note: Replace "S" with "L" for independent VT LBR samples | S 0 0 1 Q /<br>L 0 0 1 V |
|          |                                     | Granular Subbase In-Lieu of Stabilized Subgrade (Pit Proctor)                      | B P S 0 0 1 Q            |
|          |                                     | Granular Subbase In-Lieu of Stabilized Subgrade (Non-Pit Proctor)                  | B S 0 0 1 Q              |
| 200/285  | Optional Base Group                 | Base (Non-Pit Proctor)   | B 0 0 1 Q                |
|          |                                     | Base (Pit Proctor)   | B P 0 0 1 Q              |
|          |                                     | Recycled Aggregate Base (RAP)  | R 0 0 1 Q                |
| 548      | Retaining Wall Systems              | Retaining Wall Backfill  | M 0 0 1 Q                |

Notes:

1. FDOT Sample Number for Proctor samples must start with an alpha character that may be up to four characters. Extra characters after the first character may be added to depict extra information. For example, "P" for Pit-Proctor, "S" for subbase, etc. For shoulder (non-mainline) only samples, include an S for the last alpha character (BPSS0001Q). Coordinate with District Materials and Research Office (DMRO) for additional sample numbering codes.
2. The next three characters must be a sequential number that is between 001 and 999.
3. FDOT Sample # must end with a "Q" for the Contractor, "V" for Verification, "R" for Resolution, or "IV" for Independent Verification.

**ESB Plots  
X00X-T00X(Q)**

X00X = Area Number

T00X = Test Number\*

(Q) = QC test – Optional

*The sample levels are displayed on the comparison package screen. If it makes it easier for the PA to create comparison packages, it is recommended to use the Sample Level alpha character.*

| ken | FDOT Sample Number | LOT # | Mix Design | Sample Level | FDOT Sample Number | LOT # | Mix Design | Sample Level |
|-----|--------------------|-------|------------|--------------|--------------------|-------|------------|--------------|
|     | E001-T005Q         |       |            | QC           | E001-T005          |       |            | QC           |
|     | E001-T006Q         |       |            | QC           | E001-T006          |       |            | QC           |
|     | E001-T007Q         |       |            | QC           | E001-T007          |       |            | QC           |
|     | E001-T008Q         |       |            | QC           | E001-T008          |       |            | QC           |
|     | E001-T008V         |       |            | VT           | E001-T008          |       |            | VT           |

VT Sample should match the QC Sample that it pairs with. For example, if VT pairs with QC E002-T003(Q), VT would be E002-T003(V), even though it is the first VT test performed.

**Initial Production (if performed)**

IPL001(Q), IPL002(Q), IPL003(Q), IPL004(Q), etc.\*

\*Because there is only one IPL per operation, no area is needed, just test number

**Embankment**

E001-T001(Q), E001-T002(Q), E001-T003(Q), E001-T004(Q), etc.

E002-T001(Q), E002-T002(Q), E002-T003(Q), E002-T004(Q), etc.

E003-T001(Q), E003-T002(Q), E003-T003(Q), E003-T004(Q), etc.

**Subgrade**

S001-T001(Q), S001-T002(Q), S001-T003(Q), S001-T004(Q), etc.

**Base**

B001-T001(Q), B001-T002(Q), B001-T003(Q), B001-T004(Q), etc.

**Thicklift Test Strip**

**Embankment**

ETS001-T001(Q), ETS001-T002(Q), ETS001-T003(Q), ETS001-T004(Q), etc.


ETS002-T001(Q), ETS002-T002(Q), ETS002-T003(Q), ETS002-T004(Q), etc.

ETS003-T001(Q), ETS003-T002(Q), ETS003-T003(Q), ETS003-T004(Q), etc.

**Base**

BTS001-T001(Q), BTS001-T002(Q), BTS001-T003(Q), BTS001-T004(Q), etc.

Start over with each lot, phase, or plot line



**NOTE:** Area = area tested, not displayed plot. For example, E001 = first embankment lot tested, not first embankment lot plotted.

**Reduced Frequency  
X00X-T00X(Q)  
Or  
X00X-T00XRF**


X00X = Area Number  
T00X = Test Number\*  
(Q) = QC test - *Optional*  
RF = Reduced Frequency Lift with no QC test – *Required*

**For example: Lifts 2 and 4 have no QC test**

E001-T001(Q), E001-T002RF, E001-T003(Q), E001-T004RF, etc.

The RF samples are designated with a Yes on the “Is this LOT a Reduced Frequency lift?” question and have the same proctor sample as the VT test.

VT Sample should match the QC Sample that it pairs with even if it is a Reduced Frequency Lift. For example, if VT pairs with QC E002-T002RF, VT would also be E002-T002(V).



**Drainage**  
**PH00X-T00X(Q)**

PH00X = Phase Number  
T00X = Test Number  
(Q) = QC test - Optional

VT Sample should match the QC Sample that it pairs with. For example, if VT pairs with QC E002-T002(Q), VT would be E002-T002(V), even though it is the first VT test performed.


**Initial Production (if performed)**

IPL001(Q), IPL002(Q), IPL003(Q), IPL004(Q), etc.\*

\*Because there is only one IPL per operation, no area is needed, just test number

PH001-T001(Q), PH001-T002(Q), PH001-T003(Q), PH001-T004(Q), etc.  
PH002-T001(Q), PH002-T002(Q), PH002-T003(Q), PH002-T004(Q), etc.  
PH003-T001(Q), PH003-T002(Q), PH003-T003(Q), PH003-T004(Q), etc.


Start over with each phase or plot line



**MSE Wall  
X00X-T00XQ**

X00X = Area Number  
T00X = Test Number  
(Q) = QC test - *Optional*

VT Sample should match the QC Sample that it pairs with. For example, if VT pairs with QC E002-T002(Q), VT would be E002-T002(V), even though it is the first VT test performed. Ensure the samples are designated with the correct Category / Type from MAC Spec 548. Samples must be within the same category / type to be included together in a comparison package.



***Initial Production (if performed)***

IPL001(Q), IPL002(Q), IPL003(Q), IPL004(Q), etc.\*

\*Because there is only one IPL per operation, no area is needed, just test number

***3' Wall Zone***

PH001A-T001(Q), PH001A-T002(Q), PH001A-T003(Q), PH001A-T004(Q), etc.\*

PH002A-T001(Q), PH002A-T002(Q), PH002A-T003(Q), PH002A-T004(Q), etc.

***Strap/Embankment Zone***

PH001B-T001(Q), PH001B-T002(Q), PH001B-T003(Q), PH001B-T004(Q), etc.\*

PH002B-T001(Q), PH002B-T002(Q), PH002B-T003(Q), PH002B-T004(Q), etc.

***Embankment Zone Only***

PH001C-T001(Q), PH001C-T002(Q), PH001C-T003(Q), PH001C-T004(Q), etc.\*


PH002C-T001(Q), PH002C-T002(Q), PH002C-T003(Q), PH002C-T004(Q), etc.

***Thicklift Test Strip***

MTS001-T001(Q), MTS001-T002(Q), MTS001-T003(Q), MTS001-T004(Q), etc.\*

MTS002-T001(Q), MTS002-T002(Q), MTS002-T003(Q), MTS002-T004(Q), etc.

Start over with each phase or plot line



**Pad Construction  
One Lift  
XX00x(Q)**

Some pads only have one lift. In these cases, only the test number portion of the ERS sample is needed.

- XX = Pad type
- SS = Shoulder Subgrade
- SB = Shoulder Base
- SW = Sidewalk
- SU = Shared Use Path
- CD = Concrete Driveway
- CP = Curb Pad

If more than one curb pad, CP1, CP2, etc.

- Other = OT
- x = Test number
- (Q) = QC test - Optional

- SS001(Q), SS002(Q), SS003(Q), SS004(Q), etc.\*
  - SB001(Q), SB002(Q), SB003(Q), SW004(Q), etc.
  - SW001(Q), SW002(Q), SW003(Q), SW004(Q), etc.
  - SU001(Q), SU002(Q), SU003(Q), SU004(Q), etc.
  - CD001(Q), CD002(Q), CD003(Q), CD004(Q), etc.
  - CP001(Q), CP002(Q), CP003(Q), CP004(Q), etc.
  - OT001(Q), OT002(Q), OT003(Q), OT004(Q), etc.\*
- \*only if pad is one lift

VT Sample should match the QC Sample that it pairs with. For example, if VT pairs with SU002(Q), VT would be SU002(V), even though it is the first VT test performed.


**Pad Construction  
Multiple Lift  
XX00X-T00X(Q)**

Some pads have more than one lift. In these cases, the area number and test number portion of the ERS sample is needed.

XX00X = Pad Type and Area Number  
T00X = Test Number  
(Q) = QC test - Optional

SS001-T001(Q), SS001-T002(Q), SS001-T003(Q), SS001-T004(Q),  
SS002-T001(Q), SS002-T002(Q), SS002-T003(Q), SS002-T004(Q),  
SS003-T001(Q), SS003-T002(Q), SS003-T003(Q), SS003-T004(Q),  
SS004-T004(Q), SS004-T002(Q), SS004-T003(Q), SS004-T004(Q),

VT Sample should match the QC Sample that it pairs with. For example, if VT pairs with SS002-T003(Q), VT would be SS002-T003(V), even though it is the first VT test performed.



**Mixing Depth  
MD00X**

**X = Test number**  
MD001, MD002, MD003, MD004

**Base Thickness Depth  
BT00X**

**X = Test number**  
BT001, BT002, BT003, BT004

**Additional Form Information**

MAC Spec Category / Type

| <b>Material ID</b> | <b>MAC Possible Categories/Types</b> |                           |
|--------------------|--------------------------------------|---------------------------|
| 120                | ERS Density                          | Embankment                |
| 145                | ERS Density                          | Reinforcement Backfill    |
| 160                | ERS Density                          | Stabilized Subgrade       |
|                    |                                      | LRI (OBG)                 |
|                    |                                      | LRI (GAB)                 |
|                    | ERS Stabilizing Mixing Depth         |                           |
| 200                | ERS Density                          | OBG                       |
|                    |                                      | GAB                       |
|                    | ERS Base Thickness                   |                           |
| 548                | ERS Density                          | 3-ft from the Wall Zone   |
|                    |                                      | Strap Zone                |
|                    |                                      | Strap and Embankment Zone |
|                    |                                      | Embankment Zone           |

For Material Placement on all samples and any additional conditions on samples with other conditions, the following number(s) should be used in field 27. If multiple conditions apply, enter all that apply. For example, Normal Embankment with a project specific target compaction would be 1, 9. The actual target would be entered in the form field. If the override target compaction condition is indicated by a 9, then enter the value in the notes (form field 28).

| <b>MAC Conditions</b> |                                   |                                   |
|-----------------------|-----------------------------------|-----------------------------------|
| <b>1</b>              | Material Placed Condition for 120 | Normal Embankment                 |
| <b>2</b>              |                                   | Pipe run only & within cover zone |
| <b>3</b>              |                                   | Sidewalk/Driveway                 |
| <b>4</b>              |                                   | Noise or Perimeter Wall           |
| <b>5</b>              |                                   | Spread Footer                     |
| <b>6</b>              |                                   | Concrete Barrier Wall             |
| <b>7</b>              | Thicklift Test Strip              |                                   |
| <b>8</b>              | Thicklift Test Wall               |                                   |
| <b>9</b>              | Override Target Compaction        |                                   |