## STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION

## PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored By: AREHNA Coring Completion Date: 8/24/2022 Typical Section: 1

| W.P.I. No.:       |                                    |               |          | Name:                | US27 VENUS  | WILDLIFE CRO | SSING    |       |           | Lanes:                             | 4         |  |
|-------------------|------------------------------------|---------------|----------|----------------------|-------------|--------------|----------|-------|-----------|------------------------------------|-----------|--|
| Fin. Proj. ID:    | 449144-2-32-01                     |               |          | From:                | Hendry Road |              |          |       |           | Shoulder Type and Condition: Paved |           |  |
| F.A. Project No.: |                                    | Roadway ID:   | 09010000 | To:                  | Hendrie Ln  |              |          |       |           | Inside:                            | -         |  |
| County:           | Highlands                          | SR No.:       | 27       | Beg MP:              | 0.860       | End M        | P: 5.100 | Lengt | th: 4.240 | Outside:                           |           |  |
| Overall           | Pavement Condition (from DMO field | review): Good |          | Median Curbed (Y/N): |             | Paved        | Lawn     | Other | er:       | Curb & Gutt                        | er (Y/N): |  |

|             | All Cores                 |              |      |             |                      |       |      |      |      |  |  |  |      |  |       |       |      |       |                          |             |      |       |        |                       |          |
|-------------|---------------------------|--------------|------|-------------|----------------------|-------|------|------|------|--|--|--|------|--|-------|-------|------|-------|--------------------------|-------------|------|-------|--------|-----------------------|----------|
|             |                           |              |      |             | PAVEMENT LAYER (IN.) |       |      |      |      |  |  |  | BASE |  |       |       |      | CRACK |                          |             |      |       |        |                       |          |
| CORE NO.    | MILE<br>POST <sup>2</sup> | LANE<br>TYPE | LANE | WP<br>(Y/N) | FC5                  | SP9.5 | s    | ARMI | T1   |  |  |  |      | TOTAL<br>ASPHALT<br>THICKNESS<br>(IN.) | LR    | SHEL  | CONC | ABC-2 | STABILIZED<br>SUBGRADE 3 | DEPTH (IN.) | TYPE | CLASS | EXTENT | PAVEMENT<br>CONDITION | COMMENTS |
| 1           | 4.443                     | ML           | R1   | N           | 1.1                  | 1.8   | 2.1  |      |      |  |  |  |      | 5.0                                    | 10.0  |       |      |       |                          |             |      |       |        | G                     |          |
| 2           | 4.501                     | ML           | L2   | N           | 0.9                  | 2.3   | 1.1  | 0.5  | 2.1  |  |  |  |      | 6.9                                    |       |       | 8.0  |       |                          |             |      |       |        | G                     |          |
| 3           | 4.818                     | ML           | R2   | N           | 0.8                  | 2.0   | 2.5  |      |      |  |  |  |      | 5.3                                    | 9.0   |       |      |       |                          |             |      |       |        | G                     |          |
| 4           | 4.883                     | ML           | L1   | N           | 0.9                  | 2.2   | 1.2  | 0.4  | 2.9  |  |  |  |      | 7.6                                    |       |       | 7.3  |       |                          |             |      |       |        | G                     |          |
| 5           | 4.507                     | TL           | RL   | N           | 0.8                  | 5.7   |      |      |      |  |  |  |      | 6.5                                    | 11.5  |       |      |       |                          |             |      |       |        | G                     | U-Tum    |
| 6           | 4.842                     | S            | OL   | N           | 1.2                  | 2.3   | 0.8  |      |      |  |  |  |      | 4.3                                    |       |       |      | 3.6   |                          |             |      |       |        | G                     |          |
| 7           | 4.870                     | ML           | R2   | N           | 0.8                  | 2.2   | 2.3  |      |      |  |  |  |      | 5.3                                    | 7.5   |       |      |       |                          |             |      |       |        | G                     |          |
| 8           | 4.898                     | CO           | CO   | N           |                      | 5.1   |      |      |      |  |  |  |      | 5.1                                    |       | 13.0  |      |       |                          |             |      |       |        | G                     |          |
| AVERAGE     |                           |              |      |             | 0.93                 | 2.95  | 1.67 | 0.45 | 2.50 |  |  |  |      | 5.75                                   | 9.50  | 13.00 | 7.65 | 3.60  |                          |             |      |       |        |                       |          |
| MAX         |                           |              |      |             | 1.20                 | 5.70  | 2.50 | 0.50 | 2.90 |  |  |  |      | 7.60                                   | 11.50 | 13.00 | 8.00 | 3.60  |                          |             |      |       |        |                       |          |
| MIN         |                           |              |      |             | 0.80                 | 1.80  | 0.80 | 0.40 | 2.10 |  |  |  |      | 4.30                                   | 7.50  | 13.00 | 7.30 | 3.60  |                          |             |      |       |        |                       |          |
| LAYER COEF. |                           |              |      |             | 0.00                 | 0.34  | 0.34 | 0.00 | 0.30 |  |  |  |      |  | 0.18  | 0.18  | UNKW | 0.20  | 0.08                     |             |      |       |        |                       |          |

## Notes:

- 1. The data presented on this table is specific only at the locations cored at the time of the investigation. Should questions arise regarding the pavement composition, it is incumbent upon those raising the question to perform additional exploration as necessary.
- 2. Mile posts are approximate based on field recorded measurements using a Distance Measuring Instrument (DMI) or a GPS unit.
- 3. Stabilization thickness was checked on 10% of the coring locations. For pavement design, assume 12 inches of thickness for stabilization.
- 4. The cross slope is approximate and measured in the center of the lane.
- 5. A blank cell indicates measurement was not recorded.
- 6. A value of "UNK" indicates material was encountered but the total thickness was not determined.

| Lane Designations - Decreasing MP | Lane Designations - Increasing MP |                | Lane Type                      | Crack Type      | Crack Rating  | <u>Extent</u> | Pavement Condition |
|-----------------------------------|-----------------------------------|----------------|--------------------------------|-----------------|---|---------------|--------------------|
| OL/IL - Outside/Inside Shoulder   | OR/IR - Outside/Inside Shoulder   | ML - Mainline  | S - Shoulder                   | A - Alligator   | Class IB - Hairline cracks that are ≤ 1/8 inch wide | L - Light     | G - Good           |
| L1 - 1st Lane Left of Centerline  | R1 - 1st Lane Right of Centerline | TL - Turn Lane | SS - Side Street               | B - Block       | Class II - Cracks > than 1/8 inch and ≤ 1/4 inch    | M - Moderate  | F - Fair           |
| LL/LR - Left/Right Turn Lane      | RL/RR - Left/Right Turn Lane      | CO - Crossover | BR - Bridge Approach/Departure | C - Combination | Class III - Cracks > 1/4 inch                       | S - Severe    | P - Poor           |