

439826-1 / SR 555 (US 17)
POLK COUNTY

MAINLINE									SUB-SOILS			
CORE	MP	LANE	W/P	FC5	SP2F	S	TOTAL ASPHALT THICKNESS	CRACK	ABC	LR	STAB	COMMENTS
16	22.847	L1	Y	0.7	2	3.3	6	6		13	12	
15	22.977	L1	N	1	1.5	3.8	6.3			13	12	
14	23.168	L1	Y	0.7	1.5	4.2	6.4	6.4		11	12	
11	23.671	L1	Y	0.8	1.5	2.4	4.7	4.7		13	12	
32	22.926	L2	N	0.8	2.1	2.9	5.8			12.5	12	
30	23.257	L2	N	0.8	1.5	3.5	5.8	5.8		13.5	12	
28	23.613	L2	Y	0.4	1.3	3.7	5.4	2.3		11	12	
3	22.972	R1	Y	0.7	1.4	2.6	4.7	2		14	12	
4	22.972	R1	Y	0.6	1.3	2.8	4.7			13.5	12	
5	22.972	R1	Y	0.6	2.1	1.9	4.6			13.5	12	
6	22.975	R1	Y	0.8	1.4	2.9	5.1	5.1		13	12	
7	23.099	R1	N	0.7	1.3	3.1	5.1			13.5	12	
8	23.290	R1	Y	0.9	2	2	4.9			13.5	12	
17	22.871	R2	Y	0.6	1.5	3.9	6	6		12.5	12	
21	23.121	R2	Y	0.6	2.5	1.9	5	0.6		12	12	
23	23.229	R2	N	0.7	1.6	2.9	5.2			11.5	12	
26	23.532	R2	N	0.6	2.1	2	4.7	4.7		12.5	12	
AVG				0.71	1.68	2.93	5.32	4.36		12.74	12.00	

SHOULDERS									SUBSOILS			
CORE	MP	LANE	W/P	FC5	SP2F	S	TOTAL ASPHALT THICKNESS	CRACK	ABC	LR	STAB	COMMENTS
33	22.925	OL	N	1	1.3	1.5	3.8			5	12	
29	23.613	OL	N	0.9	0.7	1.5	3.1			5	12	
18	22.940	OR	N	0.5		2.6	3.1			5	12	
20	23.078	OR	N	0.6	2.4	1.4	4.4			6	12	
24	23.229	OR	N	1.1		1.6	2.7			5.5	12	
AVG				0.82	1.47	1.72	3.42			5.30	12.00	

TURN LANES, CROSSOVERS AND GORE									SUB-SOILS			
CORE	MP	LANE	W/P	FC5	SP2F	S	TOTAL ASPHALT THICKNESS	CRACK	ABC	LR	STAB	COMMENTS
1	22.851	CO	N	0.8	1.2	4	6			11.5	12	CROSSOVER
9	23.446	CO	N	1.2	1.1		2.3			9.5	12	CROSSOVER
22	23.122	GORE	N	1	1.5	2	4.5			7.5	12	
31	23.218	LTRT	Y	0.6	1	3.7	5.3	2.7		12	12	
13	23.266	LTTL	Y	0.9	1.6	2.5	5	2.5	8.1		12	
12	23.467	LTTL	N	0.7	1.3	3.5	5.5	1.5		14	12	
34	22.143	RTTL	Y	1	1.7	1.7	4.4			14	12	
2	22.969	RTTL	Y	1	2.2	2.3	5.5		8.9		12	
10	23.519	RTTL	N	1.0	1.8	3.2	6		8.7		12	
19	23.078	RTTR	Y	0.6	2.1	3.5	6.2	2.3		12.5	12	
25	23.297	RTTR	Y	0.7	1.8	3	5.5	2.5		11	12	
27	23.537	RTTR	N	1.1	1.7	2.5	5.3			13	12	
AVG				0.88	1.58	2.90	5.13	2.30	8.57	11.67	12.00	