

# 441983-1

## SR 600 (US 92) Polk County

MAINLINE														SUB-SOILS									
CORE	MP	LANE	W/P	FC 5				SP2F	S	BINDER	S	T1	TOTAL ASPHALT THICKNESS	CRACK DEPTH	SCEM	RAP	LR	CONC	STAB	RUT	SLOPE	COMMENTS	
24	3.890	L1	N	0.9				1.0	1.5	1.4	2.5	0.9	8.2					6.4	12.0		1.0		
4	4.100	L1	N	1.1				1.0	1.7		5.5	1.2	10.5					6.1	12.0				
3	4.360	L1	Y	1.4				1.1	2.1		2.1	0.6	7.3					6.7	12.0	0.2	0.6	NEW PAVEMENT/CONC CRACK	
11	3.805	L2	N	1.2				2.6		2.0		0.7	6.5					6.3	12.0	0.1	0.9	CONCRETE CRACKS	
9	4.293	L2	Y	0.9				1.0	1.8	1.3			5.0				8.0		12.0	0.6	0.9		
1	4.129	R1	Y	0.8				1.5	0.8	1.4			4.5						12.0	0.2	1.2		
2	4.400	R1	N	1.1				1.5	2.3				4.9						12.0	0.1	0.9	NEW PAVEMENT	
5	3.868	R2	N	1.1				1.6	2.1				4.8						12.0	0.6	0.9		
7	4.309	R2	Y	0.8				1.5	2.0	1.2			5.5						12.0	0.2	1.0		
AVG				1.03				1.42	1.79	1.46	3.37	0.85	6.36					8.40	6.38	12.00			

SHOULDERS														SUB-SOILS									
CORE	MP	LANE	W/P	FC5				SP2F	S	BIND	S	T1	TOTAL ASPHALT DEPTH	CRACK DEPTH	SCEM	RAP	LR	CONC	STAB	RUT	SLOPE	COMMENTS	
12	3.805	OL	N	0.9					2.0				2.9						12		0.1	0.9	
10	4.293	OL	N	1.2					2.2				3.4						12		0.2	1.2	
6	3.868	OR	N	1.0					2.5				3.5						12		0.2	0.9	
8	4.309	OR	N	1.5					2.0				3.5						12		0.2	0.9	
AVG				1.15					2.18				3.33						12.00				

TURN LANES / CROSSOVERS														SUB-SOILS									
CORE	MP	LANE	W/P	FC5	FC3	FC9.5	FC12.5	SP2F	S	BIND	S	T1	TOTAL ASPHALT DEPTH	CRACK DEPTH	SCEM	RAP	LR	CONC	STAB	RUT	SLOPE	COMMENTS	
25	3.890	L1	N	0.7				1.0	2.9	1.6			6.2				8.5		12		0.2	0.9	ACCEL LANE
27	3.994	L1	N			0.8			0.9	1.6			3.3				8.0		12	0.1	0.9	FISH HATCHERY - NORTH OF US 92	
22	4.087	C	N					1.0	1.1	2.1			4.2				9.5		12		0.2	0.9	CROSSOVERS
21	4.291	L1	Y	1.0				1.5	1.7	1.1			5.3				8.0		12		0.2	0.9	LEFT TURN ONTO REYNOLDS ROAD
17	4.053	L2	N	0.8				1.1	1.9	1.6			5.4				11.5		12	0.1	0.9	RIGHT TURN LANE	
18	3.898	R1	Y	0.8				1.4	1.0	2.0			5.2	5.2			9.5		12	0.1	0.9	LEFT TURN LANE	
19	3.940	C	N					1.0	0.7	1.5			3.2				10.5	12.0			0.2	0.9	CROSSOVER
26	3.994	R1	Y		0.7				1.5				2.2						12	0.1	0.9	FISH HATCHERY - SOUTH OF US 92	
20	4.072	R1	Y	1.0				1.6		2.0			4.6				8.5		12	0.2	0.9	LEFT TURN LANE	
28	4.250	R1	N				1.8						1.8		8				12		0.2	0.9	REYNOLDS ROAD - LEFT TURN LANE
13	3.971	R2	N	1.1				2.1	1.4	1.8			6.4				7.5		12	0.2	1.2	RIGHT TURN LANE	
14	4.077	R2	Y	1.0				1.3	1.2	2.0			5.5	2.3			8.0		12		0.2	0.9	ACCEL LANE
15	4.200	R2	Y	1.0				1.3	0.4	2.2			4.9	1.8			7.5		12		0.6	0.9	RIGHT TURN LANE
16	4.343	R2	N	1.3				1.6		2.3			5.2				8.0		12		0.5	0.9	ACCEL LANE
AVG.				0.97	0.70	0.80	1.80	1.35	1.34	1.82			4.53	3.10	8.00		8.75	12.00	12.00	0.19	0.99		