

**TABLE 1**  
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION  
**PAVEMENT EVALUATION CORING AND CONDITION DATA**

675-030-09  
Materials  
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 8/16/2021 Page: 1 of 3 Typical Section No.: 1

Roadway Section:	260050000	Name:	SR 222 (NW 39TH AVE)	Lanes:	4						
Fin. Proj. ID:	207611-5-52-01	From:	NW 43RD ST	Shoulder Type and Condition:							
F. A. Proj. No.:		To:	NW 24TH BLVD	Inside:	NONE / CURB AND GUTTER						
County:	ALACHUA	SR No.:	SR 222	Beg MP:	3.667	End MP:	5.550	Lgth:	1.883	Outside:	PAVED - 4' / CURB AND GUTTER
Median Curbed (Y / N):	Y	(X) Paved	(X) Lawn	Other:		Curb & Gutter (Y / N):	N				

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)				Base (in.) <sup>1</sup>	Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top	FC12.5	SP12.5	T1		Core Lgth. (in.)	LR	Depth (in.)	Type					
1	3.800	R1	O	1.6	1.5	1.3	4.4	--	2.10	B	II	M	P				MODERATE RAVELING, SPALLING
2	4.200	R1	I	1.7	1.5	1.5	4.7	13.3	1.70	B	III	S	P				LIGHT RAVELING, SPALLING, TRANSVERSE CRACK
3	4.590	R1	O	1.4	1.8	1.6	4.8	--	1.00	B	IB	L	P				LIGHT RAVELING, SHOIVING
4	4.800	R1	I	1.5	2.0	1.2	4.7	--	1.80	B	II	S	P				MODERATE RAVELING, SPALLING
5	5.200	R1	O	1.5	2.0	0.6	4.1	--	2.10	B	III	S	P				MODERATE RAVELING, SPALLING
6	5.545	R1	O	2.0	1.6	1.1	4.7	--	1.70	B	III	S	P				MODERATE RAVELING, SPALLING
7	3.760	R2	O	1.7	2.0	1.4	5.1	13.9	1.40	B	II	M	P				LIGHT RAVELING, SPALLING
8	4.000	R2	I	1.5	2.9	1.3	5.7	--	1.60	B	II	M	P				LIGHT RAVELING, SPALLING
9	4.445	R2	O	1.2	2.1	1.6	4.9	--	1.50	B	III	S	P				MODERATE RAVELING, SPALLING
10	4.751	R2	O	1.4	2.0	1.5	4.9	--	1.60	B	II	M	P				LIGHT RAVELING, SPALLING
11	5.229	R2	O	1.4	1.9	1.0	4.3	--	1.40	B	III	S	P				SEVERE RAVELING, SPALLED TO STRUCTURAL, SPALLING
12	5.400	R2	I	1.3	1.7	1.3	4.3	--	1.60	B	II	M	P				LIGHT RAVELING, SHOIVING, SPALLING
13	3.760	L1	O	1.7	2.0	2.1	5.8	--	1.90	B	II	S	P				MODERATE RAVELING, SPALLING
14	4.035	L1	O	1.4	2.3	1.5	5.2	--	1.40	B	III	S	P				MODERATE RAVELING, SHOIVING, SPALLING
15	4.390	L1	O	1.5	1.7	2.1	5.3	--	1.50	B	IB	L	P				LIGHT RAVELING, SHOIVING
16	4.600	L1	O	1.4	1.5	1.3	4.2	12.9	2.00	B	II	M	P				MODERATE RAVELING, SPALLING
17	5.000	L1	I	1.4	1.7	1.6	4.7	--	1.70	B	IB	L	P				MODERATE RAVELING, SPALLING
18	5.400	L1	O	1.4	1.7	1.9	5.0	--	1.90	B	II	M	P				MODERATE RAVELING, SPALLING

**NOTES:** 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.  
2. MP 4.010: MULTIPLE SMALL MAINTENANCE PATCHES IN R2 OWP.

**TABLE 1**  
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION  
**PAVEMENT EVALUATION CORING AND CONDITION DATA**

675-030-09  
Materials  
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 8/16/2021 Page: 2 of 3 Typical Section No.: 1

Roadway Section:	260050000	Name:	SR 222 (NW 39TH AVE)	Lanes:	4
Fin. Proj. ID:	207611-5-52-01	From:	NW 43RD ST	Shoulder Type and Condition:	
F. A. Proj. No.:		To:	NW 24TH BLVD	Inside:	NONE / CURB AND GUTTER
County:	ALACHUA	SR No.:	SR 222	Beg MP:	3.667
				End MP:	5.550
				Lgth:	1.883
Median Curbed (Y / N):	Y	(X) Paved	(X) Lawn	Other:	
				Curb & Gutter (Y / N):	N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)				Base (in.) <sup>1</sup>		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top	SP12.5	T1	Core Lgth. (in.)	ABC	LR	Depth (in.)	Type	Class	Extent					
19	3.800	L2	N	1.3	1.7	2.3	5.3		--	1.80	B	II	S	P				MODERATE RAVELING, SPALLING
20	4.362	L2	O	1.5	1.8	1.7	5.0		--	5.00	B	III	S	P				MODERATE RAVELING, SPALLING, TRANSVERSE CRACK
21	4.500	L2	O	1.6	2.0	1.5	5.1		--	1.80	B	III	M	P				MODERATE RAVELING, SHOIVING, SPALLING, TRANSVERSE CRACK
22	4.800	L2	O	1.5	1.9	1.6	5.0		--	1.60	B	IB	L	P				MODERATE RAVELING, SPALLING, TRANSVERSE CRACK
23	5.190	L2	O	1.5	1.9	1.9	5.3		--	1.40	B	II	L	P				LIGHT RAVELING, SPALLING
24	5.460	L2	O	2.1	1.0	1.9	5.0		12.3	1.30	B	II	M	P				LIGHT RAVELING, SPALLING
25	3.700	OR	N	2.0	2.2	1.4	5.6		--					F				BIKE LANE, LIGHT RAVELING
26	4.700	OR	N	1.3	2.4	2.1	5.8		--					F				BIKE LANE, LIGHT RAVELING
27	4.362	OL	N	1.8	1.6	1.6	5.0		--					P				BIKE LANE, MODERATE RAVELING
28	5.200	OL	N	1.8	2.0	2.0	5.8		--					F				ASPHALT OVERLAY IS 0.7 in ABOVE GUTTER, BIKE LANE, LIGHT RAVELING, SPALLING
29	3.750	LLTTL2	N	1.7	2.1	3.2	7.0	12.5		1.70	B	II	S	P				MODERATE RAVELING, SPALLING
30	3.747	LR TTL	O	2.0	2.0	2.6	6.6		--	2.00	B	IB	M	P				LIGHT RAVELING, SPALLING
31	3.726	LLTTL1	O	1.7	2.1	9.9	13.7		9.0	0.50	B	IB	M	P				LIGHT RAVELING
32	3.910	LLTTL	O	1.8	1.9	1.5	5.2		--					F				LIGHT RAVELING
33	4.054	RLTTL	O	1.7	2.3	2.0	6.0		--					F				LIGHT RAVELING
34	4.574	RLTTL	N	1.5	2.4	0.9	4.8		--	1.70	B	II	M	P				MODERATE RAVELING, SPALLING
35	4.755	LLTTL	N	1.2	2.1	0.6	3.9		--	1.70	B	II	M	P				LIGHT RAVELING
36	4.968	CTL	N	1.5	2.4	1.3	5.2		--					F				LIGHT RAVELING, SHOIVING,

**NOTES:** 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.  
2. MP 4.010: MULTIPLE SMALL MAINTENANCE PATCHES IN R2 OWP.

**TABLE 1**  
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION  
**PAVEMENT EVALUATION CORING AND CONDITION DATA**

675-030-09  
Materials  
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 8/16/2021 Page: 1 of 3 Typical Section No.: 1

Roadway Section:	260050000	Name:	SR 222 (NW 39TH AVE)	Lanes:	4						
Fin. Proj. ID:	207611-5-52-01	From:	NW 43RD ST	Shoulder Type and Condition:							
F. A. Proj. No.:		To:	NW 24TH BLVD	Inside:	NONE / CURB AND GUTTER						
County:	ALACHUA	SR No.:	SR 222	Beg MP:	3.667	End MP:	5.550	Lgth:	1.883	Outside:	PAVED - 4' / CURB AND GUTTER
Median Curbed (Y / N):	Y	(X) Paved	(X) Lawn	Other:		Curb & Gutter (Y / N):	N				

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)				Base (in.) <sup>1</sup>	Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top			Core Lgth. (in.)	LR	Depth (in.)	Type	Class	Extent					
				FC12.5	SP12.5	T1											
37	5.410	CTL	N	1.6	1.8	0.6	4.0	--	1.20	B	IB	L	P				LIGHT RAVELING, SHOING,
38	4.304	RTO	N	2.0		3.7	5.7	--					F				NW 37TH ST, LIGHT RAVELING
39	4.445	LTO	N	1.0	1.4	4.2	6.6	--					P				NW 36TH ST, MODERATE RAVELING
40	4.664	RTO	N	1.6		3.6	5.2	--					P				SR 121 TL FROM NB SR 121 TO EB SR 222, MODERATE RAVELING
41	4.878	LTO	N	1.5		4.3	5.8	--					P				NW 31ST TER, MODERATE RAVELING
42	5.437	RTO	N	1.8		0.7	2.5	--					F				NW 25TH TER, LIGHT RAVELING

**NOTES:** 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.  
2. MP 4.010: MULTIPLE SMALL MAINTENANCE PATCHES IN R2 OWP.