

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 8/16/2021 Page: 1 of 4 Typical Section No.: 1

Roadway Section: 26050000	Name: SR 331	Lanes: 4
Fin. Proj. ID: 447962-1-52-01	From: SR 25 (US 441)	Shoulder Type and Condition:
F. A. Proj. No.:	To: SR 26	Inside: CURB AND GUTTER
County: ALACHUA	SR No.: SR 331	Beg MP: 0.013
		End MP: 3.309
		Lgth: 3.296
Median Curbed (Y / N): Y	Paved (X) Lawn	Other:
		Curb & Gutter (Y / N): N
		Outside: PAVED

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)				Base (in.) ¹	Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top	SP12.5	T1	Core Lgth. (in.)	LR	Depth (in.)	Type	Class	Extent					
1	0.142	R1	O	1.1	1.8	0.5	3.4	8.2	1.70	B	II	S	P				LIGHT RAVELING, SPALLING
2	0.205	R1	O	1.6	1.2	0.6	3.4	--	3.40	B	II	M	P				GRINDING, LIGHT RAVELING, SPALLING
3	0.610	R1	O	1.6	1.4	0.4	3.4	--	3.40	B	II	L	F				LIGHT RAVELING
4	1.020	R1	O	1.4	1.6	0.7	3.7	--	3.70	B	IB	L	P				LIGHT RAVELING
5	1.300	R1	O	1.6	1.4	0.7	3.7	--	1.60	B	II	M	P				LIGHT RAVELING
6	1.620	R1	O	1.5	1.5	0.5	3.5	--	3.50	B	IB	M	P				LIGHT RAVELING, SPALLING
7	2.000	R1	O	1.5	1.4	0.4	3.3	--	3.30	B	II	M	P				LIGHT RAVELING, SPALLING
8	2.300	R1	I	1.4	1.3	0.6	3.3	--	1.40	B	II	S	P				GRINDING, MODERATE RAVELING, SEPARATION AT 1.4 in., SPALLING, SUPERELEVATED CURVE
9	2.690	R1	I	1.3	1.4	1.1	3.8	--	2.00	B	II	M	P				MODERATE RAVELING, SPALLING
10	3.000	R1	O	1.6	1.6	0.5	3.7	--	2.20	B	II	M	P				MODERATE RAVELING, SPALLING
11	3.300	R1	I	1.4	1.2	0.4	3.0	11.5	3.00	B	II	L	P				MODERATE RAVELING, SPALLING
12	0.310	R2	O	1.5	1.5		3.0	--	3.00	B	II	S	P				GRINDING, MODERATE RAVELING, SHOING, SPALLED TO STRUCTURAL, SPALLING
13	0.580	R2	O	1.5	1.5		3.0	--	3.00	B	IB	S	P				GRINDING, MODERATE RAVELING, SPALLING
14	0.855	R2	O	1.1	1.2	0.5	2.8	10.4	2.80	B	IB	S	P				GRINDING, MODERATE RAVELING, SPALLING
15	1.000	R2	I	1.3	1.5	0.6	3.4	--	1.80	B	II	M	P				MODERATE RAVELING, SPALLING
16	1.500	R2	O	1.5	1.5		3.0	--					P				LIGHT RAVELING, SPALLING
17	1.800	R2	O	1.5	1.5		3.0	--	3.00	B	II	S	P				MODERATE RAVELING, SPALLING
18	2.298	R2	I	1.5	1.5	0.5	3.5	--	2.10	B	II	S	P				GRINDING, MODERATE RAVELING, SHOING, SPALLING

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED. 7. MP 0.387: MAINTENANCE PATCH IN R1, RL TTL. 13. MP 1.385 - 1.577: MAINTENANCE PATCH IN R2.
2. MP 0.030: PAVEMENT CHANGE. 8. MP 0.975: PATCH IN L2 OWP. 14. MP 1.206 - 1.336: MAINTENANCE PATCH IN L2, OL.
3. MP 0.125: MULTIPLE SMALL PATCHES IN R2. 9. MP 1.203 - 1.213: MAINTENANCE PATCH IN L1. 15. MP 2.527: PATCH IN R2 IWP.
4. MP 0.130: MULTIPLE SMALL PATCHES IN R1 OWP. 10. MP 1.206 - 1.336: MAINTENANCE PATCH IN L2, OL. 16. MP 3.050: MULTIPLE SMALL PATCHES IN R2 IWP & OWP.
5. MP 0.226 - 0.232: MAINTENANCE PATCH IN L2. 11. MP 1.261 - 1.271: MAINTENANCE PATCH IN L1. 17. MP 3.078: MULTIPLE SMALL PATCHES IN R2 IWP.
6. MP 0.232: MULTIPLE SMALL PATCHES IN R1 OWP. 12. MP 1.313 - 1.323: MAINTENANCE PATCH IN L1.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 8/16/2021 Page: 2 of 4 Typical Section No.: 1

Roadway Section: 26050000				Name: SR 331				Lanes: 4				
Fin. Proj. ID: 447962-1-52-01				From: SR 25 (US 441)				Shoulder Type and Condition:				
F. A. Proj. No.:				To: SR 26				Inside: CURB AND GUTTER				
County: ALACHUA		SR No.: SR 331		Beg MP: 0.013		End MP: 3.309		Lgth: 3.296		Outside: PAVED		
Median Curbed (Y / N): Y				Paved		(X) Lawn		Other:		Curb & Gutter (Y / N): N		

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)				Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top	SP12.5	T1	Core Lgth. (in.)	ABC	LR	Depth (in.)	Type	Class	Extent					
19	2.527	R2	O	1.1	1.6	1.0	3.7		--	3.70	A	II	S	P				GRINDING, SEVERE RAVELING, SPALLING, SUPERELEVATED CURVE
20	2.800	R2	I	1.5	1.2	0.5	3.2		--	3.20	B	II	S	P				GRINDING, MODERATE RAVELING, SPALLING
21	3.050	R2	I	1.3	1.4	1.0	3.7		--	3.70	A	III	S	P				GRINDING, SEVERE RAVELING, SHOING, SPALLING
22	3.300	R2	O	1.5	1.4	0.5	3.4		--					P				LIGHT RAVELING
23	0.339	L1	O	1.3	1.7		3.0		--	3.00	B	II	M	P				LIGHT RAVELING, SPALLING
24	0.500	L1	O	1.7	2.2		3.9	6.5	--					P				LIGHT RAVELING
25	0.793	L1	I	1.2	1.4	0.6	3.2		12.1	3.20	B	II	L	P				LIGHT RAVELING, SHOING, SPALLING
26	1.200	L1	N	1.6	1.5	1.1	4.2		--					P				LIGHT RAVELING
27	1.400	L1	O	1.6	1.3	1.1	4.0		--					F				LIGHT RAVELING, SPALLING
28	1.800	L1	I	1.7	1.3	0.6	3.6		--					F				LIGHT RAVELING, SPALLING
29	2.195	L1	I	1.7	1.4	0.6	3.7		--	3.70	B	II	M	P				MODERATE RAVELING, SPALLING
30	2.500	L1	O	1.5	1.3	0.6	3.4		--	3.40	B	II	M	P				MODERATE RAVELING, SPALLING
31	2.800	L1	I	1.4	1.8		3.2		--	3.20	B	II	M	P				LIGHT RAVELING, SPALLING
32	3.200	L1	O	1.8	1.3		3.1		12.4	3.10	B	II	M	P				MODERATE RAVELING, SPALLING
33	0.182	L2	O	1.6	0.9	0.5	3.0		8.9	3.00	B	IB	S	P				GRINDING, MODERATE RAVELING, SPALLING
34	0.300	L2	N	1.5	1.6	0.6	3.7		--	3.70	B	II	L	P				GRINDING, LIGHT RAVELING, SPALLING
35	0.655	L2	I	1.4	1.8	0.4	3.6		--	2.00	B	II	S	P				GRINDING, MODERATE RAVELING, SPALLING
36	0.975	L2	O	1.1	1.8		2.9		--	1.80	B	IB	S	P				GRINDING, LIGHT RAVELING, SPALLING

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED. 7. MP 0.387: MAINTENANCE PATCH IN R1, RLTTL. 13. MP 1.385 - 1.577: MAINTENANCE PATCH IN R2.
2. MP 0.030: PAVEMENT CHANGE. 8. MP 0.975: PATCH IN L2 OWP. 14. MP 1.206 - 1.336: MAINTENANCE PATCH IN L2, OL.
3. MP 0.125: MULTIPLE SMALL PATCHES IN R2. 9. MP 1.203 - 1.213: MAINTENANCE PATCH IN L1. 15. MP 2.527: PATCH IN R2 IWP.
4. MP 0.130: MULTIPLE SMALL PATCHES IN R1 OWP. 10. MP 1.206 - 1.336: MAINTENANCE PATCH IN L2, OL. 16. MP 3.050: MULTIPLE SMALLPATCHES IN R2 IWP & OWP.
5. MP 0.226 - 0.232: MAINTENANCE PATCH IN L2. 11. MP 1.261 - 1.271: MAINTENANCE PATCH IN L1. 17. MP 3.078: MULTIPLE SMALL PATCHES IN R2 IWP
6. MP 0.232: MULTIPLE SMALL PATCHES IN R1 OWP. 12. MP 1.313 - 1.323: MAINTENANCE PATCH IN L1.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 8/16/2021 Page: 3 of 4 Typical Section No.: 1

Roadway Section: 26050000	Name: SR 331	Lanes: 4
Fin. Proj. ID: 447962-1-52-01	From: SR 25 (US 441)	Shoulder Type and Condition:
F. A. Proj. No.:	To: SR 26	Inside: CURB AND GUTTER
County: ALACHUA	SR No.: SR 331	Beg MP: 0.013
		End MP: 3.309
		Lgth: 3.296
Median Curbed (Y / N): Y	Paved (X) Lawn	Other:
		Outside: PAVED
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)				Base (in.) ¹	Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC12.5	SP12.5	T1	Core Lgth. (in.)	LR	Depth (in.)	Type	Class	Extent					
37	1.300	L2	O	1.6	1.6	1.8	5.0	--					P				LIGHT RAVELING, SPALLING
38	1.620	L2	O	1.2	1.5	0.6	3.3	--	3.30	B	IB	L	P				MODERATE RAVELING, SPALLING
39	2.000	L2	O	1.4	1.5	1.6	4.5	--	4.50	B	IB	S	P				LIGHT RAVELING, SPALLING
40	2.275	L2	O	1.5	1.3	0.5	3.3	--	3.30	B	III	S	P				MODERATE RAVELING, SPALLING TO STRUCTURAL, SPALLING, TRANSVERSE CRACK
41	2.560	L2	O	1.5	1.5		3.0	11.5	3.00	B	IB	S	P				LIGHT RAVELING, SPALLING
42	3.075	L2	O	1.4	1.2		2.6	--	1.40	B	II	S	P				MODERATE RAVELING, SPALLING
43	3.278	L2	N	1.5	1.5		3.0	--	3.00	B	IB	M	P				MODERATE RAVELING, SPALLING
44	0.310	OR	N	1.3	2.0		3.3	6.2					P				MODERATE RAVELING
45	1.500	OR	N	1.5	1.3		2.8	--					F				LIGHT RAVELING
46	2.527	OR	N	1.3	1.9		3.2	9.4					F				LIGHT RAVELING
47	3.300	OR	N	1.3	1.9		3.2	--					F				LIGHT RAVELING
48	0.182	OL	N	1.4	1.4	0.8	3.6	--	3.60	B	II	L	P				MODERATE RAVELING, SPALLING
49	0.975	OL	N	1.5	1.4		2.9	10.7					F				LIGHT RAVELING
50	2.000	OL	N	1.5	1.4		2.9	--					F				LIGHT RAVELING
51	3.075	OL	N	1.2	1.5	0.3	3.0	12.2					F				LIGHT RAVELING
52	0.400	RLTTL	O	1.7	8.0		9.7	--					F				LIGHT RAVELING
53	1.929	RTO	N	1.2		1.2	2.4	--					F				SE 1ST TER, LIGHT RAVELING
54	2.953	RTO	N	1.0	1.6		2.6	--					P				SE 7TH AVE, SEVERE RAVELING, SPALLING

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED. 7. MP 0.387: MAINTENANCE PATCH IN R1, RLTTTL. 13. MP 1.385 - 1.577: MAINTENANCE PATCH IN R2.
2. MP 0.030: PAVEMENT CHANGE. 8. MP 0.975: PATCH IN L2 OWP. 14. MP 1.206 - 1.336: MAINTENANCE PATCH IN L2, OL.
3. MP 0.125: MULTIPLE SMALL PATCHES IN R2. 9. MP 1.203 - 1.213: MAINTENANCE PATCH IN L1. 15. MP 2.527: PATCH IN R2 IWP.
4. MP 0.130: MULTIPLE SMALL PATCHES IN R1 OWP. 10. MP 1.206 - 1.336: MAINTENANCE PATCH IN L2, OL. 16. MP 3.050: MULTIPLE SMALL PATCHES IN R2 IWP & OWP.
5. MP 0.226 - 0.232: MAINTENANCE PATCH IN L2. 11. MP 1.261 - 1.271: MAINTENANCE PATCH IN L1. 17. MP 3.078: MULTIPLE SMALL PATCHES IN R2 IWP
6. MP 0.232: MULTIPLE SMALL PATCHES IN R1 OWP. 12. MP 1.313 - 1.323: MAINTENANCE PATCH IN L1.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 8/16/2021 Page: 4 of 4 Typical Section No.: 1

Roadway Section:	26050000	Name:	SR 331	Lanes:	4
Fin. Proj. ID:	447962-1-52-01	From:	SR 25 (US 441)	Shoulder Type and Condition:	
F. A. Proj. No.:		To:	SR 26	Inside:	CURB AND GUTTER
County:	ALACHUA	SR No.:	SR 331	Beg MP:	0.013
				End MP:	3.309
				Lgth:	3.296
Median Curbed (Y / N):	Y	Paved	(X) Lawn	Other:	
				Curb & Gutter (Y / N):	N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)				Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top	SP12.5	T1	Core Lgth. (in.)	ABC	LR	Depth (in.)	Type	Class	Extent					
55	0.551	LTO	N	1.7	1.6		3.3	6.3						F				CR 329, LIGHT RAVELING
56	1.797	LTO	N	1.9		1.8	3.7		--					F				SE 1ST ST, LIGHT RAVELING
57	3.250	LTO	N	1.2	1.6		2.8		--					P				SE 2ND AVE, MODERATE RAVELING, SPALLING
58	1.675	LR TTL	O	1.2	2.6		3.8	8.6						F				LIGHT RAVELING, SPALLING
59	0.339	LL TTL	N	2.1	7.6		9.7		--					F				LIGHT RAVELING
60	1.615	LL TTL	N	1.0	1.6		2.6		--					F				LIGHT RAVELING, WIDENING
61	2.800	LL TTL	N	0.9	1.7		2.6		--					F				LIGHT RAVELING
62	3.200	LL TTL	N	0.9	1.6		2.5		--					F				LIGHT RAVELING
A	3.078	R2	I	1.2	1.4	0.7	3.3		--	1.20	B	II	S	P				SEVERE RAVELING, SPALLING

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED. 7. MP 0.387: MAINTENANCE PATCH IN R1, RL TTL. 13. MP 1.385 - 1.577: MAINTENANCE PATCH IN R2.
2. MP 0.030: PAVEMENT CHANGE. 8. MP 0.975: PATCH IN L2 OWP. 14. MP 1.206 - 1.336: MAINTENANCE PATCH IN L2, OL.
3. MP 0.125: MULTIPLE SMALL PATCHES IN R2. 9. MP 1.203 - 1.213: MAINTENANCE PATCH IN L1. 15. MP 2.527: PATCH IN R2 IWP.
4. MP 0.130: MULTIPLE SMALL PATCHES IN R1 OWP. 10. MP 1.206 - 1.336: MAINTENANCE PATCH IN L2, OL. 16. MP 3.050: MULTIPLE SMALL PATCHES IN R2 IWP & OWP.
5. MP 0.226 - 0.232: MAINTENANCE PATCH IN L2. 11. MP 1.261 - 1.271: MAINTENANCE PATCH IN L1. 17. MP 3.078: MULTIPLE SMALL PATCHES IN R2 IWP.
6. MP 0.232: MULTIPLE SMALL PATCHES IN R1 OWP. 12. MP 1.313 - 1.323: MAINTENANCE PATCH IN L1.