

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 1 of 17 Typical Section No.: 1

Roadway Section: 26260000				Name: SR 93 (I-75)				Lanes: 6											
Fin. Proj. ID: 423071-6-52-01				From: S OF SR 121 (WILLISTON RD)				Shoulder Type and Condition:											
F. A. Proj. No.:				To: N OF SR 222 (NW 39th AVE)				Inside: PAVED											
County: ALACHUA		SR No.: SR 93 (I-75)		Beg MP: 6.035		End MP: 17.425		Lgth: 11.390		Outside: PAVED									
Median Curbed (Y / N): N				Paved				(X) Lawn				Other:				Curb & Gutter (Y / N): N			

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)				Base (in.) ¹	Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top	SP12.5	S	Core Lgth. (in.)	LR	Depth (in.)	Type	Class	Extent					
1	6.200	R1	I	0.9	1.5	6.2	8.6	--					F				
2	6.700	R1	O	1.1	1.3	5.0	7.4	--					F				
3	7.200	R1	I	0.8	1.5	5.6	7.9	--					F				
4	7.700	R1	O	0.7	1.4	5.5	7.6	--					F				
5	8.200	R1	I	1.1	1.5	5.5	8.1	--					F				
6	8.700	R1	O	0.9	1.7	4.1	6.7	--					F				
7	9.200	R1	I	0.8	1.6	4.8	7.2	13.6					F				
8	9.810	R1	O	0.9	1.9	5.1	7.9	--					F				
9	10.200	R1	I	0.8	2.9	6.6	10.3	--					F				
10	10.725	R1	O	1.1	3.5	5.7	10.3	--					F				
11	11.200	R1	I	1.0	1.7	5.2	7.9	--					F				
12	11.700	R1	O	0.9	1.9	5.8	8.6	--					F				
13	12.315	R1	I	0.8	2.1	4.9	7.8	--					F				
14	12.700	R1	O	0.9	1.8	6.2	8.9	--					F				
15	13.200	R1	I	1.0	1.7	6.0	8.7	--					F				
16	13.700	R1	O	1.0	1.8	6.2	9.0	--					F				
17	14.200	R1	I	0.9	2.7	6.1	9.7	--					F				
18	14.705	R1	O	1.0	1.8	6.0	8.8	--					F				

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
 2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
 3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
 4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
 5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
 6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 2 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
		End MP: 17.425
		Lgth: 11.390
Median Curbed (Y / N): N	Paved	(X) Lawn
		Other:
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)								Core Lgth. (in.)	Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	SP12.5	S	ARMI	S	TI	BIND	LR		Depth (in.)	Type	Class	Extent							
19	15.200	R1	I	1.1	2.1			5.4			8.6	--					F						
20	15.700	R1	O	0.8	2.1			5.6			8.5	--					F						
21	16.200	R1	I	1.2	2.2			4.1			7.5	--					F						
22	16.700	R1	O	0.7	1.9			4.3			6.9	--					F						
23	17.200	R1	I	0.9	1.7			4.1			6.7	15.0					F						
24	6.045	R3	O	1.0	3.6			3.4	1.7	2.2	11.9	--					F						
25	6.500	R3	I	1.0	3.3			9.2			13.5	--					F						
26	7.000	R3	O	0.8	3.4			8.4			12.6	10.6					F						
27	7.500	R3	I	1.0	3.3			9.0			13.3	--					F						
28	8.000	R3	O	0.7	3.4			9.3			13.4	--					F						
29	8.500	R3	I	1.1	3.1			9.9			14.1	--					F						
30	9.245	R3	O	0.8	3.0		0.5	1.8	2.0	2.2	10.3	--					F						
31	9.585	R3	N	0.8	1.7		0.5	4.9	1.6	2.2	11.7	--					F					SEPARATION AT 2.5 in. AND 4.5 in.	
32	9.900	R3	O	0.8	3.8		0.5	2.8	1.6	2.8	12.3	--					F						
33	10.500	R3	N	0.9	2.0	2.2	0.5	2.7	1.7	2.0	12.0	--					F						
34	10.950	R3	O	0.8	1.8	1.4	0.5		1.0	3.0	8.5	--					F						
35	11.415	R3	I	1.0	2.3	3.5	0.5	3.8	1.6	1.5	14.2	--					F						
36	12.005	R3	O	0.8	1.8	1.9	0.5	4.1	1.5	2.8	13.4	--					F						

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 3 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
		End MP: 17.425
		Lgth: 11.390
Median Curbed (Y / N): Y	Paved	(X) Lawn
		Other:
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)								Core Lgth. (in.)	Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	SP12.5	S	ARMI	S	TI	BIND	LR		Depth (in.)	Type	Class	Extent							
37	12.500	R3	N	1.0	2.0	2.1	0.5	4.2	1.7	2.6	14.1	12.9					F						
38	13.000	R3	O	0.9	2.1	1.5	0.5	5.1	1.5	2.9	14.5	--					F						
39	13.500	R3	I	1.0	2.1	1.4	0.5	4.5	1.7	2.1	13.3	--					F						
40	14.005	R3	O	0.8	1.6	1.8	0.5	4.3	1.7	2.6	13.3	--					F						
41	14.495	R3	I	1.2	1.6			5.0	0.6		8.4	--					F						
42	15.170	R3	O	0.9	1.3	2.3	0.5	4.1	1.5	2.5	13.1	--					F						
43	15.500	R3	I	0.8	1.9	2.0	0.5	4.3	1.5	2.6	13.6	--					F						
44	16.000	R3	O	0.7	3.9		0.5	3.8	1.6	2.4	12.9	--					F						
45	16.560	R3	I	0.9	3.4		0.5	2.9	1.4	2.4	11.5	--					F						
46	17.000	R3	O	0.9	3.4	4.5			1.7	2.3	12.8	--					F						
47	17.420	R3	N	0.8		3.9	0.5	4.0	1.4	2.4	13.0	--					F						
48	6.035	L1	I	0.8		1.5		5.4			7.7	--					F				SUPERELEVATED CURVE		
49	6.500	L1	O	0.9		1.5		5.4			7.8	--					F						
50	7.000	L1	I	0.8		1.5		4.6			6.9	14.0					F						
51	7.495	L1	O	1.0		1.4		4.7			7.1	--					F						
52	8.000	L1	I	0.7		1.4		5.4			7.5	--					F						
53	8.500	L1	O	1.1		1.5		6.3			8.9	--					F						
54	9.000	L1	I	0.8		1.5		5.6			7.9	--					F						

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 4 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
	End MP: 17.425	Lgth: 11.390
Median Curbed (Y / N): N	Paved	(X) Lawn
	Other:	Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)							Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top	FC5	SP12.5	ARMI	S	T1	BIND	Core Lgth. (in.)	CONC	LR	Depth (in.)	Type	Class					
55	9.500	L1	O	0.9	2.5		7.3			10.7		--					F				
56	10.000	L1	I	1.1	2.7		7.4			11.2		--					F				
57	10.490	L1	O	0.7	2.1		6.3			9.1		--					F				
58	10.900	L1	I	1.0	1.9		6.3			9.2		13.6					F				
59	11.495	L1	O	0.8	3.5		6.6			10.9		--					F				
60	12.000	L1	I	1.0	2.0		5.7			8.7		--					F				
61	12.490	L1	O	0.7	1.9		6.4			9.0		--					F				
62	13.000	L1	I	0.9	1.9		6.2			9.0		--					F				SUPERELEVATED CURVE
63	13.500	L1	N	0.6	2.0		6.3			8.9		--					F				
64	14.000	L1	I	1.2	2.7		6.0			9.9		--					F				
65	14.520	L1	O	0.8	2.0		1.3			4.1	--		4.10	B	III	S	P				MODERATE RAVELING, SPALLING, CUT ON EDGE OF LEAVE SLAB
66	15.000	L1	I	1.0	2.2	0.5	4.4			8.1		--					F				
67	15.500	L1	O	0.8	2.0		5.5			8.3		12.4					F				
68	16.000	L1	I	1.1	1.7		5.0			7.8		--					F				
69	16.500	L1	O	0.8	1.8		4.8			7.4		--					F				
70	17.000	L1	I	0.9	2.2	0.5	3.8			7.4		--					F				
71	17.420	L1	O	0.8	1.8		4.0			6.6		--					F				
72	6.170	L3	O	1.0	2.7	0.5	5.5	1.3	2.7	13.7		--					P				RAVELED TO STRUCTURAL

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 5 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
	End MP: 17.425	Lgth: 11.390
Median Curbed (Y / N): N	Paved	(X) Lawn
	Other:	Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)							Core Lgth. (in.)	Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top	FC5	SP12.5	ARMI	S	T1	BIND		LR	Depth (in.)	Type	Class	Extent						
73	6.700	L3	I	0.9	3.4		9.2			13.5	--					F						
74	7.200	L3	O	0.6	3.5		7.8			11.9	--					F						
75	7.700	L3	I	0.9	3.5	0.5	8.3			13.2	--					F						
76	8.200	L3	O	0.7	3.5		8.3			12.5	--					F						
77	8.830	L3	N	0.9	3.4		9.0			13.3	--					F						
78	9.200	L3	O	0.7	3.5		4.5	1.7	2.8	13.2	12.6					F						
79	9.745	L3	N	1.0	6.6					7.6	--					F						
80	10.200	L3	O	0.9	3.9	0.5	4.0	1.7	2.8	13.8	--					F						
81	10.765	L3	I	0.8	4.9	0.5	5.3	1.4	2.8	15.7	--					F						
82	11.175	L3	N	0.6	3.4	0.5	4.4	1.8	2.7	13.4	--					F						
83	11.700	L3	N	0.8	4.2	0.5	5.3	1.8	2.7	15.3	--					F						
84	12.238	L3	O	1.0	5.9					6.9	--					F						
85	12.700	L3	I	0.9	3.5	0.5	5.7	1.3	2.7	14.6	--					F						
86	13.330	L3	O	0.7	2.9	0.5	5.4	1.7	2.7	13.9	--					F						
87	13.700	L3																		OMITTED IN THE FIELD PER FDOT		
88	13.880	L3	O	0.9	2.8	0.5	4.6	1.7	2.4	12.9	--					F						
89	14.700	L3	I	0.9	3.1	0.5	5.7	1.3	2.4	13.9	--					F						
90	15.200	L3	O	0.7	2.5	0.5	4.0	1.6	2.5	11.8	--					F						

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 6 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
		End MP: 17.425
		Lgth: 11.390
Median Curbed (Y / N): N	Paved	(X) Lawn
		Other:
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)								Core Lgth. (in.)	Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top SP12.5	SP12.5	ARMI	S	T1	BIND	LR		Depth (in.)	Type	Class	Extent							
91	15.700	L3	N	1.0		2.5	0.5	5.4	1.5	2.5	13.4	--					F				SEPARATION AT 4.0 in.		
92	16.200	L3	O	0.8		3.5	0.5	2.9	1.3	2.6	11.6	--					F						
93	16.765	L3	O	0.9		4.2		3.1	1.4	2.8	12.4	--					F						
94	17.200	L3	O	0.8		3.8	0.5	0.9	0.4	2.2	8.6	11.9					F						
95	6.200	IR	N		1.5			2.9			4.4	--					G						
96	7.200	IR	N		1.5			3.5			5.0	--					G						
97	8.200	IR	N		1.3			3.0			4.3	8.2					G						
98	9.200	IR	N		1.6			2.8			4.4	--					G						
99	10.200	IR	N		2.2			1.4			3.6	--					G						
100	11.200	IR	N		2.0			1.9			3.9	--					G						
101	12.315	IR	N		2.1			2.2			4.3	--					G						
102	13.200	IR	N		1.8			2.3			4.1	--					G						
103	14.200	IR	N		1.5			2.2			3.7	--					G						
104	15.200	IR	N		1.6			1.2			2.8	--					G						
105	16.200	IR	N		1.4			1.2			2.6	8.6					G						
106	17.200	IR	N		2.3						2.3	--					G						
107	6.045	OR	N		1.7			2.0	1.8	0.7	6.2	5.8					G						
108	7.000	OR	N		2.4			1.8		0.7	4.9	--					G						

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 7 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
		End MP: 17.425
		Lgth: 11.390
Median Curbed (Y / N): N	Paved	(X) Lawn
		Other:
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)						Core Lgth. (in.)	Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				SP12.5	S	T1	BIND	ST	LR		Depth (in.)	Type	Class	Extent							
109	8.000	OR	N	1.4		4.0	1.2	0.6		7.2	--					G					
110	9.245	OR	N	1.0		0.9	2.3	0.5		4.7	--					G					
111	9.900	OR	N	1.1		4.9	2.3	0.6		8.9	--					G					
112	10.950	OR	N	1.8				0.7		2.5	--					G					
113	12.005	OR	N	1.9		4.8			0.5	7.2	--					G					
114	13.000	OR	N	1.8		4.7	2.0		0.6	9.1	7.1					G					
115	14.000	OR	N	1.9		2.2	2.8		0.6	7.5	--					F				SEPARATION AT 1.9 in.	
116	15.170	OR	N	1.9		4.4	1.9		0.5	8.7	--					F				SEPARATION AT 3.4 in.	
117	16.000	OR	N	1.5		3.5	2.2		0.5	7.7	--					G					
118	17.000	OR	N	1.9		4.1	2.2		0.6	8.8	--					F				SEPARATION AT 6.0 in.	
119	6.035	IL	N	1.7		2.0				3.7	7.8					G					
120	7.000	IL	N	1.4		1.4				2.8	--					G					
121	8.000	IL	N	1.8		1.5				3.3	--					G					
122	9.000	IL	N	1.8		2.2				4.0	--					G					
123	10.000	IL	N	2.0		2.5				4.5	--					G					
124	10.900	IL	N	1.6		2.2				3.8	--					G					
125	12.000	IL	N	1.9		1.9				3.8	--					G					
126	13.000	IL	N	1.7		2.2				3.9	10.9					G					

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 8 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Outside: PAVED
Median Curbed (Y / N): N	Paved (X) Lawn Other:	Curb & Gutter (Y / N): N
Beg MP: 6.035	End MP: 17.425	Lgth: 11.390

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)				Core Lgth. (in.)	Base (in.) ¹	Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				SP12.5	S	TI	BIND			LR	Depth (in.)	Type	Class					
127	14.000	IL	N	2.0	1.8			3.8	--					G				
128	15.000	IL	N	2.0	2.0			4.0	--					G				
129	16.000	IL	N	1.3	1.5			2.8	--					G				
130	17.000	IL	N	1.6	1.4			3.0	--					G				
131	6.170	OL	N	1.4	4.3	1.9	0.6	8.2	--					G				
132	7.200	OL	N	1.7	1.0	2.1	0.6	5.4	--					G				
133	8.200	OL	N	1.4	1.9		0.9	4.2	6.3					G				
134	9.200	OL	N	1.4	3.4	2.2	0.7	7.7	--					G				
135	10.200	OL	N	1.9	3.0	2.0	0.5	7.4	--					G				
136	11.175	OL	N	1.7	5.0	1.8	0.5	9.0	--					G				
137	12.233	OL	N	2.1				2.1	--					G				
138	13.330	OL	N	2.0	3.5	2.5	0.5	8.5	--					G				
139	13.880	OL	N	1.6	2.9	2.1	0.6	7.2	--					G				
140	15.200	OL	N	1.8	2.4	2.0	0.3	6.5	--					F				SEPARATION AT 2.8 in.
141	16.200	OL	N	1.8	4.7	1.8	1.6	9.9	6.3					F				SEPARATION AT 3.3 in.
142	17.200	OL	N	1.5	1.8		0.5	3.8	--					G				
143	9.699	R1																OMITTED IN THE FIELD PER FDOT
144	10.999	R1																OMITTED IN THE FIELD PER FDOT

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
 2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
 3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
 4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
 5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
 6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 9 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
		End MP: 17.425
		Lgth: 11.390
Median Curbed (Y / N): N	Paved	(X) Lawn
		Other:
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)			Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top FC12.5	SP12.5	Core Lgth. (in.)	ABC	LR	Depth (in.)	Type	Class					
145	12.202	R1															OMITTED IN THE FIELD PER FDOT
146	14.510	R1															OMITTED IN THE FIELD PER FDOT
147	9.748	R3	I	1.0		6.8	7.8		--				F				
148	11.043	R3															OMITTED IN THE FIELD PER FDOT
149	12.234	R3															OMITTED IN THE FIELD PER FDOT
150	14.562	R3															OMITTED IN THE FIELD PER FDOT
151	9.741	L1															OMITTED IN THE FIELD PER FDOT
152	11.043	L1															OMITTED IN THE FIELD PER FDOT
153	12.234	L1															OMITTED IN THE FIELD PER FDOT
154	14.573	L1															OMITTED IN THE FIELD PER FDOT
155	9.699	L3															OMITTED IN THE FIELD PER FDOT
156	11.045	L3	N	0.9		6.8	7.7		--				F				
157	12.233	L3															OMITTED IN THE FIELD PER FDOT
158	14.572	L3															OMITTED IN THE FIELD PER FDOT

SR 93 (I-75) NB REST AREA (RP # 26260009)

159	8.440	DEC	O	0.7		1.8	2.5	11.9					F	0.11	1.50	O	
160	8.440	OR	N		0.8	1.7	2.5	11.8					F		2.50	O	
161	116 ⁶	RP	I		1.4	1.3	2.7		--				F	0.19	2.70	O	

- NOTES:**
1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
 2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
 3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
 4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
 5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
 6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 10 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Outside: PAVED
Median Curbed (Y / N): N	Paved	(X) Lawn
	Other:	Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)				Core Lgth. (in.)	Base (in.) ¹	LR	Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top FC12.5	SP12.5	S				Depth (in.)	Type	Class	Extent					
SR 93 (I-75) NB REST AREA (RP # 26260009) - CONTINUED																			
162	116 ⁶	IR	N		1.8	2.1		3.9	--					F					
163	445 ⁶	TP	N		1.4	2.1		3.5	--					F				PARKING LOT	
164	562 ⁶	CP	N		1.9		1.1	3.0	--					F				PARKING LOT	
165	1285 ⁶	IR	N		1.8	2.3		4.1	--					F					
166	1285 ⁶	RP	I		1.4	1.4	0.5	3.3	--					F				CROSS SLOPE = 2.2-OUT, 0.3-IN	
167	9.030	ACEL	O	0.9		5.0		5.9	--					F					
168	9.030	OR	N		0.9	2.6		3.5	--					F					
SR 93 (I-75) SB REST AREA (RP # 26260014)																			
169	9.005	DEC	N	1.1		10.1		11.2	--					F					
170	9.005	OL	N		1.4	5.9		7.3	--					F					
171	95 ⁶	RP	I		1.3	7.2		8.5	--					F				WIDENING, 19.0 in FROM YELLOW LINE	
172	95 ⁶	IL	N		2.0	7.0		9.0	--					F					
173	410 ⁶	TP	N		1.6	1.7		3.3	--	3.30	B	II	M	P				PARKING LOT	
174	582 ⁶	CP	N		1.2	1.1	1.3	3.6	--					F				PARKING LOT	
175	1116 ⁶	RP	I		1.2	0.9	2.8	4.9	--					F					
176	8.400	ACEL	O	1.0		4.5	4.2	9.7	--					F					
177	8.400	OL	N		1.0	1.0		2.0	--					F					

- NOTES:**
1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
 2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
 3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
 4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
 5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
 6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 11 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
		End MP: 17.425
		Lgth: 11.390
Median Curbed (Y / N): N	(X) Lawn	Other:
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)							Base (in.) ¹			Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top FC12.5	SP12.5	S	T1	BIND	Core Lgth. (in.)	ABC	LR	SSB	Depth (in.)	Type	Class	Extent					
SR 93 (I-75) SB OFF RAMP TO SR 121 (RP # 26260015)																						
178	9.982	DEC	O	0.9		1.9	3.2				6.0		--					F				
179	9.982	OL	N		1.3	1.0					2.3		--					F				
180	270 ⁶	RP	O		1.5	1.4					2.9	7.5						F				
181	275 ⁶	IL	N		1.8						1.8	3.0						F				
182	745 ⁶	RP	O		1.5	1.5					3.0	5.8						F				
183	745 ⁶	OL	N		1.3	1.1					2.4	4.7						F				
SR 93 (I-75) SB ON RAMP FROM SR 121 (RP # 26260016)																						
184	70 ⁶	RP	O		1.3	1.3					2.6	6.8						F				
185	70 ⁶	OL	O		1.5	1.8					3.3	3.3						F				
186	543 ⁶	RP	I		0.9	1.5	2.6	2.0	2.5	9.5		12.7						F				SEPARATION AT 2.4in., SUPERELEVATED CURVE
187	543 ⁶	IL	N		1.0	0.9	1.3	4.0		7.2			--	7.20	B	II	M	P				SEPARATION AT 1.9 in., SUPERELEVATED CURVE, TRANSVERSE CRACK
188	9.585	ACEL	O	0.8		1.9	4.6			7.3		--						F				
189	9.585	OL	N		1.0	1.0				2.0		--						F				
SR 93 (I-75) NB OFF RAMP TO SR 121 (RP # 26260017)																						
190	9.640	DEC	O	0.9		2.1	3.4				6.4		--					F				
191	9.640	OR	N		1.2	1.3					2.5		--					F				
192	180 ⁶	RP	I		1.0	0.6	4.6	1.7	2.9	10.8		--						F				SEPARATION AT 3.0 in., SUPERELEVATED CURVE

- NOTES:**
1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
 2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
 3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
 4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
 5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
 6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 12 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
		End MP: 17.425
		Lgth: 11.390
Median Curbed (Y / N): N	(X) Lawn	Other:
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)								Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top FC12.5	SP12.5	S	T1	BIND	Core Lgth. (in.)	ABC	LR	Depth (in.)	Type	Class	Extent						
SR 93 (I-75) NB OFF RAMP TO SR 121 (RP # 26260017) – CONTINUED																						
193	180 ⁶	IR	N		1.0	0.9	1.4				3.3	3.4						F				SUPERELEVATED CURVE
194	528 ⁶	RP	O		1.5	7.7					9.2	--						F				
195	528 ⁶	OR	N		1.5	1.6					3.1	7.0						F				
SR 93 (I-75) NB ON RAMP FROM SR 121 (RP # 26260018)																						
196	30 ⁶	RP	O		1.3	2.1					3.4	8.5						F				
197	30 ⁶	OR	N		1.1	1.0					2.1	5.5						F				
198	750 ⁶	RP	I		1.2	1.3	3.8	2.0	2.7	11.0		9.2						F				
199	750 ⁶	IR	N		1.0	0.7	2.5			4.2	3.3							F				
200	10.165	ACEL	O	0.8		1.9	4.0			6.7		--						F				
201	10.165	OR	N		1.1	1.0				2.1		--						F				
SR 93 (I-75) SB ON RAMP FROM SR 24 (RP # 26260049)																						
202	466 ⁶	RP	O		1.3	2.0				3.3		--						F				
203	466 ⁶	OL	N		1.6	2.4				4.0		--						F				
204	805 ⁶	RP	N		1.2	1.0	3.5	1.2		6.9		--						F				
205	805 ⁶	IL	N		1.0	0.8	5.6			7.4		--						F				
206	10.610	ACEL	O	0.8		1.8	4.5	2.6		9.7		--						F				
207	10.610	OL	N		0.8	4.0		2.4		7.2		--						F				

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 13 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
		End MP: 17.425
		Lgth: 11.390
Median Curbed (Y / N): N	(X) Lawn	Other:
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)						Core Lgth. (in.)	Base (in.) ¹	Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top FC12.5	SP12.5	S	T1	LR			Depth (in.)	Type	Class	Extent					
SR 93 (I-75) NB OFF RAMP TO SR 24 (RP # 26260050)																				
208	10.624	DEC	O	0.8		1.9	4.0		6.7	--					F					
209	10.624	OR	N		0.8	0.8			1.6	--					F					
210	353 ⁶	RP	I		1.1	1.0	3.3		5.4	--					F					
211	353 ⁶	IR	N		1.2	1.9	3.3		6.4	--					F					
212	1103 ⁶	RP	O		1.5	5.5			7.0	--					F					
213	1103 ⁶	OR	N		1.1	1.5			2.6	--					F					
SR 93 (I-75) NB ON RAMP FROM SR 24 (RP # 26260051)																				
214	30 ⁶	RP	O		1.1	2.5			3.6	--					F					
215	30 ⁶	OR	N		1.5	1.4			2.9	--					F					
216	1140 ⁶	RP	I		1.5	1.9	3.4		6.8	12.2					F					
217	1140 ⁶	IR	N		1.0	0.8	4.4		6.2	--					F					
218	11.450	ACEL	O	1.0		1.9	2.6	3.5	9.0	--					F					
219	11.450	OR	N		1.6	3.7	1.2		6.5	--					F					
SR 93 (I-75) SB OFF RAMP TO SR 24 (RP # 26260052)																				
220	11.447	DEC	O	1.1		1.9	4.7		7.7	--					F					
221	11.447	OL	N		1.1	1.0			2.1	--					F					
222	550 ⁶	RP	N		1.7	2.4	7.0		11.1	--					F					

- NOTES:**
1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
 2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
 3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
 4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
 5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
 6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 14 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
		End MP: 17.425
		Lgth: 11.390
Median Curbed (Y / N): N	(X) Lawn	Other:
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)								Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top FC12.5	SP12.5	S	T1	BIND	Core Lgth. (in.)	ABC	LR	Depth (in.)	Type	Class	Extent						
SR 93 (I-75) SB OFF RAMP TO SR 24 (RP # 26260052) - CONTINUED																						
223	582 ⁶	IL	N		1.2	3.9					5.1		--					F				
224	1171 ⁶	RP	O		0.8	1.8	2.2				4.8		--					F				
225	1171 ⁶	OL	N		1.5	1.5					3.0		--					F				
SR 93 (I-75) SB ON RAMP FROM SR 26 (RP # 26260021)																						
226	530 ⁶	RP	O		1.3	0.9			0.8	3.0		--						F				SUPERELEVATED CURVE
227	530 ⁶	OL	N		2.0		1.5	1.3	1.1	5.9		--						F				
228	1193 ⁶	RP	I		1.3	2.0	3.1	2.4	2.3	11.1		--						F				
229	1193 ⁶	IL	N		1.4	1.5	2.4	2.3	2.8	10.4		--						F				SEPARATION AT 1.4 in.
230	14.060	RP	O	0.9		2.4	4.2			7.5		--						F				
231	14.060	OL	N		1.5	0.7				2.2		--						F				
SR 93 (I-75) SB OFF RAMP TO SR 26 (RP # 26260022)																						
232	14.602	DEC	O	0.8		2.0	3.4			6.2		--						F				
233	14.602	OL	N		1.4	1.3				2.7		--						F				
234	155 ⁶	RP	I		1.5	1.0	1.0	3.2	2.8	9.5		--						F				SEPARATION AT 1.5 in. AND 4.9 in., SUPERELEVATED CURVE
235	155 ⁶	IL	N		1.5	2.0		2.7	2.9	9.1		--						F				SUPERELEVATED CURVE
236	835 ⁶	RP	O		1.6	1.5				3.1	13.0							F				
237	835 ⁶	OL	N		1.6	2.8				4.4	12.0							F				

- NOTES:**
1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
 2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
 3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
 4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
 5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
 6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 15 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
		End MP: 17.425
		Lgth: 11.390
Median Curbed (Y / N): N	(X) Lawn	Other:
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)								Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top FC12.5	SP12.5	S	T1	BIND	Core Lgth. (in.)	ABC	LR	Depth (in.)	Type	Class	Extent						
SR 93 (I-75) NB OFF RAMP TO SR 26 (RP # 26260023)																						
238	14.100	DEC	O	0.9		2.2	3.7			6.8		--					F					
239	14.100	OR	N		1.2	2.3				3.5		--					F					
240	437 ⁶	RP	N		1.5	3.8				5.3		--					F					
241	437 ⁶	IR	N		1.8	1.5				3.3		--					F					
242	891 ⁶	RP	O		1.3	2.7				4.0		--					F					
243	891 ⁶	OR	N		1.6	2.5				4.1		--					F					
SR 93 (I-75) NB ON RAMP FROM SR 26 (RP # 26260024)																						
244	120 ⁶	RP	O		1.3	3.0				4.3		--					F					
245	120 ⁶	OR	N		1.7	2.5				4.2		--					F					
246	980 ⁶	RP	I		1.2	1.6	2.0	1.9	2.6	9.3		12.1					F					
247	980 ⁶	IR	N		1.2	2.0				3.2	12.5						F					
248	15.025	ACEL	O	1.1		2.6				3.7	7.1						F					
249	15.025	OR	N		1.2	1.0				2.2	1.4						F					
SR 93 (I-75) SB ON RAMP FROM SR 222 EB (RP # 26260020)																						
250	355 ⁶	RP	O		1.6	1.8	5.5			8.9		--					F					
251	355 ⁶	OL	N		1.4		4.9			6.3		--					F					

- NOTES:**
1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
 2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
 3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
 4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
 5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
 6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 16 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
	End MP: 17.425	Lgth: 11.390
Median Curbed (Y / N): N	(X) Lawn	Other:
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)							Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top FC12.5	SP12.5	S	T1	BIND	Core Lgth. (in.)	ABC	LR	Depth (in.)	Type	Class	Extent					
SR 93 (I-75) SB ON RAMP FROM SR 222 WB (RP # 26260020)																					
252	750 ⁶	RP	I		1.7	2.0	6.2				9.9		--					F			
253	750 ⁶	IL	N		1.7	2.0	6.0				9.7		--					F			
254	1016 ⁶	RP	O		1.8	2.0	5.4				9.2		--					F			
255	1016 ⁶	OL	N		1.7		4.3				6.0		--					F			
256	296 ⁶	RP	I		1.3	2.0	2.3	3.6			9.2		--					F			
257	296 ⁶	IL	N		1.4		4.1	3.2			8.7		--					F			
258	16.556	ACEL	O	0.6		4.3	3.2				8.1		--					F			
259	16.556	OL	N	0.9		2.0					2.9	6.0						F			
SR 93 (I-75) NB OFF RAMP TO SR 222 (RP # 26260026)																					
260	16.205	DEC	O	0.9		7.0					7.9		--					F			
261	16.205	OR	N		1.4	3.2					4.6		--					F			
262	81 ⁶	RP	I		1.4	2.2	3.1	3.3	1.7		11.7		--					F			
263	81 ⁶	IR	N		1.7	1.8					3.5		--					F			
264	699 ⁶	RP	O		1.5	1.5					3.0	9.1						F			
265	699 ⁶	OR	N		1.6	1.5					3.1	4.5						F			
SR 93 (I-75) SB OFF RAMP TO SR 222 (RP # 26260027)																					
266	17.515	DEC	O	0.9		3.1	1.1				5.1		--					F			

- NOTES:**
1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
 2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
 3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
 4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
 5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
 6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 17 of 17 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75)	Beg MP: 6.035
		End MP: 17.425
		Lgth: 11.390
Median Curbed (Y / N): N	(X) Lawn	Other:
		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)							Core Lgth. (in.)	Base (in.) ¹			Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top FC12.5	SP12.5	S	T1	BIND	ABC		LR	RAP	Depth (in.)	Type	Class	Extent						
SR 93 (I-75) SB OFF RAMP TO SR 222 WB (RP # 26260027) – CONTINUED																							
267	17.515	OL	N		1.5	1.1				2.6		--		0.50	B	II	M	P					
268	350 ⁶	RP	I		1.4	1.8		3.3	2.8	9.3		15.1						F					
269	350 ⁶	IL	N		1.7			2.2		3.9		--						F					
270	750 ⁶	RP	O		2.0	2.0	3.5	2.1		9.6		--						F					
271	750 ⁶	OL	N		1.8	2.2				4.0	5.9							F					
SR 93 (I-75) NB ON RAMP FROM SR 222 (RP # 26260028)																							
272	100 ⁶	RP	O		1.6	2.0				3.6	7.0							F					
273	100 ⁶	OR	N		1.5					1.5	6.9							F					
274	1130 ⁶	RP	I		1.5	2.5		1.5	2.4	7.9		12.2						F					
275	1130 ⁶	IR	N		1.5	2.2				3.7	2.2							F					
276	17.600	ACEL	O	1.4		3.5	6.4			11.3		--						F					
277	17.600	OR	N		1.3					1.3	3.2							F					

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
2. MP 10.054 to 10.074: MAINTENANCE PATCH IN L3 AND OL.
3. MP 15.840 to 15.860: MAINTENANCE PATCH IN L1.
4. RAMP # 26260049: PAVEMENT CHANGE 840 FEET.
5. RAMP 26260052: PAVEMENT CHANGE 800 FEET.
6. DISTANCE MEASURED EQUALS FEET FROM BULLNOSE.

TABLE 2
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
BRIDGE APPROACH SLAB SUBSURFACE CONDITION

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 4/29/2022 Page: 1 of 1 Typical Section No.: 1

Roadway Section: 26260000	Name: SR 93 (I-75)	Lanes: 6
Fin. Proj. ID: 423071-6-52-01	From: S OF SR 121 (WILLISTON RD)	Shoulder Type and Condition:
F. A. Proj. No.:	To: N OF SR 222 (NW 39th AVE)	Inside: PAVED
County: ALACHUA	SR No.: SR 93 (I-75) Begin MP: 6.035 End MP: 17.425 Length: 11.390	Outside: PAVED

Core Number	Milepost	Lane	Bridge Number	Slab Location	Thickness of Slab ¹ (in.)	Depth of Void ¹ Encountered (in.)	Subsoil Conditions ¹	Thickness of Asphalt Overlay (in.)	Comments
1	14.572	L3	260057	APPROACH				5.3	
2	12.233	L3	260055	APPROACH				4.2	
3	11.042	L3	260054	APPROACH				4.2	
4	9.740	L3	260063	APPROACH				4.3	
5	9.743	R3	260079	LEAVE				4.4	
6	14.523	L1	260057	LEAVE				2.4	
7	12.203	L1	260055	LEAVE				4.0	
8	10.998	L1	260054	LEAVE				1.8	1.8 in. CRACK
9	9.700	L1	260063	LEAVE				2.3	
10	9.702	R1	260079	APPROACH				2.0	
11	11.000	R1	260080	APPROACH				2.7	
12	12.203	R1	260081	APPROACH				2.3	
13	14.517	R1	260082	APPROACH				4.3	
14	11.046	R3	260080	LEAVE				4.5	
15	12.235	R3	260081	LEAVE				4.5	MODERATE RAVELING
16	14.563	R3	260082	LEAVE				4.4	

NOTES: 1. CORED TO TOP OF CONCRETE PER FDOT.