

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 3/31/2020 Page: 1 of 3 Typical Section No.: 1

Roadway Section: 29180000	Name: SR 93 (I-75) FROM SR 8 (I-10) TO SUWANNEE C/L			Lanes: 6	
Fin. Proj. ID: 446045-1-52-01	From: SR 8 (I-10)			Shoulder Type and Condition:	
F. A. Proj. No.:	To: SUWANNEE C/L			Inside: PAVED	
County: COLUMBIA	SR No.: SR 93 (I-75)	Beg MP: 27.379	End MP: 30.447	Lgth: 3.068	Outside: PAVED
Median Curbed (Y / N): N	Paved	(X) Lawn	Other:	Curb & Gutter (Y / N): N	

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)						Core Lgth. (in.)	Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top SP12.5	ARMI	S	T1	BIND		LR	Depth (in.)	Type	Class	Extent						
1	27.500	R1	I	1.0	4.7					5.7	--					P				LIGHT RAVELING, SPALLING	
2	28.000	R1	O	0.8	6.0					6.8	12.2					P				LIGHT RAVELING, SPALLING	
3	28.500	R1	I	0.8	7.0					7.8	--					P				LIGHT RAVELING, SPALLING	
4	29.000	R1	N	0.9	7.9					8.8	--					P				LIGHT RAVELING, SPALLING	
5	29.500	R1	I	1.0	5.9					6.9	--					P				LIGHT RAVELING, SPALLING	
6	30.000	R1	O	1.0	5.7					6.7	17.3					P				LIGHT RAVELING, SPALLING	
7	30.440	R1	I	1.2	6.7					7.9	--					P				LIGHT RAVELING, SPALLING	
8	27.400	R3	I	1.0	4.8	0.5	1.8	1.7	2.6	12.4	--					P				LIGHT RAVELING, SPALLING	
9	27.900	R3	O	0.8	5.0	0.5	1.1	2.0	2.3	11.7	--					P				LIGHT RAVELING, SPALLING, MECHANICAL SEPARATION AT 3.0 in.	
10	28.400	R3	N	0.9	5.1	0.5	2.3	1.8	2.5	13.1	--					P				LIGHT RAVELING, SPALLING	
11	28.900	R3	O	0.7	4.6	0.5	0.5	1.5	2.5	10.3	--					P				LIGHT RAVELING, SPALLING	
12	29.400	R3	N	0.7	5.8	0.5	1.2	1.8	2.7	12.7	--					P				LIGHT RAVELING, SPALLING	
13	29.900	R3	O	0.9	5.6	0.5	1.4	1.7	2.7	12.8	--					P				LIGHT RAVELING, SPALLING	
14	30.400	R3	I	0.6	5.8	0.5	2.7	1.5	2.8	13.9	10.6					P				LIGHT RAVELING, SPALLING	
15	27.400	L1	N	0.8	5.4					6.2	--					P				LIGHT RAVELING, SPALLING	
16	27.900	L1	I	0.9	6.4					7.3	--					P				LIGHT RAVELING, SPALLING	
17	28.400	L1	O	0.9	6.0					6.9	16.1					P				LIGHT RAVELING, SPALLING	
18	28.900	L1	I	0.9	6.7					7.6	--					P				LIGHT RAVELING, SPALLING	

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.

2. MP 28.280 - 28.311: MATENANCE PATCH IN R3.

3. MP 30.172 - 30.192: MAINTENANCE PATCH IN R3.

4. MP 30.434 - 30.447: MAINTENANCE PATCH IN L3.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 3/31/2020 Page: 2 of 3 Typical Section No.: 1

Roadway Section: 29180000	Name: SR 93 (I-75) FROM SR 8 (I-10) TO SUWANNEE C/L	Lanes: 6			
Fin. Proj. ID: 446045-1-52-01	From: SR 8 (I-10)	Shoulder Type and Condition:			
F. A. Proj. No.:	To: SUWANNEE C/L	Inside: PAVED			
County: COLUMBIA	SR No.: SR 93 (I-75)	Beg MP: 27.379	End MP: 30.447	Lgth: 3.068	Outside: PAVED
Median Curbed (Y / N): N	Paved	(X) Lawn	Other:	Curb & Gutter (Y / N): N	

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)							Core Lgth. (in.)	Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top SP12.5	ARMI	S	T1	BIND	LR		Depth (in.)	Type	Class	Extent							
19	29.400	L1	N	1.0	6.7					7.7	--					P				LIGHT RAVELING, SPALLING		
20	29.900	L1	I	0.9	6.3					7.2	--					P				LIGHT RAVELING, SPALLING		
21	30.400	L1	N	1.0	6.6					7.6	16.4					P				LIGHT RAVELING, SPALLING		
22	27.500	L3	N	1.3	5.0	0.5	0.9	1.4	2.7	11.8	--					P				LIGHT RAVELING, SPALLING		
23	28.000	L3	I	0.5	6.2	0.5	2.6	1.4	2.7	13.9	10.6					P				LIGHT RAVELING, SPALLING		
24	28.500	L3	O	0.7	5.0	0.5	2.7	1.5	2.6	13.0	--	0.70	B	II	L	P				LIGHT RAVELING, SPALLING		
25	29.000	L3	O	0.9	4.9	0.5			2.2	8.5	--					P				LIGHT RAVELING, SPALLING		
26	29.510	L3	O	1.1	4.8	0.5	2.0	1.4	2.7	12.5	--					P				LIGHT RAVELING, SPALLING		
27	30.000	L3	O	0.8	5.2	0.5	1.2	1.5	2.7	11.9	14.1					P				LIGHT RAVELING, SPALLING		
28	30.440	L3	N	0.8	4.5	0.5	0.5	1.5	2.5	10.3	--					P				LIGHT RAVELING, PATCH, SPALLING		
29	27.500	IR	N		2.4					2.4	--					F				LIGHT RAVELING		
30	28.500	IR	N		4.5					4.5	--					F				LIGHT RAVELING		
31	29.500	IR	N		3.6					3.6	13.4					F				LIGHT RAVELING		
32	30.440	IR	N		4.2					4.2	--					F				LIGHT RAVELING		
33	27.900	OR	N		1.4		4.5		0.7	6.8	8.2					F				LIGHT RAVELING		
34	28.900	OR	N		1.7		3.3		0.6	5.6	--					F				LIGHT RAVELING		
35	29.900	OR	N		1.9		5.0		0.6	7.5	--					F				LIGHT RAVELING		
36	27.900	IL	N		4.5					4.5	11.1					F				LIGHT RAVELING		

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.

2. MP 28.280 - 28.311: MATENANCE PATCH IN R3.

3. MP 30.172 - 30.192: MAINTENANCE PATCH IN R3.

4. MP 30.434 - 30.447: MAINTENANCE PATCH IN L3.

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 3/31/2020 Page: 3 of 3 Typical Section No.: 1

Roadway Section:	29180000	Name:	SR 93 (I-75) FROM SR 8 (I-10) TO SUWANNEE C/L			Lanes:	6
Fin. Proj. ID:	446045-1-52-01	From:	SR 8 (I-10)			Shoulder Type and Condition:	
F. A. Proj. No.:		To:	SUWANNEE C/L			Inside:	PAVED
County:	COLUMBIA	SR No.:	SR 93 (I-75)	Beg MP:	27.379	End MP:	30.447
				Lgth:	3.068	Outside:	PAVED
Median Curbed (Y / N):	N		Paved	(X) Lawn	Other:		Curb & Gutter (Y / N): N

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)							Core Lgth. (in.)	Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top SP12.5	ARMI	S	T1	BIND	LR		Depth (in.)	Type	Class	Extent							
37	28.900	IL	N		3.3					3.3	--					F				LIGHT RAVELING		
38	29.900	IL	N		4.4					4.4	--					F				LIGHT RAVELING		
39	27.500	OL	N		2.1		4.3		0.7	7.1	--					F				LIGHT RAVELING		
40	28.500	OL	N		2.7		4.5		1.0	8.2	--					F				LIGHT RAVELING		
41	29.510	OL	N		2.6		2.5	2.0	0.6	7.7	15.3					F				LIGHT RAVELING		
42	30.440	OL	N		1.2		2.5		0.7	4.4	--					F				LIGHT RAVELING		
43	28.311	R3	O	1.0	4.4	0.5	1.7	1.6	2.8	12.0	13.0					P				MODERATE RAVELING, RAVELED AREA, SPALLING		
44	29.623	R3	O	0.5	5.5	0.5	1.0	1.5	2.3	11.3	--					P				MODERATE RAVELING, POSSIBLE FUEL LEAK OWP, SPALLING		
45	30.175	R3	O	0.5	4.9	0.5	1.6	1.5	2.5	11.5	13.5					P				PATCH		
46	28.290	R3	O	0.9	4.6	0.5	1.8	1.5	2.2	11.5	--					P				PATCH		

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
2. MP 28.280 - 28.311: MATENANCE PATCH IN R3.

3. MP 30.172 - 30.192: MAINTENANCE PATCH IN R3.
4. MP 30.434 - 30.447: MAINTENANCE PATCH IN L3.