

**TABLE 1**  
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION  
**PAVEMENT EVALUATION CORING AND CONDITION DATA**

675-030-09  
Materials  
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 11/16/2020 Page: 1 of 2 Typical Section No.: 1

Roadway Section: 34010000	Name: SR 500 (US 27A)	Lanes: 4
Fin. Proj. ID: 445491-1-52-01	From: BEGIN CURB AND GUTTER	Shoulder Type and Condition:
F. A. Proj. No.:	To: END CURB AND GUTTER	Inside: PAVED
County: LEVY	SR No.: SR 500 (US 27A)	Beg MP: 22.327 End MP: 23.269 Lgth: 0.942
Median Curbed (Y / N): N	(X) Paved	Lawn Other: Curb & Gutter (Y / N): Y

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)						Core Lgth. (in.)	Base (in.) <sup>1</sup>		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top	FC12.5	SP12.5	T1	T2	BIND		ST	LR	Depth (in.)	Type	Class	Extent					
1	22.300	R1	N	1.0	3.0					4.0	7.0					P				MODERATE RAVELING, SPALLING	
2	22.700	R1	N	1.6	2.7					4.3	--					P				MODERATE RAVELING, SPALLING	
3	23.000	R1	I	1.5	2.5					4.0	--	4.00	B	IB	L	P				MODERATE RAVELING, SPALLING	
4	23.200	R1	O	1.5	2.5			1.1		5.1	--					F				MODERATE RAVELING, SPALLING	
5	22.400	R2	N	1.2	1.0					2.2	--	2.20	B	II	M	P				MODERATE RAVELING, SPALLING	
6	22.615	R2	N	0.8	0.9				0.6	2.3	--	2.30	B	II	M	P				GRINDING, MODERATE RAVELING, SPALLING	
7	22.900	R2	N	1.2	0.6					1.8	8.8	1.80	B	III	M	P				MODERATE RAVELING, SPALLING	
8	23.247	R2	O	1.2	2.3					3.5	--	3.50	B	II	M	P				LIGHT RAVELING, TRANSVERSE CRACK	
9	22.400	L1	O	1.6	1.9					3.5	--					F				MODERATE RAVELING, SPALLING	
10	22.615	L1	O	1.3	2.5				0.7	4.5	9.5					F				MODERATE RAVELING, SPALLING	
11	22.900	L1	I	1.4	2.0		0.6		0.8	4.8	--					F				MODERATE RAVELING, SPALLING	
12	23.260	L1	I	0.5	3.6					4.1	--	2.40	B	II	M	P				MODERATE RAVELING, SPALLING	
13	22.300	L2	I	0.6	3.1					3.7	10.0	3.70	B	IB	L	F				MODERATE RAVELING, SPALLING	
14	22.700	L2	O	0.3	1.6				0.7	2.6	--					P				LIGHT RAVELING, SPALLING	
15	23.000	L2	O	0.3	1.6					1.9	--					P				MODERATE RAVELING, SPALLING	
16	23.194	L2	N	0.7	1.1	0.8		1.9		4.5	--	4.50	B	IB	L	F				MODERATE RAVELING, SPALLING	
17	23.247	OR	N	1.3	3.1					4.4	--					F				MODERATE RAVELING, SPALLING	
18	23.260	OL	N	0.5	6.4					6.9	--					P				SEVERE RAVELING, SPALLING	

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.

2. MP 23.242: PAVEMENT CHANGE.

**TABLE 1**  
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION  
**PAVEMENT EVALUATION CORING AND CONDITION DATA**

675-030-09  
Materials  
3/13

Cored by: E. PUCKETT, ENVIRONMENTAL AND GEOTECHNICAL SPECIALISTS, INC. (EGS) Date: 11/16/2020 Page: 2 of 2 Typical Section No.: 1

Roadway Section: 34010000		Name: SR 500 (US 27A)		Lanes: 4	
Fin. Proj. ID: 445491-1-52-01		From: BEGIN CURB AND GUTTER		Shoulder Type and Condition:	
F. A. Proj. No.:		To: END CURB AND GUTTER		Inside: PAVED	
County: LEVY	SR No.: SR 500 (US 27A)	Beg MP: 22.327	End MP: 23.269	Lgth: 0.942	Outside: CURB AND GUTTER
Median Curbed (Y / N): N		(X) Paved		Lawn	Other:
				Curb & Gutter (Y / N): Y	

Core No.	Milepost	Lane	Wheel Path	Pavement Layer (in.)				Base (in.) <sup>1</sup>	Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Cross Slope Direct.	PROJECT COMMENTS
				Top			Core Lgth. (in.)	LR	Depth (in.)	Type	Class	Extent					
19	22.700	CTL	N	1.5	3.2		4.7	--					F				MODERATE RAVELING, SPALLING
20	23.100	CTL	N	1.5	2.8		4.3	--					F				MODERATE RAVELING, SPALLING
21	22.524	LTO	N	1.4			1.4	--					F				MAIN STREET, MODERATE RAVELING
22	22.793	RTO	N	1.6		1.1	2.7	--					F				CR 337, MODERATE RAVELING
23	22.896	LTO	N	1.5		0.8	2.3	--					F				COURT STREET, MODERATE RAVELING
24	23.022	RTO	N	1.3			1.3	--					F				GILBERT STREET, MODERATE RAVELING
25	23.112	LTO	N	1.7		0.6	2.3	--					F				PINE STREET, MODERATE RAVELING

**NOTES:** 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.

2. MP 23.242: PAVEMENT CHANGE.