State of Florida Department of Transportation PAVEMENT EVALUATION CORING AND CONDITION DATA SHEET

| Co | red/Log | ged By: | | | | | | | | LC Date: 10/24/2023 | | | | | | Page: | | 1 | of | | 1 | Typical Section No.: 1 | |
|---------------------------|--------------|---------|---------------------------|---------|---------|-----|-----------|---------------|-------|---------------------|----------------------|----------|---------------------|----------------|---------|-------|--------|-------|--------------------------|------------------------------------|-----------------------------|--|--|
| Roadway Section: 72010000 | | | | | 0000 | | | | | SR 10 |) (US 90) | Beaver S | treet | | | | | | | Lanes: 2 | | | |
| FIN Proj | | | 209568-2 From: | | | | | | | | | | | | | | | | | Shoulder Type and Condition: Paved | | | |
| | Project N | o.: | N/A To: | | | | | To: | | | | | | | | | | | | Inside: N | | | |
| County: Duval | | | SR No.: SR 10 | | | | Begin MP: | | 7.980 | | End MP: | | 8.269 | | Length: | | 0.289 | | Outside: 5' | | | | |
| Median Curbed (Y / N): N | | | () Paved () Lawn | | | | Other: | | | | | | | | | | | | Curb & Gutter (Y / N): N | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | |
| CORE NO. | MILE POST | LANE | WHEEL PATH (Y or N) | PAVEMEN | | | | T LAYER (in.) | | | | | BASE | | CRACK | | | PAVT. | | CROSS | | | |
| | | | | FC 12.5 | SP 12.5 | s | | | | | CORE LENGTH (in.) | TYPE | THICK-NESS (in.) | DEPTH (in.) | TYPE | CLASS | EXTENT | COND. | | SLOPE (%) | DIRECTION (I=in / O=out) | COMMENTS | |
| 1 | 8.225 | R1 | Y | 1.5 | 2.5 | 3.4 | | | | | 7.4 | CONC | - | | | | | G | | | | | |
| 2 | 8.273 | L1 | Y | 1.5 | 2.7 | 2.8 | | | | | 7.0 | LR | - | 1.2 | В | IB | L | Р | | | | POSSIBLE CRACK RELIEF LAYER, SHOVING | |
| 3 | 8.197 | L1 | Y | 1.2 | 3.0 | | | | | | 4.2 | ABC | 5.2 | | | | | G | | | | WIDENING | |
| 4 | 8.086 | LRTTL | Y | 1.5 | 2.0 | | | | | | 3.5 | ABC | 5.9 | | | | | G | | | | | |
| 5 | 8.225 | OR | N | 1.5 | 1.5 | | | | | | 3.0 | ABC | 3.6 | | | | | G | | | | 43" FROM WHITE LINE | |
| 6 | 8.273 | OL | N | 1.5 | 1.5 | | | | | | 3.0 | ABC | 4.6 | | | | | G | | | | | |
| 7 | 8.197 | OL | N | 1.5 | 1.5 | | | | | | 3.0 | ABC | 6.4 | | | | | G | | | | | |
| 8 | 8.086 | OL | N | 1.5 | 1.2 | | | | | | 2.7 | ABC | 2.5 | | | | | G | | | | 32" FROM WHITE LINE | |
| 9 | 170' | RP- L2 | Y | 1.5 | 2.8 | | | | | | 4.3 | LR | - | | | | | G | | | | MEASURED IN FT FROM ON RAMP BULLNOSE | |
| 10 | 170' | OL | N | 1.5 | 1.9 | | | | | | 3.4 | LR | - | | | | | G | | | | MEASURED IN FT FROM ON RAMP BULLNOSE | |
| 11 | 568' | RP-L1 | Y | 1.5 | 3.9 | | | | | | 5.4 | LR | 11.4 | | | | | G | | | | MEASURED IN FT FROM ON RAMP BULLNOSE | |
| 12 | 1514' | RP -L1 | Y | 1.5 | 3.1 | | | | | | 4.6 | LR | - | | | | | G | | | | MEASURED IN FT FROM ON RAMP BULLNOSE | |
| 13 | 568' | IL | N | 1.8 | 1.9 | | | | | | 3.7 | LR | - | | | | | G | | | | MEASURED IN FT FROM ON RAMP BULLNOSE,42" F | |
| 14 | 1514' | IL | Ν | 1.5 | 2.3 | | | | | | 3.8 | LR | 9.5 | | | | | G | | | | MEASURED IN FT FROM ON RAMP BULLNOSE,39" F | |
| | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | |