

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: J. NELSON Date: 11/30/17 Page: 1 of 6 Typical Section No.: 1

Roadway Section: 74040000				Name: SR 200				Lanes: 4			
Fin. Proj. ID: 441260-1-52-01				From: STRATTON ROAD				Shoulder Type and Condition:			
F. A. Proj. No.:				To: GRIFFIN ROAD				Inside: PAVED			
County: NASSAU		SR No.: SR 200		Beg MP: 16.053		End MP: 22.183		Lgth: 6.130		Outside: PAVED	
Median Curbed (Y / N): Y				Paved		(X) Lawn		Other:		Curb & Gutter (Y / N): Y	

Core No.	Milepost	Lane	Wheel Path (Y / N)	Pavement Layer (in.)							Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope	Cross Slope Direct.	PROJECT COMMENTS	
				Top FC5	Top PATCH	Top FC6	SP2C	T2	ST	Core Lgth. (in.)	LR	ABC	Depth (in.)	Type	Class	Extent						
1	16.100	R1	Y			1.4	3.0				4.4		7.4					F				LIGHT RAVELING
2	16.545	R1	N			2.0	1.2				3.2	--						F				LIGHT RAVELING
3	17.100	R1	N			1.5	2.8				4.3		5.8					F				LIGHT RAVELING
4	17.600	R1	Y			1.5	2.0				3.5	--						F				LIGHT RAVELING, SEPARATION AT 1.5in.
5	18.090	R1	Y			1.6	1.6				3.2	--		3.20	B	IB	M	P				LIGHT RAVELING, LONGITUDINAL CRACK, SPALLING
6	18.615	R1	Y	1.0			3.3				4.3	--						F				LIGHT RAVELING
7	19.125	R1	N	0.8			2.9				3.7	--						F				LIGHT RAVELING
8	19.600	R1	N	0.8			3.1				3.9	--						F				LIGHT RAVELING
9	20.080	R1	Y	1.1			3.1				4.2	--						F				LIGHT RAVELING
10	20.600	R1	N	0.9			2.9				3.8	--						F				LIGHT RAVELING
11	21.100	R1	Y	1.0			2.9				3.9	--						F				LIGHT RAVELING
12	21.600	R1	N	1.1			2.9				4.0	--						F				LIGHT RAVELING
13	16.316	R2	Y			1.3	1.5				2.8	--		2.80	A	II	S	P				LIGHT RAVELING, SPALLING
14	16.800	R2	Y			1.5	2.1				3.6	--		1.50	B	IB	M	P				LIGHT RAVELING, LONGITUDINAL CRACK, SPALLING
15	17.356	R2	Y		1.8	1.6	1.4				4.8	--						P				3.3 in. BOTTOM-UP CRACK, PATCH
16	17.800	R2	Y			1.3	2.3				3.6	--		3.60	A	IB	M	P				LIGHT RAVELING, SPALLING

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.

2. CURVE IS SUPERELEVATED

3. MP 17.356: PATCH

4. MP 18.406: CURB AND GUTTER ENDS

5. MP 18.600: INSIDE CURB ENDS

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: J. NELSON Date: 11/30/17 Page: 2 of 6 Typical Section No.: 1

Roadway Section: 74040000				Name: SR 200				Lanes: 4			
Fin. Proj. ID: 441260-1-52-01				From: STRATTON ROAD				Shoulder Type and Condition:			
F. A. Proj. No.:				To: GRIFFIN ROAD				Inside: PAVED			
County: NASSAU		SR No.: SR 200		Beg MP: 16.053		End MP: 22.183		Lgth: 6.130		Outside: PAVED	
Median Curbed (Y / N): Y				Paved		(X) Lawn		Other:		Curb & Gutter (Y / N): Y	

Core No.	Milepost	Lane	Wheel Path (Y / N)	Pavement Layer (in.)							Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope	Cross Slope Direct.	PROJECT COMMENTS	
				Top FC5	Top PATCH	Top FC6	SP2C	T2	ST	Core Lgth. (in.)	LR	ABC	Depth (in.)	Type	Class	Extent						
17	18.315	R2	Y			1.7	1.8				3.5		5.7	2.20	B	IB	M	P				LIGHT RAVELING, LONGITUDINAL CRACK, SPALLING
18	18.800	R2	Y	0.5			3.0				3.5	--		2.80	B	II	M	P				GRINDING, MODERATE RAVELING, SPALLING, TRANSVERSE CRACK
19	19.300	R2	Y	1.0			2.2				3.2	--		3.20	B	II	M	P				GRINDING, MODERATE RAVELING, SPALLING, TRANSVERSE CRACK
20	19.800	R2	Y	0.7			3.3				4.0	--						F				LIGHT RAVELING
21	20.300	R2	Y	1.0			2.7				3.7	--		3.70	B	II	M	P				GRINDING, LIGHT RAVELING, SPALLING, TRANSVERSE CRACK
22	20.800	R2	Y	0.7			3.3				4.0	--						F				LIGHT RAVELING
23	21.300	R2	Y	0.9			2.7				3.6	--		3.60	B	II	M	P				GRINDING, LIGHT RAVELING, SPALLING, TRANSVERSE CRACK
24	21.800	R2	N	1.0			3.4				4.4	--						F				LIGHT RAVELING
25	16.300	L1	Y	1.5			2.5				4.0	--		0.80	B	IB	M	P				LIGHT RAVELING, LONGITUDINAL CRACK
26	16.800	L1	Y		1.4		1.4				2.8	--						F				LIGHT RAVELING
27	17.300	L1	Y		1.4		2.4				3.8		5.2					F				LIGHT RAVELING
28	17.800	L1	Y		1.7		1.5				3.2	--						F				LIGHT RAVELING
29	18.300	L1	Y		2.1		2.5				4.6		4.7	0.70	B	IB	L	P				LIGHT RAVELING, LONGITUDINAL CRACK
30	18.700	L1	N	1.0			4.6	1.3	1.8		8.7	--						F				LIGHT RAVELING
31	19.300	L1	Y	0.7			8.5	1.5	1.8		12.5	--						F				LIGHT RAVELING
32	19.800	L1	N	0.7			6.0	0.6	1.5		8.8	--						F				LIGHT RAVELING

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.

2. CURVE IS SUPERELEVATED

3. MP 17.356: PATCH

4. MP 18.406: CURB AND GUTTER ENDS

5. MP 18.600: INSIDE CURB ENDS

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: J. NELSON Date: 11/30/17 Page: 3 of 6 Typical Section No.: 1

Roadway Section: 74040000				Name: SR 200				Lanes: 4			
Fin. Proj. ID: 441260-1-52-01				From: STRATTON ROAD				Shoulder Type and Condition:			
F. A. Proj. No.:				To: GRIFFIN ROAD				Inside: PAVED			
County: NASSAU		SR No.: SR 200		Beg MP: 16.053		End MP: 22.183		Lgth: 6.130		Outside: PAVED	
Median Curbed (Y / N): Y				Paved		(X) Lawn		Other:		Curb & Gutter (Y / N): Y	

Core No.	Milepost	Lane	Wheel Path (Y / N)	Pavement Layer (in.)							Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top PATCH	Top FC6	SP2C	T2	ST	Core Lgth. (in.)	LR	ABC	Depth (in.)	Type	Class	Extent					
33	20.300	L1	N	1.0			4.6	1.0	1.8	8.4	--					F				LIGHT RAVELING	
34	20.700	L1	Y	0.8			7.2	2.9	2.1	13.0	7.0					F				LIGHT RAVELING	
35	21.300	L1	N	0.7			5.4	2.7	2.1	10.9	--					F				LIGHT RAVELING	
36	21.800	L1	Y	0.7			2.8			3.5	--					F				LIGHT RAVELING	
37	16.100	L2	N			1.7	1.8			3.5		8.7				P				LIGHT RAVELING	
38	16.600	L2	Y			1.8	1.3			3.1	--		2.50	B	IB	M	P			LIGHT RAVELING, SPALLING, TRANSVERSE CRACK	
39	17.100	L2	Y			1.3	2.1			3.4		7.0	1.40	B	IB	M	P			LIGHT RAVELING, LONGITUDINAL CRACK, SPALLING	
40	17.600	L2	Y			1.2	1.6			2.8	--		2.80	B	IB	M	P			GRINDING, LIGHT RAVELING, SPALLING, TRANSVERSE CRACK	
41	18.100	L2	Y			1.4	1.7			3.1	--		2.00	B	IB	M	P			LIGHT RAVELING, LONGITUDINAL CRACK, SPALLING	
42	18.600	L2	Y	1.1			2.4			3.5		8.6					F			LIGHT RAVELING	
43	19.111	L2	N	1.0			2.9	1.3	1.5	6.7	--						F			LIGHT RAVELING	
44	19.600	L2	Y	0.7			8.8			9.5	--						F			LIGHT RAVELING	
45	20.100	L2	N	1.0			3.4	1.4	1.2	7.0	--						F			0.9in. BOTTOM-UP CRACK, LIGHT RAVELING	
46	20.600	L2	N	0.6			5.3		0.5	6.4	--						F			LIGHT RAVELING	
47	21.100	L2	Y	0.6			4.6	2.1	1.8	9.1	7.0						F			LIGHT RAVELING	
48	21.600	L2	Y	0.6			3.2	1.5	2.1	7.4	--						F			LIGHT RAVELING	

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.

2. CURVE IS SUPERELEVATED

3. MP 17.356: PATCH

4. MP 18.406: CURB AND GUTTER ENDS

5. MP 18.600: INSIDE CURB ENDS

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: J. NELSON Date: 11/30/17 Page: 4 of 6 Typical Section No.: 1

Roadway Section: 74040000				Name: SR 200				Lanes: 4			
Fin. Proj. ID: 441260-1-52-01				From: STRATTON ROAD				Shoulder Type and Condition:			
F. A. Proj. No.:				To: GRIFFIN ROAD				Inside: PAVED			
County: NASSAU		SR No.: SR 200		Beg MP: 16.053		End MP: 22.183		Lgth: 6.130		Outside: PAVED	
Median Curbed (Y / N): Y				Paved		(X) Lawn		Other:		Curb & Gutter (Y / N): Y	

Core No.	Milepost	Lane	Wheel Path (Y / N)	Pavement Layer (in.)							Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top PATCH	Top FC6	SP2C	T2	ST	Core Lgth. (in.)	LR	ABC	Depth (in.)	Type	Class	Extent					
49	16.316	OR	N			1.9	2.8				4.7	--					F				LIGHT RAVELING
50	17.356	OR	N			2.2	7.7				9.9	--					F				LIGHT RAVELING
51	18.315	OR	N			2.4	2.2				4.6		5.7				F				LIGHT RAVELING
52	19.300	OR	N	0.8			2.1				2.9	--					F				LIGHT RAVELING
53	20.300	OR	N	1.1			2.3				3.4	--					F				LIGHT RAVELING
54	21.300	OR	N	1.0			1.4				2.4	--					F				LIGHT RAVELING
55	18.615	IR	N	1.1			2.2				3.3	10.0					F				LIGHT RAVELING
56	19.600	IR	N	0.9			2.4				3.3	--					F				LIGHT RAVELING
57	20.600	IR	N	0.7			2.3				3.0	--					F				LIGHT RAVELING
58	17.100	OL	N			1.8	1.9				3.7		6.9				F				LIGHT RAVELING
59	18.100	OL	N			1.8	2.0				3.8	--					F				LIGHT RAVELING
60	18.600	OL	N	1.8			2.5				4.3	--					F				LIGHT RAVELING
61	20.100	OL	N	1.3			2.0				3.3		10.2				F				LIGHT RAVELING
62	21.100	OL	N	1.0			1.8				2.8		4.8				F				LIGHT RAVELING
63	18.700	IL	N	0.8			1.2				2.0	--					F				LIGHT RAVELING
64	19.800	IL	N	0.8			1.4				2.2	5.0					F				LIGHT RAVELING

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.

2. CURVE IS SUPERELEVATED

3. MP 17.356: PATCH

4. MP 18.406: CURB AND GUTTER ENDS

5. MP 18.600: INSIDE CURB ENDS

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: J. NELSON Date: 11/30/17 Page: 5 of 6 Typical Section No.: 1

Roadway Section: 74040000				Name: SR 200				Lanes: 4				
Fin. Proj. ID: 441260-1-52-01				From: STRATTON ROAD				Shoulder Type and Condition:				
F. A. Proj. No.:				To: GRIFFIN ROAD				Inside: PAVED				
County: NASSAU		SR No.: SR 200		Beg MP: 16.053		End MP: 22.183		Lgth: 6.130		Outside: PAVED		
Median Curbed (Y / N): Y				Paved		(X) Lawn		Other:		Curb & Gutter (Y / N): Y		

Core No.	Milepost	Lane	Wheel Path (Y / N)	Pavement Layer (in.)							Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope	Cross Slope Direct.	PROJECT COMMENTS
				Top FC5	Top PATCH	Top FC6	SP2C	T2	ST	Core Lgth. (in.)	LR	ABC	Depth (in.)	Type	Class	Extent					
65	20.760	IL	N	1.3			1.7				3.0	--					F				LIGHT RAVELING
66	16.141	CTL	Y			1.1	3.1				4.2		6.6				F				LIGHT RAVELING, PARABOLIC CROWN
67	16.454	RLTTL	N			1.2	1.3				2.5	--					F				LIGHT RAVELING
68	16.924	RLTTL	N			1.2	3.3				4.5		5.6				F				LIGHT RAVELING
69	17.600	RLTTL	Y			1.2	1.8				3.0	--					F				LIGHT RAVELING
70	19.126	RLTTL	Y	0.6			3.3				3.9	--					F				LIGHT RAVELING
71	22.085	RLTTL	Y	1.3			2.9				4.2	--					F				LIGHT RAVELING
72	21.123	LLTTL	Y	0.7			3.5				4.2	--					F				LIGHT RAVELING
73	19.167	LLTTL	N	1.4			4.7				6.1	--					F				LIGHT RAVELING
74	18.428	LLTTL	N	0.9			2.5				3.4	--					F				LIGHT RAVELING
75	17.233	LLTTL	N			1.5	1.6				3.1		6.4				F				LIGHT RAVELING
76	16.793	TO	Y			1.9	2.3				4.2	--					F				LIGHT RAVELING
77	18.394	TO	N			1.4	1.8				3.2		6.3				F				LIGHT RAVELING
78	19.085	TO	N	0.7			3.3				4.0	--					F				LIGHT RAVELING
79	21.024	TO	Y	0.7			1.4				2.1	--					F				LIGHT RAVELING
80	16.302	CO	N			1.1	3.0				4.1	--					F				LIGHT RAVELING, PARABOLIC CROWN

NOTES: 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.

2. CURVE IS SUPERELEVATED

3. MP 17.356: PATCH

4. MP 18.406: CURB AND GUTTER ENDS

5. MP 18.600: INSIDE CURB ENDS

TABLE 1
STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-030-09
Materials
3/13

Cored by: J. NELSON Date: 11/30/17 Page: 6 of 6 Typical Section No.: 1

Roadway Section: 74040000				Name: SR 200				Lanes: 4				
Fin. Proj. ID: 441260-1-52-01				From: STRATTON ROAD				Shoulder Type and Condition:				
F. A. Proj. No.:				To: GRIFFIN ROAD				Inside: PAVED				
County: NASSAU		SR No.: SR 200		Beg MP: 16.053		End MP: 22.183		Lgth: 6.130		Outside: PAVED		
Median Curbed (Y / N): Y				Paved		(X) Lawn		Other:		Curb & Gutter (Y / N): Y		

Core No.	Milepost	Lane	Wheel Path (Y / N)	Pavement Layer (in.)							Base (in.) ¹		Crack				Pvmt Cond	Rut Depth (in.)	Cross Slope	Cross Slope Direct.	PROJECT COMMENTS	
				Top FC5	Top PATCH	Top FC6	SP2C	T2	ST	Core Lgth. (in.)	LR	ABC	Depth (in.)	Type	Class	Extent						
81	18.777	CO	N			1.7	1.7				3.4	--					F				LIGHT RAVELING	
82	19.335	CO	N			1.7	1.9				3.6	--					F				PARABOLIC CROWN	
83	16.468	R2	Y			0.8	1.8				2.6	10.0		2.60	A	IB	S	P				
84	18.411	R2	Y	1.4			2.9				4.3	--		4.30	A	II	S	P				INSIDE WHEELPATH
85	21.900	R2	Y	0.8			3.1				3.9	--					F				LIGHT RAVELING	
86	22.100	L2	N	0.7			3.1				3.8	--					F				LIGHT RAVELING	
87	22.085	R1	N	1.1			2.8				3.9	--					F				LIGHT RAVELING	
88	21.900	L1	Y	0.8			3.2				4.0	--					F				LIGHT RAVELING	
89	21.900	OR	N	0.7			2.1				2.8	--					F				LIGHT RAVELING	
90	21.900	IL	N	1.0			1.2				2.2	--					F				LIGHT RAVELING	

- NOTES:** 1. DASHES INDICATE BASE WAS ENCOUNTERED BUT THICKNESS WAS NOT MEASURED.
2. CURVE IS SUPERELEVATED
3. MP 17.356: PATCH
4. MP 18.406: CURB AND GUTTER ENDS
5. MP 18.600: INSIDE CURB ENDS