

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: **J. NELSON** Date: **04/05/18** Page: **1** of **3** Typical Section No.: **--**

Roadway Section:	46160000	Name:	SR 30A (PANAMA CITY BEACH PKWY)	Lanes:	4-LANE DIVIDED
Fin. Proj. ID:	217836-3-32-01	From:	MANDY LN	Shoulder Type and Condition:	PAVED, GRASS
F. A. Proj. No.:	--	To:	EAST OF NAUTILUS ST	Inside:	GRASS, CURB & GUTTER
County:	BAY	Beg MP:	6.760	Outside:	PAVED
Median Curbed (Y/N):	Y	End MP:	8.879	Curb & Gutter (Y/N):	Y
		Lawn:	Y		
		Other:	--		

Core No.	Mile Post or Sta. No.	Lane	Wheel Path (Y/N)	Pavement Layer (In.)							Base			Crack			Purt Cond	Rut Depth (In.)	Cross Slope (%)	PROJECT COMMENTS					
				Top FCS	FC8	FC9.5	SP2C	SP1C	S3	T2	Core Lght. (In.)	SAND CLAY	LIMEROCK	SBRM	Depth (In.)	Type					Class	Extent			
P-1	6.845	LOTL	Y			1.70		4.20		4.30			10.20		9.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-2	7.032	ROTL	Y			1.10	2.90						4.00		12.00		0.00	A	IB	L	GOOD				NEW PAV
P-3	7.032	R2	Y			1.00		2.00	2.50	1.50			7.00		7.70	8.50	0.00	A	IB	L	GOOD				LIGHT RAV
P-4	7.032	R1	Y			1.00	1.60			3.80	1.20		7.60				0.00	A	IB	L	FAIR				LIGHT RAV
P-5	7.064	LITL	N			1.40	1.50	2.20					5.10		11.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-6	7.064	ROTL	N			1.10	6.30						7.40		10.00		0.00	A	IB	L	FAIR				LIGHT RAV
P-7	7.077	RITL	N			2.00	1.80						3.80		9.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-8	7.234	ROTL	Y			0.80	4.30						5.10		9.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-9	7.264	LOTL	Y			0.80		4.00					4.90		8.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-10	7.264	LITL	N			1.00	4.20						5.20		7.00		0.00	A	IB	L	GOOD				LIGHT RAV, C & G
P-11	7.264	LITL	Y			0.80		1.50	3.40				5.70		8.00		0.00	A	IB	L	GOOD				LIGHT RAV, C & G
P-12	7.428	LOTL	N			1.10	2.80						3.80		17.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-13	7.435	ROTL	N			0.80		3.20					4.00		12.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-14	7.453	RITL	N			1.30	2.70						4.00		13.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-15	7.459	LITL	N			1.90		3.30					5.20		9.00		0.00	A	IB	L	GOOD				LIGHT RAV

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

675-03105
 Modified
 3/13

Cored by: **J. NELSON** Date: **04/05/18** Page: **2** of **3** Typical Section No.: **--**

Roadway Section: **46160000** Name: **SR 30A (PANAMA CITY BEACH PKWY)** Lanes: **4-LANE DIVIDED**
 Fin. Proj. ID: **217836-3-32-01** From: **MANDY LN** Shoulder Type and Condition: **PAVED, GRASS**
 F. A. Proj. No.: **--** To: **EAST OF NAUTILUS ST** Inside: **GRASS, CURB & GUTTER**
 County: **BAY** SR No.: **SR 30A** Beg MP: **6.76** End MP: **8.879** Lght: **2.119** Outside: **PAVED**
 Median Curbed (Y/N): **Y** Paved: **N** Lawn: **Y** Other: **--** Curb & Gutter (Y/N): **Y**

Core No.	Mile Post or Sta. No.	Lane	Wheel Path (Y/N)	Pavement Layer (in.)							Base			Crack			Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	PROJECT COMMENTS							
				Top	FC5	FC6	FC9.5	SP2C	SP1C	S3	T2	SAND CLAY	LIMEROCK	SBRM	Depth (in.)	Type					Class	Extent					
P-16	7.459	L1	Y			1.10	1.60				2.10				4.80		14.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-17	7.610	LOTL	N			1.00	3.10								4.10		13.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-18	7.647	ROTL	N			0.90	6.40								6.30		12.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-19	7.647	LTTL	N			1.10	2.60								3.70		13.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-20	7.647	LTTL	N			1.00	1.10				2.30				4.40		18.00		4.40	B	IB	L	FAIR				LIGHT RAV, BLK CRK AT WIDENING
P-21	7.947	L2	Y			1.10	2.50				2.80				6.40		13.00		0.00	A	IB	L	FAIR				LIGHT RAV
P-22	7.647	LSH	N			1.60	2.20				1.00				4.80		9.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-23	7.734	LOTL	Y			0.80				2.50					3.30		12.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-24	7.809	LTTL	N			1.30	5.10								6.40		10.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-25	7.809	L1	Y			0.90	1.70			2.50					5.10		11.00		0.00	A	IB	L	FAIR				LIGHT RAV
P-26	7.814	R1	Y			1.40	2.10				6.10	1.10			10.70			8.30	0.00	A	IB	L	FAIR				LIGHT RAV
P-27	7.814	RITL	N			1.10					2.80				3.90		12.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-28	7.830	ROTL	N			0.80	3.40								4.20		12.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-29	7.965	LTL	N			1.40				1.40					6.40		9.00		0.00	A	IB	L	GOOD				LIGHT RAV
P-30	7.990	LOTL	Y			1.00	1.40								2.40		10.00		0.00	A	IB	L	GOOD				LIGHT RAV

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: **J. NELSON** Date: **04/05/18** Page: **3** of **3** Typical Section No.: **--**

Roadway Section:	46160000	Name:	SR 30A (PANAMA CITY BEACH PKWY)	Lanes:	4-LANE DIVIDED
Fin. Proj. ID:	217896-3-32-01	From:	MANDY LN	Shoulder Type and Condition:	PAVED, GRASS
F. A. Proj. No.:	--	To:	EAST OF NAUTILUS ST	Inside:	GRASS, CURB & GUTTER
County:	BAY	Beg MP:	6.76	End MP:	8.879
Median Curbed (Y/N):	Y	Lawr:	Y	Other:	--
		Paved:	N	Curb & Gutter (Y/N):	Y
		SR No.:	SR 30A		
		Length:	2.119		

Core No.	Mile Post or Sta. No.	Lane	Wheel Path (Y/N)	Pavement Layer (In.)							Base			Crack			Pvmt Cond	Rut Depth (In.)	Cross Slope (%)	PROJECT COMMENTS
				Top FCS	FC6	FC9.5	SP2C	SP1C	S3	T2	Core Lgh. (In.)	SAND CLAY	LIMEROCK	SBRM	Depth (In.)	Type				
P-31	8.050	RSH	N		1.30							2.80	A	IB	L	FAIR			LIGHT RAV, BLK CRK	
P-32	8.050	R2	Y		1.10	1.50	4.80	0.90	1.60	2.80	0.90	6.30	A	IB	L	FAIR			LIGHT RAV, BLK CRK	
P-33	8.074	ROTL	N				4.80					5.70	A	IB	L	GOOD			LIGHT RAV	
P-34	8.170	L2	Y			1.50	1.50	2.50	1.60	2.50	5.20	A	IB	L	FAIR				LIGHT RAV	
P-35	8.170	LSH	N					0.90	1.60	1.60	3.80	A	IB	L	GOOD				LIGHT RAV	
P-36	8.232	LITL	Y					2.40	6.50	6.50	9.90	A	IB	L	FAIR				LIGHT RAV	
P-37	8.363	ROTL	Y						1.10	1.10	1.90	A	IB	L	FAIR				LIGHT RAV, WIDENING	
P-38	8.363	RITL	Y						3.00	3.00	6.70	A	IB	L	GOOD				LIGHT RAV	
P-39	8.409	LOTL	N					4.70			5.70	A	IB	L	GOOD				LIGHT RAV, ACCEL. LANE	
P-40	8.470	ROTL	N						3.90	3.90	5.00	A	IB	L	GOOD				LIGHT RAV	
P-41	8.528	LOTL	N						3.10	3.10	4.00	A	IB	L	FAIR				LIGHT RAV, LAMINATING (0.7 in.), WIDENING	
P-42	8.536	ROTL	N						3.20	3.20	4.10	A	IB	L	GOOD				LIGHT RAV	
P-43	8.680	LITL	Y						1.70	1.70	2.50	A	IB	L	GOOD				LIGHT RAV	
P-44	8.718	ROTL	N						2.30	2.30	8.10	A	IB	L	FAIR				LIGHT RAV	
P-45	8.724	RITL	Y						1.80	4.80	7.30	A	IB	L	GOOD				LIGHT RAV	